MISC. ORDER NO. 2018 - 36

In the County Court of Craighead County, Arkansas

In the matter of awarding bids for the purchase of two (2) Dump Trucks with dump beds and hydraulics installed And delivered to the Craighead County Road Department.



ORDER

Comes before the County Court of Craighead County, Arkansas, the matter of awarding bids for the purchase of two (2) Dump Trucks with dump beds and hydraulics installed and three (3) year/150,000 mile guaranteed dealer buyback, delivered and to be used by the Craighead County Road Department.

Bids were advertised and publicly opened in accordance with Arkansas Code 14-22-101 through 14-22-115, concerning purchasing and bidding procedures.

It is therefore, considered, ordered, and adjudged that the best bid and overall best value of \$142,650.00 per Freightliner dump truck, with a three year/150,000 mile guaranteed dealer buyback of \$85,600 per dump truck, with a total award of \$285,300.00 be awarded to Tag Truck Center, 5712 Commerce Square, Jonesboro, AR 72401.

Dated this_

Day of May, 2018

Approved:

Ed Hill

Craighead County Judge

FROM:

Craighead County Purchasing Department c/o County Judges Office 511 Union Rm 119 Jonesboro, AR 72401 Phone 870-933-4500 Fax 870-933-4504

PURCHASE ORDER CRAIGHEAD COUNTY ARKANSAS

SHOW THIS NO. ON ALL INVOICES, DELIVERY SLIPS, CASES, BOXES, ETC

PURCHASE ORDER 50767

TO: THO TVUCK CENTEY
5712 COMMENCE Squere
JONES GORIAG 7240/

Gentlemen: Please fumish the following to Craighead County and be governed by the instructions hereon.

DATE 5 - 10 - 18

Req. By Tucy HT//

Req. #

Bld No. 2018-2

Charge to 2000, 200, 4005

ITEM	QUAN.	BRAND, CATALOG NO, AND DESCRIPTION UNIT TOTAL
	2	During Trucks with 125TA/Ad durif lods \$142,650 285,300 2nd Hydraulics and fully operational 2nd delivered to craig had lowner Road Deft. 2800 Micros Ad Junghow, AR 7240 2018 Fretghtliner 114 SD Trucks with 161 0x Body Stanford of Ither distant Automotic transmission
		FINITIVER LEVISITY 12 MONTHS/100,000 miles 1 thor +1017 24 month for oftrational wants Three year / 150,000 mile guaranteed deeper by back of \$85,600 for truck exterior evide ultim hed footh motolit 5/10 Att Actualiza to specs to bid 189 2018-7 1285,300

			TOTAL >	
Crata hood County Road Roft 2800 Moore Rd	DEL. PROMISED	DEL. REQUIRED	TERMS:	
	F.O.B. 105774	26100	PRICING:	
Jones boro, AR 7240/		· - -		
M				

No purchases over \$100.00 are valid unless covered by this form signed by Purchasing Agent. Submit invoice promptly to County Clerk, Craighead County Court House, P.O. Box 1167, Jonesboro, AR 72401. The above Purchase Order No. must appear on all Invoices, Delivery Silps, Cases, Boxes, Etc. even when shipped direct by your supplier.

_										
3	I certify	that	all the	e above	articles	or servi	ces have	been rec	eived in d	ood order
ċ	except			7.5						
			APPENDED !		1900				的过去式	
				, D	ated	Coleman to	10 0 60 y 10 y		20	1. m. 1.
					减少整点 。					373 F 898 5
1	552%		3600		PAGE 1				A BASSA	and VAN STANIS
ł	Signec	2.55			유용함하였다	a kepadibi		4		
-,		34 (5.43). (3		343.73				建设设置		
ļ,						Sala Agin		State of the state	"""我们是我们的	型。主教是主义是

CRAI	GHEAD COUNTY	
	Purchasing Agent	_

		63%		miles. Gross comb wt 80,000#	901-493-6328 Fax 901-366-6859
		Percent of cost		Truck warranty-5 yr 200,000 mile Engine & after treatment	Pat McHugh
		Buyback		Service location, Memphis, TN, Delivery 210 days	Memphis, TN 38118
				Detroit DD13(12.8L)450 HP, Buyback three year/150,000 miles	5278 Hwy 78
\$18,041.00	\$291,246.00	\$91,500.00	\$145,623.00	2019 Western Star 4700 SF,6 speed allison transmission,Ox Dump Body 16' Stamps	Crows Truck Service
					•
		69%		Delivery 60-90 days)Gross comb wt 80,000	
		Percent of cost		Truck warranty-36 months/150,000 miles;	
		Buyback		Buyback three year/150,000 miles. Service location Jonesboro, AR,	Ph 870-273-5079 Fax 972-5862
			l.	Engine MP7-450 HP, Transmission Mack TMD 12 speed(overdrive)60 day del	Jonesboro, AR 72404
\$15,449.00	\$302,694.00	\$105,000.00	\$151,347.00	2019 Mack Granite 64FR,Ox Dump Body 16 ft,Stampede,(eliptical)	1333 E Parker Road
				Engine MP7-425 HP, Transmission Mack TMD 12 speed(overdrive)60 day del	
\$14,253.33	\$295,520.00	\$105,000.00	\$147,760.00	2019 Mack Granite 64FR,Ox Dump Body 16 ft,Stampede,(eliptical)	TriState Truck Center
		63%		warranty. Delivery 150 days. Gross comb wt 80,000#	Ph 972-8588 Fax 972-0223
		Percent of cost		years/200,000, Truck warranty(all)12 months/100,000 miles.Trans 5 yr	12
		Buyback		Service location, Jonesboro, AR. Engine warranty three	Jonesboro, AR 72401
				Detroit DD13(12.8L)450 HP, Buyback three year/150,000 miles	5712 Commerce Square
\$17,811.67	\$290,870.00	\$92,000.00	\$145,435.00	2019 Western Star 4700 SF,6 speed allison transmission,Ox Dump Body 16' Stampe	Tag Truck Center
-		60%		warranty. Delivery 330 days. Gross comb wt 80,000#	Ph 972-8588 Fax 972-0223
		Percent of cost		years/200,000, Truck warranty(all)12 months/100,000 miles.Trans 5 yr	Tony Hickman
		Buyback		Service location, Jonesboro, AR, Engine warranty three	Jonesboro, AR 72401
,				Detroit DD13(12.8L) 450 HP Engine, Buyback three year/150,000 miles	5712 Commerce Square
\$19,016.67	\$285,300.00	\$85,600.00	\$142,650.00	2019 Freightliner 114SD with Ox Body 16ft Stampede, Allison 4500 RDS trans	Tag Truck Center
	Total Cost	per unit 7	Price per unit	ITEM BID	BIDDER NAME
3 yr BuyBack Option	3	Buyback			
per year utilizing		Guaranteed		Jonesboro, AR 72401	
Net cost per vehicle				2800 Moore Rd	DATE: May 2, 2018
				Craighead County Road Dept	County Road Dept
		er buyback	aranteed deale	Purchase two new dump trucks with automatic transmission and 3 year/150,000 guaranteed dealer buyback	Bid 2018-7
				BID TABULATION SHEET	

	CRAIGHEAD COUNTY				T	
	INVITATION TO BID-Not an Order					
	Cralghead County Judge's Office	T			+	
	511 Union St.; Suite 119				+	
	Jonesboro, Arkansas 72401	<u> </u>	 		+	
URCH	ASING OFFICE		 			
ID NO.	2018-7	DATE: A	ori 17. 20	118		
ealed b	ids, subject to the conditions on the reverse hereof, and as may be attached hereto,	will be recei	vod at thi	s office		
ntil_2:0	O.P.M. May 2, 2018 and then publicly opened, for furnishing the supplies, materials,	77111 50 (000)	100 01 111	3 Office		
nd/or se	ervices as described below.	 	 		 	
	þ	Blde will F	o onenec	May 2, 2018.	-	<u> </u>
	a transfer to the		2:00 P.M		-	<u> </u>
O.B J	onesboro, Arkansas	BY: Al Ha		<u>.</u>	ļ	
	Delivery or completion time after issuance of Purchase	PURCHA		FOTOD		
rder or	work ordered by County _120 days,	FUNCHA	Ting Dir	T		
Item #	DESCRIPTION	OLIANT	LIMIT	LINET DRICE	1110	<u> </u>
1	Furnish two (2) each Dump Trucks with Automatic transmissions and with	QUANT 2	UNIT	UNIT PRICE	AMC	UNT
	installed dump beds to Craighead County Road Department, 2800 Moore		 		 	
	Road, Jonesboro, AR. 72401 according to attached specifications. Trucks are	7.21	£ 71	211211		
A11.0734 11.07 11.14.14.1	to have dump beds and hydraulics installed and fully operational when delivered.	///	T 110	NICK (EN	ILER
2	This bid package contains 6 pages. All 6 pages must be returned	701	9/	UCK (RE16-147 45D	Z/λ	IFR
	to complete bid.	,	-//	150		
3		ļ	//	720		
4	Bid must be signed by authorized company representative. Bidder should:	OX		AMPEDO	1 2	ED
4						
	A. Clearly define and list warranty information on each item in years.		1			
	B. Include all labor, delivery charges, training, programming,					
	and any other charges FOB Jonesboro, Arkansas 72401, in bid price.				_ ·	
s	C. Include product literature and specifications with bid.					
	D. All relevant information will be considered when determining best bid for Craighea	d County.				
	E. Specify cash discounts, if available.					
	F. Note bid number on outside of bld envelope.	·			•	
	G. Specify approximate ship time in days, if awarded bid.	DELIL	IER	IN 330	DAY	2
	F. List make, model, and manufacturer of equipment being offered.					
	G. Quote same or equal equipment in all aspects.				}	
	H. Specify nearest service and parts supply location to Jonesboro, AR.				T	
	Does bidder meet all dump truck specifications? Yes No			·	 	 -
	If no, clearly list and define differences on a separate sheet.		v - v			
6	Attached equipment list with names and part numbers is for reference.				 	
7	Bidder should put total bid price on this sheet. Total bid price is \$285,300-2					
8	Bidder shall list purchase price per unit here.\$ 142,650 Buyback price per unit he	re.\$ 85,	600			
	EXECUTION OF BID	Date 4	124/	8	<u> </u>	
e, the ur	dersigned, have read all the requirements set forth in this bid proposal including spe					
truction	s, conditions, and pertinent information regarding the articles being bid on, and we ag	ree to furn	leh			
icles at 1	he prices stated.	ree to luiti	1911		<u> </u>	·
	Jse Tax Register No. 31/386-46-00/				 	
ider 2	Address 5712 COMMERCE S	50			 	
	Person Authorized to Sign Bids) Title GENERAL MANAGER				ļ	
	UNSIGNED BIDS WILL BE REJECTED				<u> </u>	
		51. B. U.S				
NOT	BIDS ARE SUBJECT TO REJECTION UNLESS SUBMITTED				L	
NOTE	CE TO BIDDERS, SEE REVERSE SIDE OR ATTACHMENTS FOR INSTRUCTIONS	AND CON	IDITIONS		<u> </u>	

rji.

. .

	CRAIGHEAD COUNTY
	JONESBORO, ARKANSAS
	CONDITIONS OF BIDDING
	Compliance with the following conditions is necessary for consideration of this bid
1	Signature-This bid must be signed with the firm name and by an authorized officer, employee or agent.
2	Sales Tax-Is not to be shown in the bid price, but is to be added by the vendor to the invoice billing to the County.
	The County is exempt from Arkansas State Sales Tax on road equipment and vehicles. Confractors are to include all costs
	into the bid price, including applicable taxes.
3	Freight and other delivery charges-to destination at designated County facility in the County must be included in bid.
	Charges may not be added after the bid is opened.
.4	Discounts-Show rate, total amount, and latest day any discounts will be allowed after receipt of article and invoice,
	otherwise County Will deduct allowed discount when payment is made.
5	Firm Price-All prices quoted will remain firm for at least 30 days from date of bid, unless otherwise specified
	by the County of bidder
6	Tay Evamet Craighead County is suggest have Class and the suggest and the suggest that the
<u></u>	Tax Exempt Craighead County is exempt from State sales tax on self propelled equipment and motor vehicles.
7	Example: Motor graders, excavators, dozers, dump trucks, pickup trucks, etc.
	identical Bids-In the event of two or more identical low bids, the contract may be awarded arbitrarily or for
Ô.	any reason to any of such bidders, or split in any proportion between the said two or more bidders at discretion of the County.
8	clean up-Complete cleanup and proper disposal of any and all lob related items is considered to be a part of any
<u> </u>	contract let by Craighead County.
9	Ambiguity in bid-Any ambiguity in any bid as the result of omission, error, lack of clarity or non-compliance
<u></u>	specifications, instructions, and all conditions of bidding shall be construed in the light most favorable to the County
10	Construction
	A. When requested, the Contractor is to supply the County with evidence of having and maintaining proper and
	specifically Workman's Compensation Insurance in accordance with the laws of the State of Arkansas,
	Public Liability, and Property Damage. All premiums and cost shall be paid by Contractor, in no way will the
04 	County be responsible in case of accident.
	B. A Performance Bond equaling the total amount of any bid exceeding \$20,000 must be provided for
	erection of any public building, public structure, or public improvement (Pursuant to Arkansas Code 18-44-503)
11	The County reserves the right to reject any and all bids, accept in whole or in part, to waive informalities in bids
_	received, to accept bids on materials or equipment with variations from specifications in those pases where efficiency
	of operation will not be impaired, and unless otherwise specified by bidder, to accept any item in the bid. If unit prices
,	and extensions thereof do not coincide, the Collinty may accept the bid for the lesser amount whether reflected
	by extension or by the correct multiple of the unit price.
	INSTRUCTIONS TO BIDDERS (Please read carefully)
1	Submit bld on bid form attached or reverse side of this sheet.
2	Address all bids to: Purchasing Director, Graighead County Judge's Office, 511 Union St.; Suite 119,
	Jonesboro, Arkansas 72401 and make certain to indicate identifying bid number on the outside of bid envelope.
3	DO NOT include Federal Excise Tax in bid. County will furnish exemption certificate.
4	Sate Manufacturer, Brand Name, Model, etc. for each item bid on.
5	Samples of items, when required must be furnished free, and, if not called for within 30 days from date of
C.3	bid opening, will be disposed of by the County
3	Bids received after stated time will not be considered.
,	Be sure and read all conditions and verify amounts before submitting bids. No changes or additions will be
	allowed after submission.
3	
,	Guarantees and warranties should be attached as a part of the bid, as they may be a consideration in awarding contract. Delivery or contract completion time is to be shown, as this date may, where time is of the
	esseñoè, determine the contract award.
ġ.	
	Additional information may be obtained from the Purchasing Department. THE COUNTY RESERVES THE RIGHT TO ACCEPT PART OR ALL OF ANY SPECIFIC BID OR BIDS
	THE SOUNT I RESERVES THE KIGHT TO ACCEPT PART OR ALL OF ANY CRECIED DIS ON AS DISS

	General				
Α	Trucks (automatic transmissions) and dump beds shall be the latest year model in curren	t production	with proper	no former e	
	by manufacturer and shall meet all federal emissions and all other EPA regulations.(Spe	cify year mo	yığı biğyeli	i bendiliratice	
В	All bidders shall offer a guaranteed three (3) year dealer buy back program and clearly do	olly year illo	uei)		
	buy back dollar amount, time frame and mileage and other criteria for the buy back program	aniinid anii			
C	Bidder shall bid truck and bed with a three (3) year/150,000 mile dealer buyback program	411,			
	Dealer should guarantee any outside vendors and /or companies that supply buy back pr	l.			
Ď	Note: Part of specifications may be Freightliner specific. Please bid equal equipment.	icing.			
E	Note: Part of specifications may be Godwin EL series specific. Please bid equal equipment	24			
· /	VEHICLE AND DUMP BED SPECIFICATIONS	nr.	· · · · · · · · · · · · · · · · · · ·		
Ě	Dump Bed Specifications (Beds being offered shall be equal to the following	14 10	· · · · · · · · · · · · · · · · · · ·		
	specifications)		cifications		
1	R/S Godwin Truck Body Company, Model Et. 16052311	Yes	No		
2	Elliptical floor, length 192, Pivot 180 degrees, Inside width 86, Side height 52.	V			
3	Custom single acting hoist, Electric Tarp system-6200.				
4	6" diameter cylinder rod(3) stage cylinder with 2000 PSI	1			
5	Hoist lifting capacity 58,540 lbs. (28 ton)	V/	<u> </u>		
6	140° cylinder stroke	1			
7	50 degree dump angle	1			
- <u></u> 8	High lift gate (6') opening discharge	//	The second second second		
9	16 Cubic yard capacity				
10		V			100
11	Fender bottom rail 10 gauge, Wood Board gusset height 8', Bulkhead 74.				
12	All Hydraulics, All safety features, flaps, lights.				
13	Áir shift PTO				
	Asphalt apron, Deck 1/4" AR450, Sides 3/16" AR450, Rear post material 1/4" high tensile		,		
14	Air operated tailgate, High lift, Height 56, Material, 3/16" hardox AR450, air operated control	ols, 🗸			
there	The state of the s				
	Vehicle Configuration				
1	114SD CONVENTIONAL CHASSIS				
2	SPECIFY MODEL YEAR	1,20	219		THE CO. LEWIS CO., LANSING,
3	ŞET FÖRWARD AXLE TRUCK	//			
4	TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK	//			
5	FREIGHTLINER LEVEL II WARRANTY	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			
6	EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs.			and and and any or many opening	
7	EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs.				
8	EXPECTED PUSHER AXLE(S) LOAD; 12350.0 lbs.	1			
9	EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350:0 lbs.	1			
10	EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs.	1			
11	DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM	1			
2	2010 EPA/CARB EMISSION CERTIFICATION				
3	DR 12V 190 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE	1		Andrew Control of the	
4	(3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES				
5	POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX				
6	ZF-SACHS 15-1/2 INCH TWIN XTEND ULTRA SOFT DAMPER CERAMIC CLUTCH				İ

17	TORQUE LIMITING CLUTCH BRAKE	1				
18	ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING	 -		11 YES 11 1 A		
19	BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE					
20	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM					
21	JACOBS COMPRESSION BRAKE			r graffiere in time pagades.		
22	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH LH B-PILLAR MOUNTED VERTICAL TAILPIPE	/		to a magnification of a state of the state o		
23	ENGINE AFTERTREATMENT DEVICE, AUTOMATIG OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH	/			THE STATE OF THE S	marke of marketing court of and
24	BRÎGHT UPPER STACK(S)		·	· · · · · · · · · · · · · · · · · · ·		
25	13 GALLON DIESEL EXHAUST FLUID TANK		 			
26	BORG WARNER (KYSOR) REAR AIR ON/OFF ENGINE FAN CLUTCH	/				
27	DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR	/				
28	1500 SQUARE INCH ALUMINUM RADIATOR	/				
29	DELCO 12V 39MT+ HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH	/		مند سنده و دو هما دو هما المناسبة و المناسبة	-	
30	ALLISON AUTOMATIC 4500 RDS TRANSMISSION	/	 -			
31	MFS-18-133A 18,000# FL/1 SINGLE FRONT AXLE			en man e sesenana se	· de a	
32	MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	<u> </u>		Madeshire all from a per Brown of the c		
33	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS					-
34	TRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR					
35	ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE					
36	18,000# TAPERLEAF FRONT SUSPENSION	_/_	-	·	+	
37	FRONT SHOCK ABSORBERS					
38	RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE	7				~
39	4.30 REAR AXLE RATIO	./			^,	
40	MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES	/		rada ay gabayada i wasaaya wayay 2004 ilika ilaa ka		
41	MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES	/			-	
42	DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES	/				
43	(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE	/				
44	MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES				-	
45	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)					~
46	TUFTRAG 46,000# 2-STAGE REAR SPRING SUSPENSION			·	+	
47	TUFTRAC STANDARD RIDE HEIGHT				+	
48	56 INCH AXLE SPACING					
49	FORE/AFT AND TRANSVERSE CONTROL RODS			- 	1	
	HENDRICKSON PARALIFT ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE	/		The state of the s	-	
51	HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS	V		~AA		
52	(1) DASH VALVE AND (1) GAUGE FOR SINGLE LIFT AXLE					
			<u> </u>		<u>+ </u>	.1

AIR PIPING FOR (1) LIFT/INON-LIFT AXLE WITH REGULATOR CHASSIS MOUNTED 55 MERITOR 15X4 Q+ CAM PUSHER/TAG BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 56 MERITOR AUTOMATIC PUSHER/TAG SLACK ADJUSTERS 57 HENDRICKSON HLUCZ 13,200# AIR LIFT STEERABLE PUSHER AXLE SUSPENSION 58 WABCO 4S/4M ABS WITHOUT TRACTION CONTROL 59 PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED THROUGH IGNITION 60 SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME 61 S850MM (222 INCH) WHEELBASE 62 11/32X3-1/2X10-16/16 INCH STEEL FRAME (8.73MMX277.8MM0.344X10.94 INCH) 120KSI 63 1/4 INCH (6MM) C-CHANNEL INNER FRAME REINFORCEMENT 64 HEAVY DUTY SUSPENSION CROSSMEMBER 66 100 GALLONATS LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/6SR22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G388 11822.5 18 PLY RAD IAL FRONT TIRES 69 GOODYEAR G388 11822.5 19 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR FURS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 72 ACCURIDE 29844A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29844A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 74 ACCURIDE 29844A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 75 ACCURIDE 29844A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 76 ACCURIDE 29844A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
SHOES 66 MERITOR AUTOMATIC PUSHERITAG SLACK ADJUSTERS 67 HENDRICKSON HLUCZ 13,200# AIR LIFT STEERABLE PUSHER AXLE SUSPENSION 68 WABCO 4S/4M ABS WITHOUT TRACTION CONTROL 59 PRIMARY CONNECTOR/REGEPTACLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED THROUGH IGNITION 60 SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME 61 S650MM (222 INCH) WHEELBABE 62 11/32X3-1/2X10-16/16 INCH STEEL FRAME (8.73MMX277.8MM(0.344X10.94 INCH) 120KSI 63 1/4 INCH (5MM) C-CHANNEL INNER FRAME REINFORCEMENT 64 HEAVY DUTY SUSPENSION CROSSMEMBER 65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 100 GALLON378 LITER ALLUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/6SR22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G288 11822.5 16 PLY RADIAL PUSHER/TAG TIRES 69 GOODYEAR G388 11822.5 16 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
SHOES 66 MERITOR AUTOMATIC PUSHERITAG SLACK ADJUSTERS 57 HENDRICKSON HLUCZ 13,200# AIR LIFT STEERABLE PUSHER AXLE SUSPENSION 58 WABGO 4S/4M ABS WITHOUT TRACTION CONTROL 59 PRIMARY CONNECTOR/RECEPTAGLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED THROUGH IGNITION 60 SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTAGLE MOUNTED END OF FRAME 61 S850MM (222 INCH) WHEELBABE 62 11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM0.344X10.94 INCH) 120KSI 63 1/4 INCH (6MM) C-CHANNEL INNER FRAME REINFORCEMENT 64 HEAVY DUTY SUSPENSION CROSSMEMBER 65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 100 GALLON/378 LITER ALLUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/95R22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G288 11822.5 16 PLY RADIAL PUSHER/TAG TIRES 69 GOODYEAR G288 11822.5 16 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 74 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 75 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
HENDRICKSON HLUC2 13,200# AIR LIFT STEERABLE PUSHER AXLE SUSPENSION 58 WABCO 4S/4M ABS WITHOUT TRACTION CONTROL 59 PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED THROUGH IGNITION 60 SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME 61 5650MM (222 INCH) WHEELBASE 62 11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI 63 1/4 INCH (6MM) C-CHANNEL INNER FRAME REINFORCEMENT 64 HEAVY DUTY SUSPENSION CROSSMEMBER 65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 100 GALLON378 LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G298 MSA 385/65R22.5 14 PLY RADIAL PRONT TIRES 69 GOODYEAR G338 1AD 295/76R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29844A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
58 WABCO 4S/4M ABS WITHOUT TRACTION CONTROL 59 PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED THROUGH IGNITION 60 SAE JS60 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME 61 S650MM (222 INCH) WHEELBASE 62 11/32X3-1/2X10-15/16 INCH STEEL FRAME (8,73MMX277.8MM/0.344X10.94 INCH) 1/20KS1 63 1/4 INCH (8MM) C-CHANNEL INNER FRAME REINFORCEMENT 84 HEAVY DUTY SUSPENSION CROSSMEMBER 65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 1/30 GALLON/378 LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G298 MSA 385/65R22.5 14 PLY RAD IAL FRONT TIRES 69 GOODYEAR G388 11R22.5 16 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED THROUGH IGNITION 60 SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME 61 5850MM (222 INCH) WHEELBASE 62 11/32X3-1/2X10-16/16 INCH STEEL FRÂME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI 63 1/4 INCH (5MM) C-CHANNEL INNER FRAME REINFORCEMENT 64 HEAVY DUTY SUSPENSION CROSSMEMBER 65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 100 GALLON378 LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70 CONMET FRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 72 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED THROUGH IGN/ITION 60 SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME 61 S850MM (222 INCH) WHEELBASE 62 11/32X3-1/2X10-16/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI 63 1/4 INCH (5MM) C-CHANNEL INNER FRAME REINFORCEMENT 64 HEAVY DUTY SUSPENSION GROSSMEMBER 65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 100 GALL ON378 LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G298 11R22.5 16 PLY RADIAL PUSHER/TAG TIRES 69 GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70 COMMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 72 ACCURIDE 29844A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
FRAME 61 5650MM (222 INCH) WHEELBASE 62 11/32X3-1/2X10-16/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI 63 1/4 INCH (6MM) C-CHANNEL INNER FRAME REINFORCEMENT 64 HEAVY DUTY SUSPENSION CROSSMEMBER 65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 100 GALL ON 378 LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G388 11R22.5 16 PLY RADIAL PEAR TIRES 69 GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 293/4A 22.5X8.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
61 \$650MM (222 INCH) WHEELBASE 62 11/32X3-1/2X10-16/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI 63 1/4 INCH (6MM) C-CHANNEL INNER FRAME REINFORCEMENT 64 HEAVY DUTY SUSPENSION GROSSMEMBER 65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 100 GALLON;378 LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G288 11R22.5 16 PLY RADIAL REAR TIRES 69 GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
62 11/32X3-1/2X10-15/16 INCH STEEL FRÂME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI 63 1/4 INCH (8MM) C-CHANNEL INNER FRAME REINFORCEMENT 64 HEAVY DUTY SUSPENSION GROSSMEMBER 65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 100 GALLON/378 LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/65R22-5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G288 11R22.5 16 PLY RADIAL REAR TIRES 69 GOODYEAR G338 1AD 295/75R22-5 14 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72 ACCURIDE 29844A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29844A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
120KSI 63 1/4 INCH (5MM) C-CHANNEL INNER FRAME REINFORCEMENT 64 HEAVY DUTY SUSPENSION GROSSMEMBER 65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 100 GALLON/378 LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES 68. GOODYEAR G288 11R22.5 16 PLY RADIAL REAR TIRES 69. GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70. CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71. ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72. ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73. ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
64 HEAVY DUTY SUSPENSION CROSSMEMBER 65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 100 GALLON/378 LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G288 11R22.5 16 PLY RADIAL REAR TIRES 69 GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	!
65 16.5 INCH CHROME STEEL STRAIGHT BUMPER 66 100 GALLON/378 LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G288 11R22.5 16 PLY RADIAL REAR TIRES 69 GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
66 100 GALLON/378 LITER ALUMINUM FUEL TANK - LH 67 GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES 68 GOODYEAR G388 11R22.5 16 PLY RADIAL REAR TIRES 69 GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES 68. GOODYEAR G288 11R22.5 16 PLY RADIAL REAR TIRES 69. GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70. CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71. ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72. ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73. ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
68 GOODYEAR G288 11R22.5 16 PLY RADIAL REAR TIRES 69 GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
69 GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES 70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
70 CONMET PRE-SET BEARING ALUMINUM REAR HUBS 71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
71 ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS 72 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
FRONT WHEELS 72 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS 73 ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
7.3 ACCURIDE 29644A 22.5X8:25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS	
WHEELS	
74 114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB	
75 AIR CAB MOUNTS	
76 NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE	
77 CHROMED HOOD MOUNTED AIR INTAKE GRILLE	
78 DUAL 26 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS ROOF MOUNTED	
79 DUAL HORN SHIELDS	
80 HALOGEN COMPOSITE HEADLAMPS WITH BRIGHT BEZELS	
81 DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE	
82 DOOR MOUNTED MIRRORS	
83 LH AND RH 8" BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS	
84 TINTED DOOR GLASS LH AND RH WITH TINTED OPERATING WING WINDOWS	
85 RH AND LH ELECTRIC POWERED WINDOWS	
86 INTERIOR CONVENIENCE PACKAGE WITH CB PROVISION	-
87 2-1/2 LB. FIRE EXTINGUISHER	
88 HEATER, DEFROSTER AND AIR CONDITIONER	\neg

89	CAB INSULATION	7	Γ	Ţ		,
90	SOLID-STATE CIRCUIT PROTECTION AND FUSES	V	 	ļ		
91	LH AND RH ELECTRIC DOOR LOCKS	1	ļ			
92	(1) 12 VOLT POWER SUPPLY IN DASH	V	ļ		· · · · · · · · · · · · · · · · · · ·	
93	TRIANGULAR REFLECTORS WITHOUT FLARES					
94	BOSTROM TALLADEGA 910 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH AIR	/	<u> </u>	ļ		
,	LUMBAR	/				
95	HIGH BACK NON SUSPENSION PASSENGER SEAT			 		
96	LH AND RH INTEGRAL DOOR PANEL ARMRESTS		<u> </u>	·		ļ
97	CLOTH DRIVER SEAT COVER		 	<u> </u>		
98	CLOTH PASSENGER SEAT COVER	./	<u> </u>	<u> </u>		
99	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN	/	 	 		
100	97 DB BACKUP ALARM	/	 			
101	ELECTRONIC CRUISE CONTROL WITH SWITCHES ON AUXILIARY GAUGE PANEL (B DASH PANEL)	/			· ·	
102	ODOMETER/TRIP/HOUR/DIAGNOSTIC/VOLTAGE DISPLAY: 1X7 CHARACTER, 26 WARNING LAMPS, DATA LINKED, ICU3	/				
103	DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1939, LOCATED BELOW DASH	/	 			
104	2 INCH ELECTRIC FUEL GAUGE					
105	FUEL FILTER RESTRICTION INDICATOR					
106	DUAL REAR AXLE TEMPERATURE GAUGES FOR TANDEM AXLES					
107	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE					
108	ENGINE OIL TEMPERATURE GAUGE					
109	2 INCH TRANSMISSION OIL TEMPERATURE GAUGE					
110	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY					
111	ELECTRIC ENGINE OIL PRESSURE GAUGE					
112	AM/FMWB RADIO WITH FRONT AUXILIARY INPUT		-			
113	DASH MOUNTED RADIO					
114	ELECTRONIC 3000 RPM TACHOMETER		· 			
115	TRAILER HAND CONTROL BRAKE VALVE		····	· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·
116	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHERWIPER AND HAZARD IN HANDLE			**************************************		
117	PAINT: ONE SOLID COLOR					
118	CAB COLOR (EQUAL TO L5495EB ULTRA RED PEARL METALLIC ELITE BC)		· · · · · · · · · · · · · · · · · · ·			
119	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT	1				<u>.</u>
120		7				
120						
1	Unit cost and buy back proposal Bidder shall list the purchase price per unit here and on top sheet.\$ 142,650	2		······································		
2	Bidder shall list the guaranteed three (3) year/150,000 mile dealer buy back price here per ur]	00/1	7,00	
	Store of the line and Armentood at thee foll Aegus 100,000 thing degree binh back buce liefe bet ri	iii and on t	op sneet.	BJ,60		
						

Prepared for: Ed Hill Craighead COunty 511 Union Jonesboro, AR 72401 Phone: 870-933-4510


Prepared by: Phillip Goodman TAG Truck Center 1650 E. Brooks Road Memphis, TN 38116 Phone: 901-345-5633

A proposal for Craighead COunty

Prepared by **TAG Truck Center**Phillip Goodman

Apr 23, 2018

Freightliner 114SD



Components shown may not reflect all spec'd options and are not to scale



Prepared for: Ed Hill Craighead COunty 511 Union Jonesboro, AR 72401 Phone: 870-933-4510

3 6 1 2

Prepared by: Phillip Goodman TAG Truck Center 1650 E. Brooks Road Memphis, TN 38116 Phone: 901-345-5633

SPECIFICATION PROPOSAL

	Data Code	Description	Weight Front	Weight Rear
Price Le	vel		19	
	PRL-18D	SD PRL-17D (EFF:04/17/18)		
Data Ver	rsion			
	DRL-001	SPECPRO21 DATA RELEASE VER 001	ANDRE WASHINGTON OF THE PARTY.	CICLE OF STREET STREET, STREET STREET,
Interior (Convenience	e/Driver Retention Package		
ATTACHER - E. KIRKE STAFF TO WAR	055-004	INTERIOR CONVENIENCE PACKAGE WITH CB PROVISION		
Vehicle 0	Configuratio	n.		
and succession of the successi	001-177	114SD CONVENTIONAL CHASSIS	7,934	6,576
(004-219	2019 MODEL YEAR SPECIFIED		·
C	002-003	SET FORWARD AXLE - TRUCK		•
C	019-002	STRAIGHT TRUCK PROVISION		
	003-001	LH PRIMARY STEERING LOCATION		
General S	Service			
	\A 1-002	TRUCK CONFIGURATION	o martinala sono	
A	AA6-001	DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)		
A	A85-011	CONSTRUCTION SERVICE		
А	\84-1GM	GOVERNMENT BUSINESS SEGMENT		
Α	A4-010	DIRT/SAND/ROCK COMMODITY		
А	A5-002	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
Α	B1-008	MAXIMUM 8% EXPECTED GRADE		
A	B5-001	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
98	95-1AE	FREIGHTLINER LEVEL II WARRANTY		
A	66-99D	EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs		
. A6		EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs		
A	67-99D	EXPECTED PUSHER AXLE(S) LOAD: 13200.0 lbs		

Prepared for: Ed Hill Craighead COunty 511 Union Jonesboro, AR 72401 Phone: 870-933-4510

Prepared by:
Phillip Goodman
TAG Truck Center
1650 E. Brooks Road
Memphis, TN 38116
Phone: 901-345-5633

Data Code	Description	Weight Front	Weight Rear
A63-99D	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 77200.0 lbs		
Truck Service			
AA3-004	END DUMP BODY	* 10 3 3 5 7 10 1 10 7 10 7 20 10 3 3 2 5 5 6 5 6 5 7 5 7 5 7 5 7 5 7 5 7 5 7 5	en e
AF3-165	OX BODIES (TBEI)		
∉ Engine ₁			
101-2YA	DETROIT DD13 12.8L 450 HP @ 1625 RPM, 1900 GOV RPM, 1650 LB/FT @ 975 RPM		
Electronic Parameto	ers .		
79A-065	65 MPH ROAD SPEED LIMIT		
79B-000	CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT		
79M-002	PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED OR PARK BRAKE NOT APPLIED		
79W-001	ONE REMOTE PTO SPEED		
79X-005	REMOTE PTO SPEED 1 SETTING - 900 RPM		
Engine Equipment			
99C-017	2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION		
99D-011	2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)		
13E-001	STANDARD OIL PAN		
105-001	ENGINE MOUNTED OIL CHECK AND FILL		
014-1B5	SIDE OF HOOD AIR INTAKE WITH DONALDSON HIGH CAPACITY AIR CLEANER WITH SAFETY ELEMENT, FIREWALL MOUNTED		
124-1D7	DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE		
292-071	(3) ALLIANCE MODEL 1231XOE, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES		
290-017	BATTERY BOX FRAME MOUNTED		
281-001	STANDARD BATTERY JUMPERS		
282-003	SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB	·	
291-017	WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
289-001	NON-POLISHED BATTERY BOX COVER		
87P-998	NO CAB AUXILIARY POWER WIRING		



CRAIGHEAD COUNTY						
INVITATION TO BID-Not an Orde						
Craighead County Judge's Office	er		<u> </u>			
511 Union Ch. Cult. 440		·				
511 Union St.; Sulte 119						
PURCHASING OFFICE Jonesboro, Arkansas 72401						
BID NO. 2018-7						
Sealed bids, subject to the conditions on the reverse by	DATE:	April 17, 2	2018	<u>-</u>		-
Sealed bids, subject to the conditions on the reverse hereof, and as may be attached heretountil 2:00 PM May 2, 2018 and then publicly opened, for furnishing the currilles		eived at th	nis offic	:e		
until <u>2:00 PM May 2, 2018</u> and then publicly opened, for furnishing the supplies, materials, and/or services as described below.					 -	
antition activities as described delow.	·			,		
	Bids will	be opene	d May	2 2018		
O.B Jonesboro, Arkansas		2:00 P.N		<u>Z, Z010,</u>		
Acking Della	BY: Al H	ainoe	OB PROPERTY.	· # ===================================	- Contraction -). 21 (-25 - 12 May - 1 - 1 - 1
Maximum Delivery or completion time after issuance of Purchase		ASING DI	DEOT/	<u> </u>		
order or work ordered by County 120 days.	1 01/01/	ווט טווסף	RECTO	JK		
Item # DESCRIPTION	OLIANT	1 14 11 ==	ļ			
1 Furnish two (2) each Dump Trucks with Automatic transmissions and with	QUANT	UNIT	UNIT	PRICE	AMO	DUNT
mistalled dullip beds to Craidness County Road Department agos is	2		-			T
Modu, Juliespolo, AR. / 24UT according to attached angels - U. T.	1	7-1				T
to have dump beds and hydraulics installed and fully operational inter-		116	18	UCK	CEI	VIZA
This bid package contains 6 pages. All 6 pages must be returned						
to complete pig.	20	219 (VE.	TERM	7 3	THE
Bid must be signed by authorized company representative.			47	10 SF		7,1,7
4 Bidder should:					1	
A. Clearly define and list warranty information on each item in years.	(DX	577A	M PED		BEZ)
B include all labor, delivery charges to the		7	7.7.1			
B. Include all labor, delivery charges, training, programming,			 -		<u> </u>	ļ
and any other charges FOB Jonesboro, Arkansas 72401, in bid price.		<u> </u>			ļ	
C. Include product literature and specifications with bid.	 		L		ļ	<u> </u>
D. All relevant information will be considered when determining best bid for Craigher E. Specify cash discounts, if available	ed County		 .			
	d Courty,					
F. Note bid number on outside of bid envelope.		<u></u>				
G. Specify approximate ship time in days, if awarded bid.	Dell	11 0-13	77			
F. List make, model, and manufacturer of equipment being offered	DECI	UER		150	DA	YS
G. Quote same or equal equipment in all aspects					e governe	142 (\$1.50 PM)
H. Specify hearest service and parts supply location to longshare. AD						
Does bluder meet all dump truck specifications? Yes						
IT no, clearly list and define differences on a separate sheet						
Attached equipment list with names and part numbers is for reference.						
/ Diggs allowed bill mild blice on the chart Taket List	96					
Bidder shall list purchase price per unit here. \$ 145,435 Buyback price per unit here.						
Buyback price per unit her	e.\$ <u>92,</u>	000				
EXECUTION OF BID		,				
the linderstaned have read all the results.	Date 4/	23/18	·			
the undersigned, have read all the requirements set forth in this bid proposal including specifically conditions, and pertinent information recording the little proposal including specifically conditions.	fleations			=		
actions, conditions, and pertinent information regarding the articles being bid on, and we ago se at the prices stated.	ree to furnis	th .			<u> </u>	
os at the prices stated,	TO THAT INC	""				
nsas Use Tax Register No3//386-16-001						
Person Authorized to Sign Pide) Title	<u> </u>		-			
THE STATE WAS THE SELECT WAS ASSETTED.	=					
UNSIGNED BIDS WILL BE DE LECTED						
	Ì	İ			~	
BIDS ARE SUBJECT TO BE JECTION UNITED AND ADDRESS OF THE PROPERTY OF THE PROPE	**************************************			· ·	i	
BIDS ARE SUBJECT TO REJECTION UNLESS SUBMITTED O NOTICE TO BIDDERS, SEE REVERSE SIDE OR ATTACHMENTS FOR INSTRUCTIONS	N THIS FO	RM				

	CRAIGHEAD COUNTY
	JONESBORD, ARKANSAS
	Compliance with the following and Italy
` ī ˙	Compliance with the following conditions is necessary for consideration of this bid. Signature-This bid must be signed with the firm pages.
2	Signature-This bid must be signed with the firm name and by an authorized officer, employee or agent. Sales Tax-Is not to be shown in the bid price, but is to be added to the sales Tax-Is not to be shown in the bid price, but is to be added to the sales Tax-Is not to be shown in the bid price.
- · · -	Sales Tax-Is not to be shown in the bid price, but is to be added by the vendor to the invoice billing to the County. The County is exempt from Arkansas State Sales Tax on road aguirment and the invoice billing to the County.
	The County is exempt from Arkansas State Sales Tax on road equipment and vehicles. Contractors are to include all costs into the bid price, including applicable taxes.
<u>-</u>	into the bid price, including applicable taxes.
J	Freight and other delivery charges-to destination at designated County facility in the County must be included in bid. Charges may not be added after the bid is opened.
	Charges may not be added after the bid is opened.
4	Discounts-Show rate, total amount, and latest day any discounts and latest day any discounts.
	otherwise County will deduct allowed discount when payment is made.
5	Firm Price-All prices quoted will remain firm for at least 30 days from date of bid, unless otherwise specified by the County or bidder
	by the County or bidder
6	Tax Exempt-Graighead County is exempt from State sales tax on self propelled equipment and motor vehicles.
•	Example: Motor graders avecuate and motor vehicles.
7	Example: Motor graders, excavators, dozers, dump trucks, pickup trucks, etc.
	acontrol bigstiff (i) Iwo of more identical fourthists also and in the second s
8	any reason to any of such bidders, or split in any proportion between the said two or more bidders at discretion of the County. Clean up-Complete cleanup and proper disposal of any and all leb related flores by
. 0	Clean up-Gomplete cleanup and proper disposal of any and all job related items is considered to be a part of any contract let by Craighead County.
A	contract let by Craighead County.
. 9	Ambiguity in bid-Any ambiguity in any bid as the result of omission, error, lack of clarity or non-compliance
merce a.	specifications, instructions, and all conditions of bidding shall be construed in the light most favorable to the County
10	Construction Construction
	A. When requested, the Contractor is to supply the County with address of hard
	A. When requested, the Contractor is to supply the County with evidence of having and maintaining proper and specifically Workman's Compensation Insurance in accordance with the laws of the State of Arkansas,
	Public Liability, and Property Damage. All promises and an additional laws of the State of Arkansas,
	Public Liability, and Property Damage. All premiums and cost shall be paid by Contractor. In no way will the County be responsible in case of accident.
***	B. A Performance Bond equaling the total
	B. A Performance Bond equaling the total amount of any bid exceeding \$20,000 must be provided for
11	
	The County reserves the right to reject any and all bids, accept in whole or in part, to walve informalities in bids received, to accept bids on materials or equipment with varieties as follows:
	received, to accept bids on materials or equipment with variations from specifications in those cases where efficiency of operation will not be impaired, and unless otherwise specified by hidden to
. ,	of operation will not be impaired, and unless otherwise specified by bidder, to accept any item in the bid. If unit prices
	and extensions thereof do not coincide, the County may accept the bid for the lesser amount whether reflected by extension or by the correct multiple of the unit price.
j	by extension or by the correct multiple of the unit price.
	INSTRUCTIONS TO DIRECTO
1	Submit bid on bid form attached or reverse side of this shoot
۷ :	Addiess all bids to: Purchasing Director Crainbood County Ludent or
	PULC MICHURCHURCH DIAMENTARIA MONOL AND TANALAR SALLEY
5	Samples of Items, when required must be furnished free, and, if not called for within 30 days from date of
·	old opening, will be disposed of by the County
	Sids received after stated time will not be considered.
7 F	Se sure and read all conditions and wife.
:	le sure and read all conditions and verify amounts before submitting bids. No changes or additions will be
9 10	Suarantees and warranties should be attached as a part of the bid, as they may be a consideration in awarding contract.
7 L	elivery or contract completion time is to be shown, as this date may, where time is of the
1-	againg) agroiding the Colificati SMMM
10 JA	dditional information may be obtained from the Burchesine Deserted
1,	TE COUNTY RESERVES THE RIGHT TO ACCEPT DADY OF ALL OF AND ACCEPT DADY
A	ND TO ACCEPT BID WITH OR WITHOUT TRADE-IN, AND REJECT ANY AND ALL BIDS.
	THE PROPERTY OF ANY AND ALL RIDGE

A Trudits (automatic transmissions) and dump beds shall be the latest year model in current production with proven performance by manufacturer and shall meet all federal emissions and another EPA regulations (Specify year model). All bidders shall offer a guarariated three (3) year dealer buy back program and dearly defining buy back dollar around, time frame and mileage and other criteria for the buy back program. C Bidder shall bid truck and bed with a three (3) year dealer buy back program. Desteits shall dis quarantee any outside vendors and for companies that supply buy back priding. Desteits shall dis quarantee any outside vendors and for companies that supply buy back priding. Note: Part of specifications may be Fordwin EL series specific. Please bid equal equipment. Note: Part of specifications may be Fordwin EL series specific. Please bid equal equipment. Programment of the Part of specifications and for companies that supply buy back priding. Note: Part of specifications may be Fordwin EL series specific. Please bid equal equipment. Programment of the Part of specifications may be Fordwin EL series specific. Please bid equal equipment. Programment of the Part of specifications may be Fordwin EL series specific. Please bid equal equipment. Programment of the Part of Specifications and Fordwin EL series specific Please bid equal equipment. Programment of the Part of Specifications and Fordwin EL series specific Please bid equal equipment. Programment of the Part of Specifications and Fordwin EL series specific Please bid equal equipment. Programment of the Part of Specifications and Fordwin EL series specific Please bid equal equipment. Programment of the Part of Specifications and Fordwin EL series specific Please bid equipment. Programment of the Part of Specifications and Fordwin EL series specific Please bid equipment. Programment of the Part of Specifications and Fordwin EL series specific Please Part of Specifications and Fordwin EL series specific Please Part of Specifications and		General			i		
B All bidders shall offer a guaranteed three (0) year dealer buy back program and called year model) All bidders shall offer a guaranteed three (0) year dealer buy back program. Dider of shall bid truck and bed with a three (3) year/150,000 mile dealer buyback program. Dider should guarantee any outside vendors and for compenies that supply buy back pring. Dider of a pedicinations may be freightliner specific. Please bid equal equipment. WEHICLE AND DUNP BED SPECHICATIONS I Mote: Part of specifications may be Godwin Expecific. Please bid equal equipment. WEHICLE AND DUNP BED SPECHICATIONS I MyS Godwin Truck Body Company Model Et. 16962311 I MyS Godwin Truck Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Body Company Mys Mys Mys Mys Mys Mys Mys Mys Mys My	A	Trucks (automatic transmissions) and dump had a latter				- !	
B All bidders shall offer a gustranteed three (0) year dealer buy back program and called year model) All bidders shall offer a gustranteed three (0) year dealer buy back program. Duy back todar amount, time frame and mileage and other criteria for the buy back program. Diesier should gustrantee any outside vendors and for compenies that supply buy back pring. Diesier should gustrantee any outside vendors and for compenies that supply buy back pring. Diesier should gustrantee any outside vendors and for compenies that supply buy back pring. Note: Part of specifications may be Godwin Existence specific. Please bid equal equipment. WEHICLE AND DUMP BED SPECHICATIONS F Ummp Bed Specifications (Reds being offered shall be equal to the following indeed the specifications appeared shall be equal to the following indeed specifications appeared to the specifications and the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specifications appeared to the specificatio		by manufacturer and shall most all foderal and a line the latest year model in current	nt productio	n with prov	en performa	псе	
Duy bask dollar amount, time frame and mileage and other cellarie for the buy bask program. C Rikder shall bid funck and bed with a three (3) year/150,000 mile dealer buyback program. Desier should guarantee any outside vendors and for companies that supply buy bask pricing. Desier should guarantee any outside vendors and for companies that supply buy bask pricing. Desier should guarantee any outside vendors and for companies that supply buy bask pricing. Desier should guarantee any outside vendors and for companies that supply buy bask pricing. Notice: Part of specifications may be Godwin Et. series specific, Please bid equal equipment. VEHICLE AND DUMP BED SPECIFICATIONS F Dump Bed Specifications (Reds being offered shall be equal to the following was pecifications supperfications). I ANS Godwin Truck Body Company Model Et. 16052311 2. Elliptical floor, length 192, Pivot 180 degrees, inside width 86, Side height 52. 3. Outstorn single acting hock; Ellichotic Tany system 9200. 1. Outstorn single earling hock; Ellichotic Tany system 9200. 2. Plotest affing capacity 56,540 bs. (26 bon) 3. Holest affing capacity 56,540 bs. (26 bon) 4. High lift gate (6) opening discharge 4. High lift gate (6) opening discharge 4. High lift gate (6) opening discharge 5. Elliptical floor, and a safety floor and a safety of the	В	All bidders shall offer a guaranteed the control of	ecify year n	nodel)	. i.		-
C Bilder shall bid truck and bed with a three (3) year/160,000 mide dealer buy-back program. Dealer should guarantee any outside vendors and for comprehe shat supply buy back pricing. D Note: Part of specifications may be freightliner's specific. Please bid equal equipment. Mole: Part of specifications may be Godwiff. be sorbed specific. Please bid equal equipment. WEHICLE AND DUNP BED SPECIFICATIONS F Dump Bed Specifications (Reds being offered shall be equal to the following specifications (Reds being offered shall be equal to the following specifications (Reds being offered shall be equal to the following specifications). 1					1 -		
Desiler should guarantee any outside vendros and for companies that supply buy back profing. Desiler should guarantee any outside vendros and for companies that supply buy back prioring. Note: Part of specifications may be Foodwin Et. series specific. Please bid equal equipment. EMOLE: Part of specifications may be Godwin Et. series specific. Please bid equal equipment. VEHICLE AND DUMP BED SPECIFICATIONS. FUND BED SPECIFICATIONS. PROSECTION OF TURK BODY Company Model Et. 1806/2011 1 RIVS Godwin Truck Body Company Model Et. 1806/2011 1 RIVS Godwin Truck Body Company Model Et. 1806/2011 2 cilipiteat floor, langth 192, Pivct 180 degrees, Inside width 86, Side height 52. Outstom single acting bed, Electric Tarp system-8200. (**diarriset crylinder rodd)* stage crylinder with 2000 PSI thiotal filing capacity 65, 540 lbs. (28 ton) 1 40* crylinder stocks 1 (30 degree dump angle 1 (40) crylinder stocks 1 (30 degree dump angle 1 (41) If gate (6) opening discharge 1 (50 degree dump angle 1 (41) If priority before mail 10 gauge, Wood Board guaset height 6*, Bulkhead 74. 1 All Hydraulics, All safety features, Rabs, lights, 1 All shift PTO 1 Applial apron, Dock 1/4* Ar450, Sides 3/16* Ar450, Rear post material 1/4* high tensile 1 Ar operated taligate, High lift, Height 56, Material, 3/16* hardox AR450, air operated controls. Vehicle Configuration 1 Int 450 CONVENTIONAL CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE TRUCK FREIGHTHINER LEVEL II WARRANTY 6 EXPECTED PRONT AXLE(S) LOAD: 160000 lbs. EXPECTED FRONT AXLE(S) LOAD: 12350,0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 800000 lbs. EXPECTED GROSS COMBINATION WEIGHT: 800000 lbs. EXPECTED GROSS COMBINATION WEIGHT: 800000 lbs. EXPECTED GROSS SOMBINATION WEIGHT: 800000 lbs. EXPECTED GROSS COMBINATION WEIGHT: 800000 lbs. EXPECTED GROSS SUBJICATION CERTIFICATION 1 DOT3 12.8 459 lb 9 B000 RPM, 2000 GOV RPM, 1650 LBFT @ 1100 RPM 2 2010 EPACARRE BMSSION CERTIFICATION 2 AND ARTHUR STOCK SEMBLE STOCK ARASON CERTIFICATION 3 DR 12V 160 AMP 28-3 GU	·	The standard disposition in the figure and mileage and other enterings to the standard standard and standard st			The second of	** ·	
D Note: Part of specifications may be Frieighiner specific. Please bid equal equipment. Note: Part of specifications may be Foreighiner specific. Please bid equal equipment. VEHICLE AND DUMP BED SPECIFICATIONS F Dump Bed Specifications (Beds being affered shall be equal to the following image specifications) specifications: Specifications: Note: Part of specifications (Beds being affered shall be equal to the following image specifications) specifications: Yes No 1 RNS Godwin Truck Body Company, Wodel EL 18052311 2 cillipideal Body, length 192, Phot 180 degrees, Inside width 86, Side height 52. 3 Oustern single acting hold; Electric Tarp system-8200. 4 of diarrieter cylinder rod(3) stage cylinder with 2000 PSI 5 Holds trifling epeacity 56,540 lbs. (28 lon) 5 140° cylinder stocks 6 0 degree dump agite 1 140° cylinder stocks 1 150° degree dump agite 1 140° cylinder stocks 1 150° degree dump agite 1 140° polinder stocks 1 150° degree dump agite 1 141° cylinder stocks 1 150° degree dump agite 1 141° cylinder stocks 1 150° degree dump agite 1 141° All Hydravitics, All safety leatures, flaps, lights, 1 141° All Hydravitics, All safety leatures, flaps, lights, 1 141° All Hydravitics, All safety leatures, flaps, lights, 1 141° All Hydravitics, All safety leatures, flaps, lights, 1 141° All Hydravitics, All safety leatures, flaps, lights, 1 141° All Hydravitics, All safety leatures, flaps, lights, 1 141° All Hydravitics, All safety leatures, flaps, lights, 2 150° All safety leatures, flaps, lights, 3 150° All safety leatures, flaps, lights, 4 160° All safety leatures, flaps, lights, 5 160° All safety leatures, flaps, lights, 5 160° All safety leatures, flaps, lights, 6 160° All safety leatures, flaps, lights, 7 160° All safety leatures, flaps, lights, 8 160° All safety leatures, flaps, lights, 8 160° All safety leatures, flaps, lights, 9 160° All safety leatures, flaps, lights, 1 160° All safety leatures, flaps, lights, 1 160° All safety leatures, flaps, lights, 1 160° All sa	·	The state of the s	·				
Mote: Part of specifications may be Godwin Et Series specific. Please bid equal equipment.		The strong straining and outside vendors and for companies that a series	ricine.				
VEHICLE AND DUMP BED SPECIFICATIONS F Dump Bed Specifications (Beds being offered shall be equal to the following Meat Specifications (Beds being offered shall be equal to the following Meat Specifications specifications (Reds being offered shall be equal to the following Meat Specifications specifications) 1 RNS Gotwin Truck Body Company Model EL 16082311 Yas No 2 Elliptical floor, length 192, Pivot 180 degrees, Inside width 86, Side height 52. 3 Oustern single acting hold, Electric Tarp system-8200. 4 d'arrianter oylinder rod(3) stage cylinder with 2000 PSI Holst lifting capacity Sc, 540 lbs. (28 ton) 5 Holst lifting capacity Sc, 540 lbs. (28 ton) 6 140° cylinder stocks 1 (50 degree dump angle 190 lbs. (28 ton) 1 (50 degree dump angle 190 lbs. (28 ton) 1 (60 Using yard capacity) 1 (60 Using	·	Total to specifications fliav be Freightliner specific Diones Eld				··	
Dump Bed Specifications (Beds being offered shall be equal to the following Meet Specifications	Ë	indice Part of specifications may be Godwin EL series specific. Please hid equal equipme					
Uniting bed Specifications (Bods being offered shall be equal to the following imperiations) specifications (Piss Specifications) specifications (Piss Specifications) 1 RVS Godwin Truck Body Company, Model EL 1805/2311 2 Elliptical floor, length 192, Pivot 180 degrees, Inside width 86, Side height 52. 3 Clustom single acting hoist, Electric Tarp system 8200. 4 6* diameter cylinder rot(8) stage cylinder with 2000 PSI 4 hoist lifting capacity 65, 540 lbs. (28 lon) 5 Hoist lifting capacity 65, 540 lbs. (28 lon) 6 140* cylinder stroks 7 80 degree dump angle 8 High Ilft gate (6*) opening discharge 9 16 Cubic yard capacity 10 Fender bottom rati 10 gauge, Wood Board gusset height 6*, Bulkhead 74. 11 All Hydraulics, All safety features, flaps, lights, 12 Air shift PTO 13 Asphalt apron, Deck 114* AR450,Sides 3/16* AR450, Rear post material 1/4* high tensile 14 Air operated tailgate, High Ilft, Height 86, Malerial, 3/16* hardox AR450, air operated controls. Vehicle Configuration 1 1145D CONVENTIONAL, CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 1 TRALLER TOWING PROVISION AT END OF FRAME FOR TRUCK 5 FREIGHTLINER LEVEL II WARRANTY 6 EXPECTED FROM AXLE(5) LOAD: 18000.0 lbs. 6 EXPECTED PROME AXLE(5) LOAD: 18000.0 lbs. 6 EXPECTED PROME AXLE(5) LOAD: 18000.0 lbs. 6 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 6 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 78350.0 lbs. 6 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 6 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 7 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 7 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 7 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 8 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 8 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 8 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 9 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 9 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 9 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 9 EXPECTED AIL 480 HP @ 1800 RPM, 280 GROV RPM, 1650 LB/FT @ 1100 RPM 10 END RPM 20 RPM 20 RPM 20 RPM 20 RPM 20	******	YEARLY F AND DUMO DED COERCE 22.2	**************************************		j.	:	- 1 .
Regionations) Rivis Goldwin Truck Body Company Model EL 18052311 Goldwin Stoke Company C	F	Dump Bed Specifications (Beds being offered shall be equal to the following	Mont Pe				
2 Elliplical loos, length 192, Pivot 180 degrees, inside width 86, Side height 52. 3 Custom single acting hold, Electric Tarp system-8200. 4 6" diamister cylindor rod(3) stage cylinder with 2000 PSI Holst illing capacity 56,540 lbs. (28 ton) 6 140" cylindor stroke 7 50 degree dump angle 1 lifty cylindor stroke 9 16 Cubic yard capacity 10 Fender bottom rall 10 gauge, Wood Board gusset height 8", Bulkhead 74. 11 All Hydraulics, All safety features, flaps, lights, Ar shift PTO 13 Asphalt apron, Deck 1/4" AR450, Sides 3/16" AR450, Rear post material 1/4" high tensile 14 Air operated tailgate, High lift, Height 56, Material, 3/16" hardox AR430, air operated controls. 14 Air operated tailgate, High lift, Height 56, Material, 3/16" hardox AR430, air operated controls. 15 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 16 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 17 FREIGHTHISER LEVEL II WARRANTY 18 EXPECTED PRONT AXLE(S) LOAD: 18000.0 lbs. EXPECTED PRONT AXLE(S) LOAD: 18000.0 lbs. EXPECTED PRORES AXLE(S) LOAD: 12850.0 lbs. EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 78350.0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 1 DOI 12' 18.0 40 PP @ 1800 RPM, 2800 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPAICARB MISSION CERTIFICATION 3 DR 12' 180 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THEADED STUD BATTERRES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX		[specifications]	—- I—————,,,	T10	i	****	
Eliptocal floor, length 192, Privat 180 degrees, Inside width 86, Side height 52. Outstom single acting holds, Electric Tarp system-8200. Inside acting apacity 56,540 flos. (28 for) Holds lifting capacity 56,540 flos. (28 for) Inside acting apacity 56,540 flos. (28 for) Inside acting apacity 56,540 flos. (28 for) Inside acting acting acting acting apacity 56 degree dump angle Inside acting act	1	IR/S Godwin Truck Body Company Model EL 16052311	Yes	NO.		·	
Justim single acting host, Electric Tarp system-6200. 4 of disameter cylinder rod(3) stage cylinder with 2000 PSI Holst lifting capacity 56,540 lbs. (26 ton) 5 Holst lifting capacity 56,540 lbs. (26 ton) 6 140' cylinder stroke 7 150 degree dump angle 8 High lift gate (5) opening discharge 9 16 Cubic yard capacity 10 Fender bottom rall 10 gauge, Wood Board gusset height 5', Buikhead 74. 11 All Hydraulics, All safety features, flaps, lights, 12 Air shift PTO 13 Asphalt apron, Deck 1/4' AR450,Sides 3/16' AR450, Rear post material 1/4' high tensile 14 Air operated tailgate, High lift, Height 56, Material, 3/16' hardox AR450, air operated controls. Vehicle Configuration 1 1145D CONVENTIONAL CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 1 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 5 FREIGHTLINER LEVEL II WARRANTY 6 EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs. EXPECTED PISHER AXLE(S) LOAD: 46000.0 lbs. EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. 6 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 1 DD13 12.81.450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CABB EMISSION CERTIFICATION 1 DR 12Y 180 AMP 28-SI CUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE 1 G) ALLIANGE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	2	Elliptical floor, length 192, Pivot 180 degrees, Inside width 86, Side height 59				77.50	1
4 G' diarrieter cylinder rod(3) stage cylinder with 2000 PSI 5 Holst lifting capacity 56,540 lbs. (28 ten) 6 140° cylinder stroke 7 160 degree dump angle 8 High lift gate (6) opening discharge 9 16 Cubic yard capacity 10 Fender bottom rail 10 gauge, Wood Board gusset height 8", Buikhead 74. 11 All Hydraulics, All safety features, flaps, lights, 12 Air shift PTO 13 Asphalt apron, Deck 1/4" AR450, Sides 3/16" AR450, Rear post material 1/4" high tensile 14 Air operated taligate, High lift, Height 56, Material, 3/16" hardox AR450, air operated controls. Vehicle Configuration 1 114SD CONVENTIONAL CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 1 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 5 FREIGHTLINER LEVEL II WARRANTY 6 EXPECTED FRONT AXLE(5) LOAD: 18000 lbs. 1 EXPECTED FRONT AXLE(5) LOAD: 18000 lbs. 1 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 1 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 1 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 1 DD 12.8 L450 HP @ 1600 RPM, 2080 GÖV RPM, 1650 LBIFT @ 1100 RPM 2 2010 EPACARB EMISSION CERTIFICATION 1 DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE 1 BATTERY VOLT SENSE 1 G) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA 1 THREADED STUD BATTERIES 1 POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MCUNTED NEARION BATTERY 1 TRAY/BOX	3	Custom single acting hoist, Electric Tare system-6200		~ } .			
Most litting capacity 56,540 lbs. (28 ten)	4	6" diarrieter cylinder rod(3) stage cylinder with 2000 ps					
6 140' cylinder stoke 7 50 degree dump angle 8 High lift gate (6') opening discharge 9 16 Cubic yard capacity 10 Fender bottom rail 10 gauge, Wood Board gusset height 8", Bulkhead 74. 11 All Hydraulics, All safety features, flaps, lights, 11 Ali rishift PTO 13 Asphalt apron, Deck 114" AR450, Sides 3/16" AR450, Rear post material 1/4" high tensile 14 Air operated tailigate, High lift, Height 66, Material, 3/16" hardox AR450, air operated controls. 14 Interpretation 11 Ali Stoch Ventice Configuration 12 Specify Model, YeAR 15 Specify Model, YeAR 16 Set FORWARD AXIE. TRUCK 17 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 18 FREIGHTLINER LEVEL II WARRANTY 18 EXPECTED FRONT AXIE(S) LOAD: 18000.0 lbs. 19 EXPECTED FRONT AXIE(S) LOAD: 12350.0 lbs. 10 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 10 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 10 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 10 DD13 12.8 L450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 10 DR 12V 180 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE 10 POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	5	Heist lifting capacity 56,540 lbs. (28 ton)					- +
7 50 degree dump angle 8 High lift gate (6') opening discharge 9 16 Cubic yard capacity 10 Fender bottom rail 10 gauge, Wood Board gusset height 8", Bulkhead 74. 11 Ail Hydrauliss, All safety features, flaps, lights, 12 Air shift PTO 13 Asphalt apron, Deck 1/4" AR450, Sides 3/16" AR450, Rear post material 1/4" high tensile 14 Air operated tailgate, High lift, Helght 56, Material, 3/16" hardox AR450, air operated controls. Vehicle Configuration 1 114SD CONVENTIONAL CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 4 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 5 FREIGHTLINER LEVEL II WARRANTY 6 EXPECTED FRONT XLLE(S) LOAD: 18000.0 lbs. 7 EXPECTED FRONT XLLE(S) LOAD: 12350.0 lbs. 8 EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. 9 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 9 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 10 DD13 12.8 L450 HP @ 1800 RPM, 2080 GOV PMM, 1650 LB/FT @ 1100 RPM 12 2010 EPA/CARB EMISSION CERTIFICATION DR 127 IN 100 PMM, 1650 LB/FT @ 1100 RPM 13 2010 EPA/CARB EMISSION CERTIFICATION BATTERY VOLT SENSE 14 POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY 15 TRAY/BOX	6	140° cylinder stroke				1	
High lift gate (6') opening discharge 16 Cubic yard capacity 17 Fender bottom rail 10 gauge, Wood Board gusset height 8", Bulkhead 74. 18 Hydraulics, All safety features, flaps, lights, 19 All Hydraulics, All safety features, flaps, lights, 20 All shift PTO 21 Asphalt apron, Deck 1/4" AR450,Sides 3/16" AR450, Rear post material 1/4" high tensile 21 All operated tailgate, High lift, Height 66, Material, 3/16" hardox AR450, air operated controls. 22 Vehicle Configuration 23 SET FORWARD AXLE - TRUCK 24 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 25 FREIGHTLINER LEVEL II WARRANTY 26 EXPECTED FRONT AXLE(8) LOAD: 18000.0 lbs. 26 EXPECTED READ RRIVE AXLE(8) LOAD: 46000.0 lbs. 27 EXPECTED PROHER AXLE(S) LOAD: 12350.0 lbs. 28 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 29 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 20 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 20 EXPECTED ROADS COMBINATION WEIGHT: 80000.0 lbs. 20 EXPECTED ROADS COMBINATION WEIGHT: 80000.0 lbs. 20 EXPECTED SHIP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 20 2010 EPA/CARB EMISSION CERTIFICATION 20 DR 12V 180 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE 37 BALLIANGE MODEL 1231, GROUP 31, 12 VOLT MAINTENANGE FREE 3375 CCA 27 THREADED STUD BATTERIES 28 POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED MEAR/ON BATTERY 28 TRAY/BOX				1		***************************************	
16 Cubic yard capacity 16 Fender bettem rail 10 gauge, Wood Board gusset height 8", Bulkhead 74. All Hydraufies, All safety features, flaps, lights, 11 All Hydraufies, All safety features, flaps, lights, 12 Air shift PTO 13 Asphalt apron, Deck 1/4" AR450, Sides 3/16" AR450, Rear post material 1/4" high tensile 14 Air operated tailgate, High lift, Height 56, Material, 3/16" hardox AR450, air operated controls. Vehicle Configuration 1 114SD CONVENTIONAL CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 1 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 5 FREIGHTLINER LEVEL II WARRANTY 6 EXPECTED RONT AXLE(S) LOAD: 18000.0 lbs. EXPECTED REAN DRIVE AXLE(S) LOAD: 46000.0 lbs. EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. EXPECTED BROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION CERTIFICATION 3 DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA 1 THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY 1 TRAY/BOX				7	† ~~~ ~~~		
Fender bottom rall 10 gauge, Wood Board gusset height 8", Bulkhead 74. All Hydrauliss, All safety features, flaps, lights, Asphalt apron, Deck 1/4" AR450,Sides 3/16" AR450, Rear post material 1/4" high tensile Alr operated taligate, High lift, Height 56, Material, 3/16" hardox AR450, air operated controls. Vehicle Configuration 1	9	16 Cubic yard caposity			<u> </u>		
Ashali apron, Deck 1/4" AR450, Sides 3/16" AR450, Rear post material 1/4" high tensile Air operated tailgate, High lift, Height 56, Material, 3/16" hardox AR450, air operated controls. Vehicle Configuration 1 114SD CONVENTIONAL CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 4 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 5 FREIGHTLINER LEVEL II WARRANTY 6 EXPECTED REAR DRIVE AXLE(S) LOAD : 18000.0 lbs. EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs. EXPECTED QROSS VEHICLE WEIGHT CAPACITY : 76350.0 lbs. DEXPECTED GROSS VEHICLE WEIGHT CAPACITY : 76350.0 lbs. DOING 13 L.8. L450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION DERTIFICATION DR 12V 180 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERRY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	10 1	Fender bottom roll 10 course 184. 1.5	·				
Asphalt apron, Deck 1/4* AR450, Sides 3/16* AR450, Rear post material 1/4* high tensile Air operated taitgate, High lift, Height 56, Malerial, 3/16* hardox AR450, air operated controls. Vehicle Configuration 1 114SD CONVENTIONAL CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 4 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 5 FREIGHTLINER LEVEL II WARRANTY 6 EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs. EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76360.0 lbs. EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76360.0 lbs. DD 13 12.81.450 HP @ 1890 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION CERTIFICATION DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MCUNTED NEAR/ON BATTERY TRAY/BOX	11	All Hydraulics All a-f-t-t-f-t-f-t-f-t-f-t-f-t-f-t-f-t-f-t-		· · · · · · · · · · · · · · · · · ·			
Asphalit apron, Deck 1/4* AR450, Sides 3/16* AR450, Rear post material 1/4* high tensile Air operated tailgate, High lift, Height 56, Material, 3/16* hardox AR450, air operated controls, Vehicle Configuration 1 1145D CONVENTIONAL CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 4 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 5 FREIGHTLINER LEVEL II WARRANTY 6 EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs. 7 EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. 8 EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. 9 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 10 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 11 DD13 12.81 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 12 2010 EPA/CARB EMISSION CERTIFICATION 13 DR 12V 180 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE 14 BATTERY VOLT SENSE 15 (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MCUNTED NEAR/ON BATTERY TRAY/BOX	12 -	ai riyoladiks, Ali safety features, flaps, lights,				, i	
Vehicle Configuration 1 114SD CONVENTIONAL CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 4 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 5 FREIGHTLINER LEVEL II WARRANTY 6 EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs. 6 EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. 7 EXPECTED PUSHER AXLE(S) LOAD: 46000.0 lbs. 8 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 9 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 1 DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION CERTIFICATION 3 DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE 4 (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX			·			·	
Vehicle Configuration 1	13	Asphalt apron, Deck 1/4" AR450, Sides 3/16" AR450, Rear post material 1/4" high tensile	-	-	1	-	_
Vehicle Configuration 1 114SD CONVENTIONAL CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 4 TRÄILER TOWING PROVISION AT END OF FRAME FOR TRUCK 5 FREIGHTLINER LEVEL II WARRANTY 6 EXPECTED FRONT AXLE(S) LOAD : 18000.0 lbs. 7 EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs. 8 EXPECTED PUSHER AXLE(S) LOAD : 12350.0 lbs. 9 EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 76350.0 lbs. 1 EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs. 1 DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION CERTIFICATION 3 DR 12V 180 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE 4 (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	14 %	Air operaled tailgate, High lift, Height 56, Material, 3/16" hardox AR450, air operated contro	i. Ols	1	· - ·		
1 114SD CONVENTIONAL CHASSIS 2 SPECIFY MODEL YEAR 3 SET FORWARD AXLE - TRUCK 4 TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK 5 FREIGHTLINER LEVEL II WARRANTY 6 EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs. 7 EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. 8 EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. 9 EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 10 EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. 11 DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 12 2010 EPA/CARB EMISSION CERTIFICATION 13 DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE 14 (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA 1 THREADED STUD BATTERIES 1 POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY 1 TRAY/BOX						· •	·
SPECIFY MODEL YEAR SET FORWARD AXLE - TRUCK TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK FREIGHTLINER LEVEL II WARRANTY EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs. EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2010 EPA/CARB EMISSION CERTIFICATION DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	/ehicle Configuration	•	•	į		-
SET FORWARD AXLE - TRUCK TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK FREIGHTLINER LEVEL II WARRANTY EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs. EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. EXPECTED REAR DRIVE AXLE(S) LOAD: 12350.0 lbs. EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2010 EPA/CARB EMISSION CERTIFICATION BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	1 1	14SD CONVENTIONAL CHASSIS	1 - 1 - 1 - 1				······································
TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK FREIGHTLINER LEVEL II WARRANTY EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs. EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION CERTIFICATION BOR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX				4		,	
EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs. EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. DD13 12.81 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION CERTIFICATION DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	3 S	ET FORWARD AXLE - TRUCK		-1			
EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs. EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. DD13 12.81 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION CERTIFICATION DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	4 T	RAILER TOWING PROVISION AT END OF FRAME FOR TRUCK			: 1m	· · ·	1
EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION CERTIFICATION DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX) H	REIGHTLINER LEVEL II WARRANTY	 	; -			
EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs. EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION CERTIFICATION DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	6 E	XPECTED FRONT AXLE(S) LOAD: 18000.0 lbs.	·			- 1	
EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. DESCRIPTION OF THE WEIGHT CAPACITY: 76350.0 lbs. DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION CERTIFICATION B DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	7 E	XPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs.		;			
EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs. DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2 2010 EPA/CARB EMISSION CERTIFICATION B DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	3 E	XPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs.					-
DESTRUCTED GROSS COMBINATION WEIGHT: 80000.0 ibs. DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2010 EPA/CARB EMISSION CERTIFICATION DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX) E)	XPECTED GROSS VEHICLE WEIGHT CAPACITY · 76350 0 lbs		· · · · · · · · · · · · · · · · · · ·			
DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM 2	0 E)	KPECTED GROSS COMBINATION WEIGHT , ANDON O INC.				-	1
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	1 DE	213 12.8L 450 HP @ 1800 RPM 2080 GOV RPM 4650 LB/FT @ 4400 PPM				· †	1
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	2 20	110 EPA/CARB EMISSION CERTIFICATION	·		·		
BATTERY VOLT SENSE (3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	3 DF	R 12V 160 AMP 28-SI OLIADRAMOUNT DAD ALTERNATOR					
(3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	ВА	ATTERY VOLT SENSE	·	·			
POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX							1
POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX	(V) TH	REPARED STID BATTERIES	•	• !			i
TIME PLACE	. (1)	MEADED STOD BATTERIES		;		:	
TIME PLACE	D A	OTHER AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY		,		ŧ	!
ZF-SACHS 15-1/2 INCH TWIN XTEND ULTRA SOFT DAMPER CERANIC CLUTCH	PO	H I (PM 1A					•
A STATE OF THE SECOND OF THE PROPERTY OF THE P				, ,			

17	7 TORQUE LIMITING CLUTCH BRAKE
18	
19	BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY
	VALVE VALVE
20	FI FOTRONIC ENGINE INTECDAL OUT TROUBLE
21	The state of the s
22	PHOLITICARD UNDER CALCULATION OF THE CALCULATION OF
22	THE PROPERTY OF THE PROPERTY OF THE PROPERTY AND A CONTRACT OF THE PROPERTY OF
23	PROCESSOR WITH EN BESTELAK MOUNTED VERTICAL TAIL DIDE
20	
. ,	THE OF THE WAND DASH MOUNTED REGENERATION REQUIES TOWARD
24	DRIGHT UPPER STACK(S)
25	THE STATE OF THE PARK
26	THE SECTION OF THE PROPERTY OF
27	DUC SUPPLIED ENGINE MOUNTED FUEL EIL TER/FUEL WATER CERADATION
	THE PROPERTY OF THE PROPERTY O
28	1500 SQUARE INCH ALUMINUM RADIATOR
29	DELCO 12V 39MT+ HD/OCP STARTER WITH THERMAL PROTECTION AND
•	INTEGRATED MAGNETIC SWITCH
30	ALLISON AUTOMATIC 4500 RDS TRANSMISSION
31	MFS-18-133A 18,000# FL1 SINGLE FRONT AXLE
32	MERITOR 16 5X6 0+ CAST SPICED CAM COOKED DRAWS
	IMERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR,
33	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS
34	TRW THE SO POINT STACK ADJUSTERS
35	TRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR
36	ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE
37	18,000# TAPERLEAF FRONT SUSPENSION
38	FRONT SHOCK ABSORBERS
	RT-46-160P-46,000# R-SERIES TANDEM REAR AXLE
39	4.30 REAR AXLE RATIO
40	MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES
41	MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND
	, and the second
42	DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES
- tom	
43	(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK
	I DINTAND REAR AXLE VALVE
44	MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR,
	FABRICATED SHOES
45	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)
46	TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION
47	TUFTRAC STANDARD RIDE HEIGHT
	56 INCH AXLE SPACING
	FORE/AFT AND TRANSVERSE CONTROL RODS
	HENDRICKSON DADALIET III TDA III LIGA COLURA
:	HENDRICKSON PARALIFT ULTRA HLUCZ COMPOSILITE 13,200# AIR LIFT
	STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE
. d	FERNISHUS VIDA LIJA 40 0000 BUOLEE AAG - OO-
51 !	SUSPENDIONS
51 !	HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS (1) DASH VALVE AND (1) GAUGE FOR SINGLE LIFT AXLE

,

53	DEVENOE HET 100 - When he was
	REVERSE LIFT AXLE WIRING WITH LAST STATE RETENTION WITH IGNITION OFF
54	AIR PIPING FOR (1) LIFT/NON-LIFT AXLE WITH REGULATOR CHASSIS MOUNTED
55	MERITOR 15X4 Q+ CAM PUSHER/TAG BRAKES, DOUBLE ANCHOR, FABRICATED
56	MERITOR AUTOMATIC PUSHER/TAG SLACK ADJUSTERS
57	HENDRICKSON HLUC2 13,200# AIR LIFT STEERABLE PUSHER AXLE SUSPENSION
	TO THE STATE OF THE PUSHER AXLE SUSPENSION
58	WABCO 4S/4M ABS WITHOUT TRACTION CONTROL
59	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED THROUGH IGNITION
60	SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME
61	5650MM (222 INCH) WHEELBASE
62	11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI
63	1/4 INCH (6MM) C-CHANNEL INNER FRAME REINFORCEMENT
64	HEAVY DUTY SUSPENSION CROSSMEMBER
65	16.5 INCH CHROME STEEL STRAIGHT BUMPER
66	100 GALLON/378 LITER ALUMINUM FUEL TANK - LH
67	GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES
68	GOODYEAR G288 11R22.5 16 PLY RADIAL REAR TIRES
69	GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES
70	CONMET PRE-SET BEARING ALUMINUM REAR HUBS
71	ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC
72	ACCURIDE 29644A 22,5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS
73	ACCURIDE 29644A 22:5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG
74	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB
75	AIR CAS MOUNTS
76	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE
77	CHROMED HOOD MOUNTED AIR INTAKE GRILLE
78	DUAL 26 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS ROOF MOUNTED
79	DUAL HORN SHIELDS
80	HALOGEN COMPOSITE HEADLAMPS WITH BRIGHT BEZELS
81	DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE
82	DOOR MOUNTED MIRRORS
83	LH AND RH 8" BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS
84	TINTED DOOR GLASS LH AND RH WITH TINTED OPERATING WINDOWS
	RH AND LH ELECTRIC POWERED WINDOWS
87	INTERIOR CONVENIENCE PACKAGE WITH CB PROVISION
	2-1/2 LB. FIRE EXTINGUISHER HEATER DEEDOSTER AND AID CONDITIONED
00	HEATER, DEFROSTER AND AIR CONDITIONER

89	CAB INSULATION				
90	SOLID-STATE CIRCUIT PROTECTION AND FUSES				
91	LH AND RH ELECTRIC DOOR LOCKS				
92					
93	(1) 12 VOLT POWER SUPPLY IN DASH				-
94	TRIANGULAR REFLECTORS WITHOUT FLARES				
	BOSTROM TALLADEGA 910 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH AIR LUMBAR				
95	HIGH BACK NON SUSPENSION PASSENGER SEAT				
96	LH AND RH INTEGRAL DOOR PANEL ARMRESTS				_
97	CLOTH DRIVER SEAT COVER				
98	CLOTH PASSENGER SEAT COVER	-			
99	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN				
100	97 DB BACKUP ALARM				es magadana, ristori, i -
101	ELECTRONIC CRUISE CONTROL WITH SWITCHES ON AUXILIARY GAUGE PANEL (B DASH PANEL)				
102	ODOMETER/TRIP/HOUR/DIAGNOSTIC/VOLTAGE DISPLAY: 1X7 CHARACTER, 26 WARNING LAMPS, DATA LINKED, ICU3				
103	DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1939, LOCATED BELOW DASH				_
104	2 INCH ELECTRIC FUEL GAUGE			_	ĺ
105	FUEL FILTER RESTRICTION INDICATOR				
106	DUAL REAR AXLE TEMPERATURE GAUGES FOR TANDEM AXLES				
107	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE				
108	ENGINE OIL TEMPERATURE GAUGE				
109	2 INCH TRANSMISSION OIL TEMPERATURE GAUGE				
110	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY				
111	ELECTRIC ENGINE OIL PRESSURE GAUGE				-
112	AM/FM/WB RADIO WITH FRONT AUXILIARY INPUT				
113	DASH MOUNTED RADIO				
	ELECTRONIC 3000 RPM TACHOMETER				
	TRAILER HAND CONTROL BRAKE VALVE				
116	SELF-CANGELING TURN SIGNAL SWITCH WITH DIMMER, WASHER-WIPER AND				
	HAZARD IN HANDLE			1.77.	
1	PAINT: ONE SOLID COLOR				
	CAB COLOR (EQUAL TO L5495EB ULTRA RED PEARL METALLIC ELITE BC)				
119	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT				
	Militer constru				
	Total VVBIQITE 19.018 Ins		T		
1 E	Unit cost and buy back proposal Bidder shall list the purchase price per unit here and on top sheet.\$ 145, 435				
2 E	Ridder shall list the guaranteed there (2) and (5) and (5) are				
	Bidder shall list the guaranteed three (3) year/150,000 mile dealer buy back price here per unit and o	n top shee	1.8 92,0	00	



4700 SF SB

\$156 | West | Sec. Stands | 2 Emile | 12 Emile





Serious trucks.

	201	9 M	ack	Grant	fe	tri-	αv
CRAIGHEAD COUNTY					1	1	<u> </u>
INVITATION TO BID Not an Order							
Craighead County Judge's Office	- Lagrange Committee	<u> </u>					
511 Union St.; Suite 119						- In-	
Jonesboro, Arkansas 72401					T	4-19-0-	
PURCHASING OFFICE						,-	
3ID NO. 2018-7	DATE: A	pri) <u>17, 2</u> (<u>) 18</u>		1		
Sealed bids, subject to the conditions on the reverse hereof, and as may be attached hereto, i	vill be rece	ived at th	s office)			
mul <u>22:00:PM May 2, 2018</u> and then publicly opened, for furnishing the supplies, materials:							en) promise
nd/or services as described below.						T	ستر سهداروسه
A Company of the Comp	Bids will b	e opene	d May 2	2:2018.		1	
A Control of the Cont	- Amer	2:00 P.M			· · ·	<u> </u>	
O.B. Jonesboro, Arkansas	BY: Al Ha	ines			_	1 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 -	
Aaximum Delivery or completion time after issuance of Purchase	PURCHA	SING DIF	RECTO	R.			
order or work ordered by County 120 days: - 60-90 day delivery		,,,	1	·			تعامضات
TEM # DESCRIPTION /	QUANT	UNIT	UNIT	PRICE	AMO	LINIT	
1 Furnish two (2) each Dump Trucks with Automatic transmissions and with	2				1 / 11/10	OFA!	
installed dump beds to Craighead County Road Department, 2800 Moore		of other was a section of the sectio	4	· · · · · · · · · · · · · · · · · · ·		<u> </u>	
Road, Jonesboro, AR, 72401 according to attached specifications. Trucks are		 	 	منشه ومنهج وروده ومنا	·		
to have dump beds and hydraulics installed and fully operational when delivered.	·	1	1	dela articularia <u>, ii</u>		·	سندهث
2. This bid package contains 6 pages. All 6 pages must be returned	1	ļ	·		<u>i</u>		سنست
to complete bid.	ļ		<u> </u>	· · · · · · · · · · · · · · · · · · ·		ومن المساورة المساورة المساورة المساورة المساورة المساورة المساورة المساورة المساورة المساورة المساورة المساورة	استندها
Bid must be signed by authorized company representative.	<u> </u>		 -				
4 Bidder should		<u> </u>	 	فزيت سنشره دو والعد			
A. Clearly define and list warranty information on each item in years.							
B. Include all labor, delivery charges, training, programming,	<u></u>		ļ				
and any other charges FOB Jonesboro, Arkansas 72401, in bid price.		· · · · · · · · · · · · · · · · · · ·	ļ				
C. Include product literature and specifications with bid.			1	an alamata ist			
All relations listermation will be available and the control of th	ieros A. Visa estado.				, <u>-</u>		
D. All relevant information will be considered when determining best bid for Graighea E. Specify cash discounts, if available.	d County.			يت ينظم عند مناه			
F. Note bid number on outside of bid envelope.		**************************************			1		
		riona-in-motor					
G. Specify approximate ship time in days, if awarded bid.			<u> </u>				
F. List make, model, and manufacturer of equipment being offered.		distriction and the second second second					
G. Quote same oriequal equipment in all aspects.	نسين تست	ر د <u>ر خار ترسمت</u>		2 <u>4 2 4 1 1 2 2 4 4 4 4 4 4 4 4 4 4 4 4 4 </u>			
H. Specify nearest service and parts supply location to Jonesboro, AR,		· · · · · · · · · · · · · · · · · · ·	-	ر در برین کرد اور در			
5 Does bidder meet all dump truck specifications? Yes \ No.		***************************************	-				
If no, clearly list and define differences on a separate sheet.	:				***: ****		
6 Attached equipment list with names and part numbers is for reference.	·					- Constant Paris - Supply	
Bidder should publicital bid price on this sheet. Total bid price is \$ 295,520						or	
8 Bidder shall list purchase price per unit here: \$147,760 Buyback price per unit her	re. \$ <i>[05</i>]	000					
EXECUTION OF BID	Date 5 -	1-18	April a rise manuscritta.				~
e, the undersigned, have read all the requirements set forth in this bid proposal including spec	cifications.	ila ana fairte		· · · · · · · · · · · · · · · · · · ·			\neg
tructions, conditions, and pertinent information regarding the articles being bid on, and we ag	ree to fum	ish		· · · · · · · · · · · · · · · · · · ·			
icles at the prices stated.						 	
kansas Use Tax Register No. 00 // 63 96 - 545 Tri. 5	tate	Tru	ck	Cente	(I)	16	
ider Jangen Flund Address 1333 & Parker rd.	Tonesbo			7240	- '		·
(Person Authorized to Sign Bids) Title Salesman		· <u>* </u>	/	1017			
UNSIGNED BIDS WILL BE REJECTED						undiame our school	
BIDS ARE SUBJECT TO REJECTION UNLESS SUBMITTED (AN TUIC F	ADM	سدسند			رنسوس مشرست	
NOTICE TO BIDDERS, SEE REVERSE SIDE OR ATTACHMENTS FOR INSTRUCTIONS	ם מותו אוכ בממחנות	OKINI	<u>.</u>				
A DIRECTOR ALPHA SUME DIDE OU VI (VOLINCIA DE LON INDI KOCHONZ	AND CON	INTTONS),		<u> </u>	<u> </u>	. 1

	CRAIGHEAD COUNTY
	JONESBORO, ARKANSAS
(mainten) (Charles and a	CONDITIONS OF BIDDING
	Compliance with the following conditions is necessary for consideration of this bid.
1.	Signature-This bid must be signed with the firm name and by an authorized officer employee or agent
Ž	Sales Tax-is not to be shown in the bid price, but is to be added by the vendor to the invoice billing to the County.
······································	The County is exempt from Arkansas State Sales Tax on road equipment and vehicles. Confractors are to include all costs
	Into the bid price, including applicable taxes.
3	Freight and other delivery charges to destination at designated County facility in the County must be included in bid.
-	Charges may not be added after the bid is opened.
4	Discounts-Show rate, total amount, and latest day any discounts will be allowed after receipt of article and involce,
	otherwise County will deduct allowed discount when payment is made,
5	Elm Price All prices quoted will remain firm for at least 30 days from date of bid, unless otherwise specified
am partiti annay	by the County or bidder
6	Tax Exempt Graighead County is exempt from State sales tax on self propelled equipment and motor vehicles.
	Example: Motor graders, excavators, dozers, dump trucks, pickup trucks, etc.
7	identical Bids in the event of two or more identical low bids, the contract may be awarded arbitrarily or for
	any reason to any of such bidders, or split in any proportion between the said two or more bidders at discretion of the County.
8	Clean up-Complete cleanup and proper disposal of any and all job related items is considered to be a part of any
	contract let by Craighead County.
9	Ambiguity in bid-Any ambiguity in any bid as the result of omission, error, lack of clarity or non-compliance
r-ministerie — 1,4,4,4 <u>2,4</u>	specifications, instructions, and all conditions of bidding shall be construed in the light most favorable to the County
10	Construction
. 1-4	A. When requested, the Contractor is to supply the County with evidence of having and maintaining proper and
	specifically Workman's Compensation insurance in accordance with the laws of the State of Arkansas.
	Public:Liability, and Property Damage. All premiums and cost shall be paid by Contractor. In no way will the
12-12-1-1	County be responsible in case of accident:
trikupa er engelemen ikabe	B. A Performance Bond equaling the total amount of any bid exceeding \$20,000 must be provided for
	erection of any public building, public structure, or public improvement (Pursuant to Arkansas Code 18-44-503.)
11	The County reserves the right to reject any and all bids, accept in whole or in part, to waive informalities in bids.
	received, to accept bids on materials or equipment with variations from specifications in those cases where efficiency
<u> Lawrence — de</u>	of operation will not be impaired, and unless otherwise specified by bidder, to accept any Item in the bid. If unit prices
	and extensions thereof, do not coincide, the County may accept the bid for the lesser amount whether reflected
	by extension or by the correct multiple of the unit price.
	INSTRUCTIONS TO BIDDERS (Please read carefully)
7	Submit bid on bid form attached or reverse side of this sheet.
2	Address all bids to; Purchasing Director, Craighead County Judge's Office, 511 Union St.; Suite 119,
	Jonesboro, Arkansas 72401 and make certain to indicate identifying bid number on the outside of bid envelope.
3	DO NOT include Federal Excise Tax in bid. County will furnish exemption certificate.
4	Sate Manufacturer, Brand Name, Model, etc. for each item bid on.
5	Samples of items, when required must be furnished free, and, if not called for within 30 days from date of
	bid opening, will be disposed of by the County
6	Bids received after stated time will not be considered.
7	Be sure and read all conditions and verify amounts before submitting bids. No changes or additions will be
	allowed after submission.
8	Guarantees and warranties should be attached as a part of the bid, as they may be a consideration in awarding contract.
9	Delivery or contract completion time is to be shown, as this date may, where time is of the
	essence, determine the contract award.
10	Additional information may be obtained from the Purchasing Department.
· · · · · · · · · · · · · · · · · · ·	THE COUNTY RESERVES THE RIGHT TO ACCEPT PART OR ALL OF ANY SPECIFIC BID OR BIDS
	AND TO ACCEPT BID WITH OR WITHOUT TRADE-IN, AND REJECT ANY AND ALL BIDS.
	ž

	Genera	<u></u>						<u> </u>
A	Trucks (automatic transmissions) and dump beds shall be the latest year model in curren	المادة الاعتمال	 الأثار في	ارورسورسین ۱۳۰۰ دی.	1			
44	by manufacturer and shall meet all federal emissions and all other EPA regulations (Spe	it broauctio	n With	provei	n perton	nance	<u> </u>	
В	All bidders shall offer a guaranteed three (3) year dealer buy back program and clearly do	city year m	iodel)		<u> </u>			
	buy back dollar amount, time frame and mileage and other criteria for the buy back program	etining			ļ	بندية فتعلقه فتحلب		
C	Bidder shall hid trick and fined with a three (2) year (150 000). It is a large shall hid trick and fined with a three (2) year (150 000).	am.			<u> </u>			
	Bidder shall bid truck and bed with a three (3) year/150,000 mile dealer buyback program	<u>b:</u>			<u> </u>			
Ď	Dealer should guarantee any outside vendors and for companies that supply buy back pr	icing.		···				
E	Note: Part of specifications may be Freightliner specific; Please bid equal equipment.			13 - 5446 - Ser Samuel Anne		· · · · · · · · · · · · · · · · · · ·		
	Note: Part of specifications may be Godwin EL series specific. Please bid equal equipme	<u>řít.</u>	7- 16v hamme	·······		-		
	VEHICLE AND DUMP BED SPECIFICATIONS		ــــــــــــــــــــــــــــــــــــــ					
F	Dump Bed Specifications (Beds being offered shall be equal to the following	Meet So	ecifica	ations		·		
	specifications)	Yes	1	Nó				
1	R/S Godwin, Truck Body, Company, Model EL 16052311							
2	Elliptical floor, length 192, Pivot 180 degrees, Inside width 86, Side height 52.			Service Contractor			1	
3	Custom single acting hoist. Electric Tarp system 6200						1	
4	6" diameter cylinder rod(3) stage cylinder with 2000 PSI	//						TWO INCHES OF THE PARTY OF THE
5	Hoist lifting capacity 56,540 lbs. (28 ton)					raman ner salvida arabur - esp mai.	1	
6	140" cylinder ströke.		_	r 10 tor i Leannan ang	<u> </u>			
7	50 degree dump angle		•		Ì		1	f
8	High lift gate (6') opening discharge	17		3400 miles and according		i	 	<u> </u>
9	16 Cubic yard capacity		,				†	
10	Fender bottom rail 10 gauge, Wood Board gusset height 8', Bulkhead 74.			·	ļ .		 	
11	All Hydraulics, All safety features, flaps, lights,	1/	~ =	•••			1	
12	Alt shift PTO					- `	 	<u></u>
13	Asphalt apron, Deck 1/4" AR450, Sides 3/16" AR450, Rear post material 1/4" high tensile				i indiah massila	and a proper of the last of th	-	
14	Air operated tallgate. High lift, Height 56, Material, 3/16" hardox AR450, air operated contr	ols.			 	**************************************	 -	ļ
							ļ	
	Vehicle Configuration	w Kinne .				مهد ومد بعث معاشدتها.		
1	114SD CONVENTIONAL CHASSIS			·····				
2	SPECIFY MODEL YEAR	a019	7	· · · · · · · · · · · · · · · · · ·			د. است. « « منسان » ما ا	and the first of the second of
3	ŞET FORWARD AXLE-TRUCK	4011	·		<u> </u>		 	
4	TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK	1/						<u> </u>
5 6	FREIGHTLINER LEVEL II WARRANTY			·			1	
6	EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs.					والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة والمراجعة	-	
7	EXPECTED REAR DRIVE: AXLE(S) LOAD : 46000.0 lbs.	44 K					 	
8	EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs.	13,200				· · · · · · · · · · · · · · · · · · ·	 	
9	EXPECTED GROSS VEHICLE WEIGHT CAPACITY; 76350.0 lbs.	75,20	0	* 4				
10	EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs.	1,3790			alem surren, r. a. a saab 1 k.			
	DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM	HASHO	10	101	LIK	. 11 7		
	2010 EPA/CARB EMISSION CERTIFICATION	hasut	<u> (- </u>	6 0 [T 10.	11 1		
13	DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE	1/	-					
أحسين	BATTERY VOLT SENSE.			į				
14	(3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES	Mack			in degriner arganes, s,	Med - De ann adam I refige		
	POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX				-lery	Licen	anert	instalk
		עי שיו	• 1	-u,	1-17	CALLED	diam's	1/17/14/16

17	TORQUE LIMITING CLUTCH BRAKE	
18	ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING	
19	BW MODEL BA-921 19:0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY	
1	VALVE	
20	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM	
21	JACOBS COMPRESSION BRAKE	
22	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM	planet in the second of the se
ļ	ASSEMBLY WITH LIT BEPILLAR MOUNTED VERTICAL TAILPIPE	
23	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD	
	REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH	
24	BRIGHT UPPER STACK(S)	
25	13 GALLON DIESEL EXHAUST FLUID TANK	07
26	BORG WARNER (KYSOR) REAR AIR ON/OFF ENGINE FAN CLUTCH	8.7
27	DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH	
	WATER-IN-PUEL INDICATOR	
28	1500 SQUARE INCH ACUMINUM RADIATOR	
29	DELGO 12V-39MT+ HD/OCP STARTER WITH THERMAL PROTECTION AND	
7.50	INTEGRATED MAGNETIC SWITCH	
30	ALLISON AUTOMATIC 4500 RDS TRANSMISSION	
31	MFS-18-133A 18,000# FL1 SINGLE FRONT AXLE	M-drive
32	All markets of the Control of the Co	
, U.Z.	MERITOR 16.6X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	
33	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS	
34	TRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR	
35	ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE	
36	18,000# TAPERLEAF FRONT SUSPENSION	
37	FRONT SHOCK ABSORBERS	
38	RT-46-160P 46:000# R-SERIES TANDEM REAR AXLE	44 k 3.79
39	4.30 REAR AXLE RATIO	3.79
40	MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES	
والمتاسطة والمواقعة والمعاددة		
41	MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND	
	YOKES	
42	DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES	
43	(1) INTERAXLE LOCK VALVE (1) DRIVER CONTROLLED DIFFERENTIAL LOCK	
	FÖRWARD-REAR AND REAR-REAR AXLE VALVE	
44	MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR,	
	FABRICATED SHOES	
45	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)	
46	TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION	49k
47	JUFTRAC STANDARD RIDE HEIGHT	
48	56 INCH AXLE SPACING	
49	FORE/AFT AND TRANSVERSE CONTROL RODS.	
50	HENDRICKSON PARALIFT ULTRA HLUG2 COMPOSILITE 13,200# AIR LIFT	
	STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE	
51	HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2	
	SUSPENSIONS	
	(1) DASH VALVE AND (1) GAUGE FOR SINGLE LIFT AXLE	
<u> </u>	Bry 1996 Francis Ch. Rock Fr. 100 Alb Abb Brill 100 Fb	

Éà	DEVENOE VET AVI S UNDIVIDUATED FOR STATE SETEUTION WHEN TOWNED OF S		 			
53	REVERSELIFT AXLE WIRING WITH LAST STATE RETENTION WITH IGNITION OFF					
54	AIR PIPING FOR (1) LIFT/NON-LIFT AXLE WITH REGULATOR CHASSIS MOUNTED		Ĭ			
55	MERITOR 15X4 Q+ CAM PUSHER/TAG BRAKES, DOUBLE ANCHOR, FABRICATED				-	
	SHOES				ŀ	
56	MERITOR AUTOMATIC PUSHER/TAG SLACK ADJUSTERS			***		
57	HENDRICKSON HLUC2 13:200# AIR LIFT STEERABLE PUSHER AXLE SUSPENSION					-,-
112		1	ļ			J-44,000-100-1
58	WABCO 4S/4M ABS WITHOUT TRACTION CONTROL		-		-	
59	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED THROUGH IGNITION					
60	SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF				-	
المساورة المساورة	FRANE			A1-		
61	5650MM (222 INGH) WHEELBASE	1				
62	11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277;8MM/0,344X10,94 INCH) 120KSI					
63	1/4 INCH (6MM) C-CHANNEL INNER FRAME REINFORCEMENT			explained i	MIP	art
64	HEAVY DUTY SUSPENSION CROSSMEMBER			1.131.159	perpe	NUZ N
65	16,5 INCH CHROME STEEL STRAIGHT BUMPER					
66	100 GALLON/378 LITER ALUMINUM FUEL TANK - LH	//				
67	GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES	//			1	
68	GOODYEAR G288 11R22.5 16 PLY RADIAL REAR TIRES	(_		The state of the s	1	
69	GOODYEAR G338 1AD 295/75R223514 PLY RADIAL PUSHER/TAG TIRES	//				
70	CONMET PRE-SET BEARING ALUMINUM REAR HUBS	//				
71	AGGURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS		٠			
72	ACCURIDE 29644A 22:5X8:25 10:HUB PILOT ALUMINUM DISC REAR WHEELS				10-	
73	ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISG PUSHER/TAG WHEELS	/			\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	***************************************
74	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB				 	
75	AIR CAB MOUNTS	1/	}			···
76	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE		·		 	angus di sebuah di sebuah di sebuah di sebuah di sebuah di sebuah di sebuah di sebuah di sebuah di sebuah di s
77	CHROMED HOOD MOUNTED AIR INTAKE GRILLE				1	
78	DUAL 25 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS ROOF MOUNTED			Action and the second s		
		//				
79	DUAL HORN SHIELDS	//		<u> </u>	<u> </u>	
80	HALOGEN COMPOSITE HEADLAMPS WITH BRIGHT BEZELS	//			<u> </u>	2/07
81	DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE	Brish	t no	heat or m	otor	
82	DOOR MOUNTED MIRRORS.					
83	LH AND RH 8" BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS					
84	TINTED DOOR GLASS LH AND RH WITH TINTED OPERATING WING WINDOWS		-			
85	RH AND LH ELECTRIC POWERED WINDOWS	-	ļ			, ——,
86	INTERIOR CONVENIENCE PACKAGE WITH CB PROVISION	//		-	+	
87	2-1/2 LB. FIRE EXTINGUISHER	1/		1		
88	HEATER, DEFROSTER AND AIR CONDITIONER	1	iana+ hr	-i		
20 18 15 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		1	<u> </u>	<u> </u>		<u> </u>

89	GAB INSULATION	- /-	<u> </u>	
90	SOLID-STATE CIRCUIT PROTECTION AND FUSES:			
91	LHAND RHELECTRIC DOOR LOCKS	(/		
92	(1) 12 VOLT POWER SUPPLY IN DASH			
93	TRIANGULAR REFLECTORS WITHOUT FLARES	//		
94	BOSTROM TALLADEGA 910 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH AIR			
3.9	FRINBAS:			
95	HIGH BACK NON SUSPENSION PASSENGER SEAT			
96	LH AND RH INTEGRAL DOOR PANEL ARMRESTS	-//		
97	CLOTH DRIVER SEAT COVER	1/		
98	GLOTH PASSENGER SEAT GOVER			
99	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN	//		
100	97 DB BACKUP ALARM	(/		
101	CHARLEST TO BY MEDICAL PRODUCT OF COMPANY AND A CONTROL OF THE CON	/	Commission of the Commission o	
1.01	ELECTRONIC CRUISE CONTROL WITH SWITCHES ON AUXILIARY GAUGE PANEL (B. DASH PANEL)			
102	ODOMETER/TRIP/HOUR/DIAGNOSTIC/VOLTAGE DISPLAY: 1X7 CHARACTER, 26	1		
19E	WARNING LAMPS, DATA LINKED, IGU3			
103	DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1939, LOCATED BELOW DASH	1	manufic data and a same and a same and a	
900.	LOWOLD IN TELL WOR COMMED TO WAS BINE SAR THANK FOCK TED BETOM DVSH			
104	2 NOH ELECTRIC FUEL GAUGE			
105	A MON GEGORNO FUEL GADGE FUEL FILTER RESTRICTION INDICATOR	//		
106	DUAL REAR AXLE TEMPERATURE GAUGES FOR TANDEM AXLES			
107	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE	//		
108	ENGINE OIL TEMPERATURE GAUGE			
more assistant and	2 INCH TRANSMISSION OIL TEMPERATURE GAUGE	1/		
	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY	-	water the state of	
	ELECTRIC ENGINE OIL PRESSURE GAUGE			
	AMEMMB RADIO WITH FRONT AUXILIARY INPUT	1	Marie of 10st activity on comments and the company of the company	
	DASH MOUNTED RADIO	(/		
	ELECTRONIC 3000 RPM TACHOMETER	1/		
	TRAILER HAND CONTROL BRAKE VALVE	1/	 	
	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHERWIPER AND	!		
Dţ Q .	PECE ON DEFINATION OF STAND AND THE MILE DIMMER, WASHERWIPER AND			- [
117	PAINT ONE SOLID COLOR	-/-		
	Company of the Compan	(13000	
	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT	white	\$3500 option	for red
	Weight Front, 9324 lbs. Weight Rear, 9694 lbs. Total Weight, 19,018 lbs.	/_		
- Att A	Unit cost and buy back proposal		and the same of th	
7	Bidder shall list the purchase price per unit here and on top sheet.\$ [47,760]		and the same of th	
2	Bidder shall list the guaranteed three (3) year/150,000 mile dealer buy back price here per u		habaat 6 105 000	
	:	THE AUTO OU TO	hauser a 100 000	ف برود در و مرسید می وجد می وجد که
	50 A 100 A 1			
	A CONTROL OF THE CONT	<u> </u>	<u></u>	

MACK.

Vehicle Summary

cu	STOMER/	VEHICLE INFO	Description	Front Weight (LB)	Rear Weight (LB)
S	002EF2	CHASSIS (BASE MODEL)	GRANITE 64FR	5144	1903
S	99X93X	FINAL ASSEMBLY PLANT	Made in Macungle, PA USA	0	0
S	PB1091	PRICE BOOK LEVEL	2019B Pricebook	0	0
	A19049	VEHICLE MODEL YEAR	2019 MODEL YEAR	0	0
	MP2001	CUSTOMER FLEET SIZE	DEALER FLEET WITH LESS THAN 25 VEHICLES IN OWN FLEET OF ANY VEHICLE BRAND	0	0
S	013001	TYPE OF SERVICE	COMMERCIAL	0	0
S	505015	INITIAL REGISTRATION LOCATION	ALL 50 STATES, CARB ENGINE EMISSION (US17)	0	0
S	534014	LANGUAGE- PUBS/DECAL/SIGNS	ENGLISH	0	0
S	DHX10X	ROAD CONDITION	WELL MAINTAINED SURFACED ROADS >95% DRIVING DISTANCE	0	0
	0050L5	VEHICLE USE & BODY/TRAILER TYPE	DUMP TRUCK	, 0	0
	DKXG2X	GROSS COMBINATION WEIGHT	80,000 LB (36 TONNES) GROSS COMBINATION WEIGHT	0	0
S	7OBB1X	BRAKE REGULATION	BRAKE REGULATION, STOPPING DISTANCE 94M (310FT)	0	0
		TOPOGRAPHY	GRADES <3% GREATER THAN 98% OF DRIVING DISTANCE MAX GRADE 8%	0	0
S	E1BD1X	AMBIENT TEMP UPPER LIMIT (GTA)	AMBIENT TEMPERATURE HOT, WARMER THAN 104 F (40 C) ALLOWED UP TO 25 HOURS PER YEAR	0	0
S	032A89	TERRAIN GRADE	ON-OFF HIGHWAY, STARTING GRADES<18%	0	0
S	033A10	LOADING SURFACE	CONCRETE LOADING AND / OR UNLOADING SURFACE	0	0
S	0342A2	VEHICLE VOCATION	CONSTRUCTION SERVICE	0	0
APPL	-ICATION	PACKAGES	Description	Front Weight ((LB)	Rear Weight (LB)
	PK7107	GRANITE AF CONFIG. PKG.	PK7 179B; CTO; LH BB, 33L DEF, 93 GALLON SLEEVED, INBOARD AIR	0	0
S	023AB3	APPLICATION RECOMMENDATIONS	WITHOUT SPECIAL SALES PACKAGE	0	0

	026086	SALES PROMOTION	2017/18 RAPID QUOTE MANAGEMENT PROGRAM - US	0	0
S	022001	PILOT INSPECTION	NO PILOT REQUESTED	0	Ó

EN	ENGINE/TRANSMISSIONS				Front Weight (LB)	Rear Weight (LB)
	1000W0	ENGINE PACKAGE	MP7-425M MACK 425HP @ 1500-1800 RPM (PEAK) 2100 RPM (GOV) 1560 LB-FT, US'17	1855	463	
S	Q1CA1X	GEAR SELECTION TUNING	BASIC, GEAR-SELECTION TUNING	0	0	
	1360Z6	TRANSMISSION	MACK TMD12AFO-HD mDRIVE HD 12 SP- (OVERDRIVE)	503	168	
S	U6AA1X	ENGINE GOVERNOR TYPE	ENGINE GOVERNOR TYPE MIN-MAX	0	0	

EXI	HAUST/EM	IISSIONS	Description	Front Weight (LB)	Rear Weight (LB)
S	CIRAA4	CARB 2008 IDLE REGULATION	IDLE EMISSION CERTIFICATION, CARB (WITH DECAL LOCATED ON LOWER LH CORNER / DRIVER DOOR	0	. 0
S	DPF04F	DPF DIESEL PARTICULATE FILTER	CLEARTECH ONE BOX E.A.T.S. RH SIDE UNDER CAB US17	0	0
	8NAB1X	DPF COVER	DPF COVER STAINLESS STEEL, POLISHED	0	0
	DF10P1	DEF TANK	8.7 GALLON (33 L) 26" INTEGRAL TO LH FUEL TANK	0	0
	U6BZ1X	DEF TANK COVER	WITHOUT DEF TANK COVER	0	0
	130AD7	EXHAUST	SINGLE VERTICAL RIGHT SIDE CAB MOUNTED, LOWER VENTURI DIFFUSER, TURNED END	-4 6	-2
S	5BAAAX	EXHAUST HEAT SHIELD TYPE	EXHAUST HEAT SHIELD TYPE, BASIC	0	0
	KRXAPX	EXHAUST STACK HEIGHT	9' 6" FROM GROUND	0	0
	Q0AC1X	EXHAUST SYSTEM MATERIAL FINISH	SINGLE, BRIGHT FINISH HEAT SHIELD, STACK AND SCR COVER (IF EQUIPPED)	0	0
S	78AC7X	EMISSION ON BOARD DIAG CONTROL	EMISSION OBD, DISPLAY ONLY, USA2018	0	0

ENGINE EQUIPMENT				Front Weight (LB)	Rear Weight (LB)
S	125AA4	AIR CLEANER	11" x 30" (279 mm x 762 mm) UNDER HOOD SINGLE ELEMENT DRY TYPE W/AIR INTAKE FROM BOTH SIDES OF HOOD	0	0
S	1VAAAX	AIR INTAKE SOURCE	W/O INSIDE/OUTSIDE AIR INTAKE	0	0
S	121AA5	BUG SCREEN	BLACK ALUMINUM MOUNTED BEHIND GRILLE, WITHOUT WINTER FRONT COVER	0	0
S	113AA6	AIR COMPRESSOR	MERITORWABCO 318 (18.7 CFM)	0	0
	132AB2	ALTERNATOR	DELCO 12V 135A (35SI) BRUSHLESS	27	0

Price Level:12/08/2017

S	316AA	6 BATTERIES	(3) MACK 12V 650/1950 CCA THREADED STUD TYPE	0	0
	393AC	4 BATTERY BOX - MOUNTING	BATTERY BOX LEFT HAND RAIL BACK OF FUEL TANK	0	0
	L5XF1>	BATTERY BOX COVER	POLISHED ALUMINUM	5	0
S	MOXZ1	X BATTERY SHOCK PAD	S W/O BATTERY SHOCK PADS	0	0
S	LLXZ1X	EMERGENCY START CONNECTIONS	W/O EMERGENCY STARTING RECEPT.	0	0
	318AA3	BATTERY DISCONNEC SWITCH	T FLAMING RIVER BIG SWITCH WIRED TO POSITIVE SIDE	3	0
S	NCXA5	K STARTER	12 VOLT DELCO 39MT-MXT	0	0
S	110 A A5	ENGINE BRAKE	MACK MP7 POWERLEASH	0	0
S	JMXB1X	ENGINE BRAKE LIGHTING (CA)	VEHICLE AND TRAILER (IF APPLICABLE) STOP LAMPS ACTIVATE UPON SERVICE BRAKE APPLICATION ONLY (3899000)	0	0
	118AB8	FAN DRIVE	BEHR FAN AND ELECTRONIC MODULATING VISCOUS FAN DRIVE	. 0	0
	119AB9	•	N CHEVRON EXTENDED LIFE COOLANT W/O NITRITES(50/50 MIX DYED RED) TO -34DEG	0	0
		COOLANT FILTER / CONDITIONER	SPIN ON CANISTER W/O CHEMICAL FOR USE W/TEXACO EXTENDED LIFE COOLANT ONLY	0	0
S	508AA3	COOLING PERFORMANCE	STANDARD COOLING PERFORMANCE	12	-2
S	124AA3	HOSES - RADIATOR/HEATER	MACK BRAND EPDM RADIATOR & HEATER HOSES	0	0
S		FUEL-WATER SEPARATOR	MACK W/MANUAL DRAIN VALVE (INTEGRAL W/PRIMARY FUEL FILTER)	0	0
S	MBXA1X	PRIMARY FUEL FILTER POSITION (CA)	STANDARD FUEL FILTER POSITION	0	0
S		AUX. FUEL SYSTEM EQUIPMENT	WITHOUT AUXILLIARY FUEL HEATING	0	0
S	E8XZ1X	FUEL EQUIPMENT WATER HEATER (CA)	W/O FUEL HEATER	0	0
S	QHXC1X	OIL PAN	OIL PAN	0	0
	5NXA1X	ENGINE BLOCK HEATER	120V 1500 WATT ENGINE BLOCK HEATER	5	0
S	EFXZ1X	ENGINE OIL PAN HEATER	W/O OIL PAN HEATER OPTIONW/O OIL PAN HEATER	0	0
S	HZXZ1X	ENGINE OIL DRAIN KIT	W/O OIL CHANGE SYSTEM	0	0
	36AD1X	CAPS & COVERS	FURNISH CAP RETAINER FOR OIL FILL & RADIATOR OVERFLOW TANK, BATTERY BOX, AND TOOL BOX (IF FURNISHED)	0	0
S	NDXZ1X	ENGINE STARTING AID	W/O ENGINE COLD START AID	0	0
S		ALCOHOL EVAPORATOR (CA)	W/O ALCOHOL EVAPORATOR	. 0	0

CLU	JTCH/TRA	NS EQUIPMENT	Description	Front Weight (LB)	Rear Weight (LB)
S	49200B	GEAR SHIFTER	MACK mDRIVE-PREMIUM SHIFTER	0	
S	133AC7	CLUTCH	ZF/SACHS SINGLE PLATE 17" (430MM) ORGANIC MATERIAL	, 0	0

	0VA74V	CONTOURDED AT DAD	10115		
	2XAZ1X	CLUTCH PEDAL PAD	W/O CLUTCH PEDAL	0	0
S	IUXZ1X	CLUTCH ACTUATION SYSTEM	W/O AIR ASSIST	0	0
	RBXZ1X	CLUTCH LUBE LINE	W/O LUBRICATION FITTING OPTION	0	0
S	RGXZ1)	CLUTCH BRAKE	W/O CLUTCH BRAKE	0	0
S	6VAZ1X	ENGINE START CONDITION	W/O CLUTCH STARTING SWITCH OPTION	0	0
	195025	DRIVELINE - MAIN	SPICER SPL350XL "EXTENDED LUBE SERIES"	16	40
	204AB0	DRIVELINE - INTERAXLE	SPICER SPL250HDXL EXTENDED LUBE SERIES	0	31
S	83AZ1X	PROP SHAFT BEARING GUARD	WITHOUT DRIVESHAFT GUARD FOR CENTER BEARING	0	0
S	76AA1X	PROPELLR SHAFT MAIN, UNVSL JNT	PROPELLER SHAFT MAIN, UNIVERSAL JOINT HALF- ROUND TYPE	0	0
S	4LDA1X	TRANSMISSION OUTPUT TORQUE	TRANSMISSION OUTPUT TORQUE BASIC	0	0
S	8WAAAX	PROP SHAFT INTERAXL UNIV JOINT	. HALF-ROUND UNIVERSAL JOINT	0	0
S	RCXB1X	BELL HOUSING	ALUMINUM	0	0
S	D38Z1X	TRANSMISSION ADAPTATION RING	WITHOUT TRANSMISSION ADAPTATION RING	0	0
s	5DAZ1X	TRANSMISSION DUST PROOFING	W/O TRANSMISSION DUSTPROOFING	0	0
S	7RXD1X	LUBRICANTS, TRANSMISSION	75W - 90 (SYNTHETIC LUBRICANT)	0	0
S	139049	TRANSMISSION OIL COOLER	MACK mDRIVE TRANSMISSION OIL COOLER MTD LH SIDE OIL TO WATER COOLER	0	0
S	M6CA3X	TRANSMISSION OIL MONITORING	WITHOUT TRANSMISSION OIL MONITORING, REMOTE FITTING	0	0
	442012	TRANSMISSION TORQUE CONVERTER	W/O TRANS TORQUE CONVERTER	0	0
S	3JAA1X	HILL START ASSIST	GRADE GRIPPER	О	0

FRO	NT AXLE	EQUIPMENT	Description	Front Weight (LB)	Rear Weight (LB)
S	240AA2	FRONT AXLE	18000# (8200 KG) MACK FXL18 (WIDE PIVOT CENTER) STRAIGHT SPINDLE/UNITIZED BEARINGS	325	0
S	RHXZ1X	FRONT AXLE SPREAD	WITHOUT FRONT AXLE SPREAD	0	0
	7QBZ1X	VEHICLE PREP, ADDITIONAL AXLES	WITHOUT VEHICLE PREPARATION, ADDITIONAL FRONT AXLES	0	0
S	244AB1	SPRINGS - FRONT	MACK TAPERLEAF 18000# (8200 KG) GROUND LOAD RATING	27	0
	241021	FRONT AXLE BRAKES	BENDIX NEXT GENERATION DRUM BRAKE, HEAVY DUTY 16.5 X 6 (9.65mm thick)	34	0
	LQXF1X	BRAKE LINING MATERIAL FRONT	BENDIX EES-600	0	0
S	U3XA1X	BRAKE, FRONT	CAST IRON	0	0
	UDXA1X	FRONT AXLE BRAKE DUST SHIELD	FURNISH	5	0

S	U0AA1X	FRONT BRAKE ADJ. MANUFACTURE	HALDEX - AUTOMATIC	0	0
S	V7AD1X	FRONT BRAKE CHAMBER MFG.	FRONT BRAKE CHAMBER MANUFACTURER, MGM	0	0
S	O5BD1X	FRONT BRAKE CHAMBER SIZE	FRONT BRAKE CHAMBER 24SQ INCHES (SERVICE)	0	0
S	YHXZ1X	FRONT SPRING BIAS	WITHOUT FRONT SPRING BIAS (EQUAL STIFFNESS L/R)	0	0
s	0KXA1X	HUB MATERIAL, FRONT	FERROUS	157	0
s	1BXBDX	HUB OIL SEAL, FRONT	FAG SCHAEFFLER	0	0
S	K4AAAX	SPINDLE NUTS, FRONT	STANDARD	0	0
S	1KAA1X	SHOCK ABSORBER, FRONT	DOUBLE ACTING TYPE	0	0
S	245AA9	STEERING	SHEPPARD SD110	111	0
S	7VXC1X	LUBRICANTS, FRONT AXLE	PETROLEUM/SYNTHETIC (50/50) OIL FRONT AXLE	0	0

DE 4	D 4VI 5 5				Rear Weight
REA		QUIPMENT	Description	(LB)	(LB)
	268AA3	REAR AXLES - TANDEM	44000# (20000kg) MACK S440 FABRICATED STEEL HOUSING	0	1445
S	6MAA1X	REAR AXLE CASING WIDTH	W/O WIDE TRACK AXLE OPTION	0	0
S	R4XZ1X	LUBE PUMP, REAR AXLE	W/O LUBE PUMP AND FILTER	0	0
S	018AA6	CARRIER - REAR AXLE	CRDP150/151	. 0	0
	TAXAVX	REAR AXLE RATIO	3.79 RATIO	0	0
	1860[6	REAR SUSPENSION - TANDEM	SS440 MACK MULTILEAF (CAMELBACK) 44000# - EXTRA THICK SPRING THICKNESS	0	1921
	402AA3	SPRINGS - ANTI-SWAY	SPRINGS, ANTI-SWAY	0	104
	XZXA1X	REAR SUSP. BEAM BUSHINGS	BRONZE	0	36
S	5MAZ1X	BREATHER FILTER (rear axle)	WITHOUT BREATHER FILTER RELOCATION	0	. 0
S	GWXABX	BOGIE SPREAD, REAR	50" AXLE SPACING (BOGIE WHEELBASE)	0	16
S	ZAX99X	SUSPENSION LEVELLING DEVICE	W/O AIR SUSP HEIGHT CONTROL	0	0
	J6DZ1X	AIR SUSPENSION DUMP WARNING	WITHOUT AIR SUSPENSION DUMP WARNING	0	0
	2AAAAX	REAR SPRING INSULATOR MAT'L	RUBBER SHOCK INSULATORS	0	0
S	YVXZ1X	REAR SHOCK ABSORBER	W/O REAR SHOCK ABSORBERS	0	0
	XYXB1X	TRANSVERSE TORQUE RODS, R SUSP	TRANSVERSE TORQUE ROD (REAR AXLE ONLY)	0	0
S	253053	BRAKES - REAR	BENDIX NEXT GENERATION DRUM BRAKE, HEAVY DUTY 16.5 X 7 (9.65mm thick) (Total for QTY = 2)	0	27
		BRAKE LINING MATERIAL DRIVE	BENDIX EES-600	0	. 0

S	U4XA1X	(BRAKE DRUMS/ROTORS - REAR	CASTIRON	c	0
S	U1AA1X	REAR BRAKE ADJ MANUFACTURE	HALDEX - AUTOMATIC	C	0
	UEXA1X	DRIVE AXLE BRAKE DUST SHIELD	FURNISH	12	0
S	V1AB1X	REAR BRAKE CHAMBER SIZE	REAR SPRING BRAKE CHAMBERS 30/30 TYPE	0	0
S	300AD0	REAR BRAKE CHAMBER MFG.	MGM MODEL TR-T; TAMPER-RESISTANT BRAKE CHAMBERS (Total for QTY = 2)	0	0
S	0LXI5X	HUB MATERIAL, DRIVE	IRON PRESET REAR HUB W/INTEGRATED SPINDLE NUT	0	318
S	1CXI2X	HUB OIL SEAL, DRIVE	PREMIUM	0	0
s	N2AE1X	SPINDLE NUTS, MAIN AXLE	SPINDLE NUTS, MAIN AXLE, INTEGRATED	0	0
S	3LAC1X	POWER DIVIDER LOCKOUT	POWER DIVIDER LOCKOUT, W/BUZZER & LIGHT	0	40
	7WXB1X	LUBRICANTS, REAR AXLE(s)	75W - 90 (SYNTHETIC LUBRICANT)	0	0
S	254 AA 1	TRACTION DIFFERENTIAL	OMIT DIFFERENTIAL LOCKS	0	0
S	9GAAAX	ABS SENSOR & MODULATOR	4S/4M SYSTEM REAR WHEEL END SENSORS	0	0
S	698AA5	ANTILOCK BRAKE System	BENDIX WITH TRACTION CONTROL	0	0
S	URXD1X	BRAKE VALVE VERSION	BENDIX SWITCHES AND VALVES WHERE POSSIBLE	0	0
s	H9CZ1X	TRACTION CONTROL DISABLE	W/O AUTOMATIC TRACTION CONTROL (ATC) DISABLE SWITCH	0	0
S	3ZAA1X	SPRING BRAKE INVERSION VALVE	TRACTOR SPRING BRAKE INVERSION VALVE	5	0
PUSH	HER/TAG A	AXLE EQUIPMENT	Description	Front Weight (LB)	Rear Weight (LB)
		AUXILIARY AXLE CONTROLS	WITHOUT AUXILIARY AXLE CONTROLS	0	0

PUSHER/TAG AXLE EQUIPMENT	Description	Weight Weight (LB) (LB)
MAC01C AUXILIARY AXLE CONTROLS	WITHOUT AUXILIARY AXLE CONTROLS	0 0

FRA	ME EQUI	PMENT/FUEL TANKS	Description	Front Weight (LB)	Rear Weight (LB)
	2712 2 6	WHEELBASE	226"	183	183
	374057	AF (OVERHANG)	57"	-13	223
	27 4AA 9	FRAME RAILS	STEEL - 300MM X 105MM X 11.1MM - (11.81" X 4.13" X 0.437")	0	0
S	7TXZ1X	RUST PROTECTION (for frame), ADDITIONAL (CA)	W/O RUST PREVENTATIVE OPTION	0	0
S	Z9XZ1X	FRAME INNER LINER	WITHOUT FRAME REINFORCEMENT - INSIDE	0	0
S	6CBZ1X	FRAME OUTER LINER (CA)	WITHOUT FRAME REINFORCEMENT - OUTSIDE	0	0

2							A B	11
e L		CRAIGHEAD COUNTY			T	1	1	
		INVITATION TO BID-Not an Order					 	
		Craighead County Judge's Office	`\	***************************************				
		511 Union St.; Suite 119		**	7			
		Jonesboro, Arkansas 72401					 	
		ASING OFFICE			1 3 3 1 3 2 1 3			ا الرج: إن المرا
	BID NO	2018-7.	DATE A	April 17, 20	118	<u>_</u>	un un juligan	W. W.
	Sealed	bids, subject to the conditions on the reverse hereof, and as may be attached hereto, on the Nav 2, 2018 and then exhibits a second for the property of the pr	will be rece	di le kovik	is office		1	S /
j	C. 111	out to may 2, 20 to and then publicly opened, for turnishing the sunnies materials	THE OC. LOSE	avou at til	is office		33 13 	inementalis
	and/or s	services as described below.	******		ļ		-	
		The state of the s	Bide will	he anana	May 2, 2018.			
	4-1		Olda Mill	2:00 P.M				لمدبق
	F.O.B	Jonesboro, Arkansas	BÝ: AI Ha		4	_		٠ - ا
	Maximu	m Delivery or completion time after issuance of Purchase			COTOS			1
	Order o	work ordered by County 120 days.	LOKOUN	SING DIR	EULOR			à
ľ	Item#		OUNT	LATIN	1 11 11 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	_		
	1	Furnish two (2) each Dump Trucks with Automatic transmissions and with	QUANT		HINIT PRICE	AMO	JNT	
- [2.00	installed dump beds to Craighead County Road Department, 2800 Moore	1	45,623		291	246.	
		Road, Jonesboro, AR. 72401 according to attached specifications. Trucks are						3
	Transmik 19. taka	to have dump beds and hydraulics installed and fully operational when delivered.		-				
	2	This bid package contains 6 pages. All 6 pages must be returned		<u> </u>				
		to complete bid.		ļ		18": 1		
	3	Bid must be signed by authorized company representative.		-		-		ì
	# 4	Bidder should:	 	<u> </u>			14 On their specification	
1	from Heren V Lags	A. Clearly define and list warranty information on each item in years.			***************************************			
	*π	B. Include all labor, delivery charges, training, programming,	***************************************					
"		and any other charges FOB Jonesboro, Arkansas 72401, in bid price.			*****			
		C. Include product literature and specifications with bid.				1		
		D. All refevant information will be considered when determining best bid for Craighead	d CAORE.		water sectories and many descriptions	- (, , , , , , , , , , , , , , , , , , , 		
		E. Specify cash discounts, if available.	1 County.					
	49	F. Note bid humber on outside of bid envelope.						
			-1/1		318		ۇ. ئىينىچىنىتىدىدى	
		F. List make, model, and manufacturer of equipment being offered.	D) OP (B	MICL	1210 C WSTAL	<u>ተለሳ ኔ</u>)	
		G. Quote same or equal equipment in all aspects.	17 00	31 E1	シー・テ	47	00	
		H. Specify nearest service and parts supply location to Jonesboro, AR. 5215	711.00	1.300	78 MEMI		- X.A.	
, ,	5	Does bidder meet all dump truck specifications? Yes No.	2.11(9)	mity !	10 Michigan	1113,12	2 3 8 1	12
		If no, clearly list and define differences on a separate sheet	<u> </u>					-4
· · · ·	6	Attached equipment list with names and part numbers is for reference	œ					
	7	Bidder should put total bid price on this sheet. Total bid price is \$ 291.246	20			1-4-21-4	31.	
خوافت	8	Bidder shall list purchase price per unit here. \$1 15 Buyback price per unit here	5 91	500 (4	A)	-	44-4-44	1
		The state of the s	Ţ			1		
	أشديم	EXECUTION OF BID	Dale An	74 21	3 2018	-		
W	e, the ur	iversigney, have read all the requirements set forth in this bid proposal including energi	fications					2.
ınş	uction	s, conditions, and pertinent information regarding the articles being bid on, and we ago	ee lo lumi	sh			d In	
ĮΠ	icies at i	ne prices stated.		-		 -	<u></u>	
٩H	kansas l	Jse Tax Register No. 127448 - 18 - 001					والمراسية	: 2
310		BUS IRUCKS BRUKE Addres 5228 (4) HUMY 78 1	NEMP	H12 1	5 <i>38118</i>	∤ \$ -	نسير فيهوند سعجه	¥
		Person Authorized to Sign Bids) Title		to the second second second second	ATIVE		<u>ئىرى چەسىد</u>	\$ A
		THE REPORT OF THE PROPERTY OF	- 3	(4) (4) (4)	ITI IVE		\$15 (FA)	
:	و المحاول المحاود المحاود المحاود	BIDS ARE SUBJECT TO REJECTION UNLESS SUBMITTED O	N THIS FO)ŔМ			- 44	.1
-	NOTIC	ETO BIDDERS, SEE REVERSE SIDE OR ATTACHMENTS FOR INSTRUCTIONS A	AND CON	DITIONS				7 -
					<u></u>	<u> </u>	and the second	<u>1</u> .

LARGE

	CRAIGHEAD COUNTY		
1	JONESBORO, ARKANSAS		
سند المجالة	CONDITIONS OF BIDDING	1	,
	Compliance with the following conditions is necessary for consideration of this bid.	********	
1	Signature-This bid must be signed with the firm name and by an authorized officer, employee or agent.		
2	Sales Tax-is not to be shown in the bid price, but is to be added by the vendor to the invoice billing to the County.		
	The County is exempt from Arkansas State Sales Tax on road equipment and vehicles. Contractors are to include all cost	\$ S	
	I into the did price, including applicable taxes.		
3	Freight and other delivery charges to destination at designated County facility in the County must be included in bid.		н .
	Charges may not be added after the bid is opened.	<u> </u>	7
4	Discounts-Show rate, total amount, and latest day any discounts will be allowed after receipt of article and invoice,		H.
برويشي	otherwise County will deduct allowed discount when payment is made.		حميسوس بأمسمي سيسم
5	Firm Price-All prices quoted will remain firm for at least 30 days from date of bid, unless otherwise specified		·
	by the County or bidder		-
6	Tax Exempt-Craighead County is exempt from State sales tax on self propelled equipment and motor vehicles.		
2012	Example: Motor graders, excavators, dozers, dump trucks, pickup trucks, etc.		
7	Identical Bids-In the event of two or more identical low bids, the contract may be awarded arbitrarily or for		
	any reason to any of such bidders, or split in any proportion between the said two or more bidders at discretion of the Court	ntv	1 10
. 8	Clean up-Complete cleanup and proper disposal of any and all job related items is considered to be a part of any		
	contract let by Craighead County.		
9	Ambiguity in bid-Any ambiguity in any bid as the result of omission, error, lack of clarity or non-compliance		<u> </u>
	specifications, Instructions, and all conditions of bidding shall be construed in the light most favorable to the County		
10	Construction		
	A. When requested, the Contractor is to supply the County with evidence of having and maintaining proper and		
	specifically Workman's Compensation Insurance in accordance with the laws of the State of Arkansas.		
	Public Liability, and Property Damage. All premiums and cost shall be paid by Contractor. In no way will the		
4 (1)	County be responsible in case of accident.		man water and the same of the same
	B. A Performance Bond equaling the total amount of any bid exceeding \$20,000 must be provided for		منت سندان المدوسيت
	erection of any public building, public structure, or public improvement (Pursuant to Arkansas Code 18.44-503)		
<u> 11 =</u>	The County reserves the right to reject any and all bids, accept in whole or in part, to waive informalities in bids		3
	received, to accept bids on materials or equipment with variations from specifications in those cases where efficiency		
	of operation will not be impaired, and unless otherwise specified by bidder, to accept any item in the bid. If unit prices		
9	and extensions thereof do not coincide, the County may accept the bid for the lesser amount whether reflected		
	by extension or by the correct multiple of the unit price.		
	INSTRUCTIONS TO BIDDERS (Please read carefully)		-
1	Submit bid on bid form attached or reverse side of this sheet.		
2	Address all bids to: Purchasing Director, Craighead County Judge's Office, 511 Union St.; Suite 119		
148	Jonesboro, Arkansas 72401and make certain to indicate identifying bid number on the outside of bid envelope.		
3	DO NOT include Federal Excise Tax In bid. County will furnish exemption certificate.	-	
4	Sate Manufacturer, Brand Name, Model, etc. for each item bid on.		
5	Samples of Ilems, when required must be furnished free, and, if not called for within 30 days from date of		
	bid opening, will be disposed of by the County		
	Bids received after stated time will not be considered.	-	
7 🔭	Be sure and read all conditions and verify amounts before submitting bids. No changes or additions will be		
	allowed after submission		
8	Guarantees and warranties should be attached as a part of the bid, as they may be a consideration. In awarding contract.		
<u>. y </u>	Delivery or contract completion time is to be shown, as this date may, where time is of the		
	essence, determine the contract award.		
10	Additional information may be obtained from the Purchasing Department.		
	THE COUNTY RESERVES THE RIGHT TO ACCEPT PART OR ALL OF ANY SPECIFIC BID OR BIDS		
	AND TO ACCEPT BID WITH OR WITHOUT TRADE-IN, AND REJECT ANY AND ALL BIDS.		
2017年			

1 1.4 1.6

		General				
	Α				1	
1		Trucks (automatic transmissions) and dump beds shall be the latest year model in current by manufacturer and shall meet all federal emissions and all other EPA regulations (Spec	t production with pro	ven performance		
^	В	All hidders shall offer a migrant and the state of the st	city year model)			
		All bidders shall offer a guaranteed three (3) year dealer buy back program and clearly de	fining			
	C	buy back dollar amount, time frame and mileage and other criteria for the buy back progra)M.			E-
		Bidder shall bid truck and bed with a three (3) year/150,000 mile dealer buyback program	CH.			1
ŀ		Dealer should guarantee any outside vendors and for companies that supply buy back pri	cing.	- A-		
-	D ,	Note: Part of specifications may be Freightliner specific. Please bid equal equipment.				
1	Ē	Note: Part of specifications may be Godwin EL series specific. Please bid equal equipmen	it.			
	É	VEHICLE AND DUMP BED SPECIFICATIONS		t-s L	2 1 3 .	***************************************
	F.	Dump Bed Specifications (Beds being offered shall be equal to the following	Meet Specification	18		
- 1		specifications)	Yes No			
,	<u>्</u> री	R/S Godwin Truck Body Company Model EL 16052311				
	2	Elliptical floor, length 192, Pivot 180 degrees, Inside width 86, Side height 52.			-	
	3	Custom single acting hoist, Electric Tarp system-6200.			-	
1	4	6" diameter cylinder rod(3) stage cylinder with 2000 PSI			-	
_	5	Holst lifting capacity 56,540 lbs. (28 ton)		***************************************	·	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	. 6	140" cylinder stroke				
		50 degree dump angle	V	-		
27.7	√8	High lift gate (6) opening discharge	/			
	9	16 Cubic yard capacity			,	
1	10	Fender bottom rail 10 gauge, Wood Board gussel height 8", Bulkhead 74.		7	\$ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
4	11.	All Hydraulics, All safety features, flaps, lights,				
, d , i , i	12	Air shift PTO				
	13	Asphalt apron, Deck 1/4" AR450, Sides 3/16" AR450, Rear post material 1/4" high tensile		***************************************		
	147	Air operated tailgate, High lift, Height 56, Material, 3/16" hardox AR450, air operated control	ols.			
	4.7	The state of the s				
		Vehicle Configuration				
	1	114SD CONVENTIONAL CHASSIS 4700 W. STAR	1			
	2	OPECIFT MODEL TEAR	2019	And the Control of th	6.	
		SET FORWARD AXLE - TRUCK				
	4 ,	TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK	V.			. 41
- -		FREIGHTLINER LEVEL II WARRANTY	V	- <u> </u>		
ة. مياسة		EXPECTED FRONT AXLE(S) LOAD : 18000.0 lbs.				***************************************
		EXPECTED REAR DRIVE AXLE(S) LOAD: 46000,0 lbs.	V			
		EXPECTED PUSHER AXLE(S) LOAD: 12350.0 lbs. 13, 200				-
	*******	EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 76350.0 lbs. 77, 207				market the state of the second or the second of
		EXPECTED GROSS COMBINATION WEIGHT: 80000,0 lbs.			1	
: لايد.		DD13 12.8L 450 HP @ 1800 RPM, 2080 GQV RPM, 1650 LB/FT @ 1100 RPM			1	-
بذب		2010 EPA/CARB EMISSION CERTIFICATION	V			
: /		DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE				***************************************
خيت		BATTERY VOLT SENSE	V		* .	T. # 1981
ï		3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA		-		
	Alaki	[HREADED STUD BATTERIES				
	15	POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY				
À	1 K	'RAY/BOX				
	16	F-SACHS 15-1/2 INCH TWIN XTEND ULTRA SOFT DAMPER CERAMIC CLUTCH				ar annes ann gairtí, a-mailte agus air
		NO CLUTCH ON AUTOR ATIC TRANSMI	CCM			100
			2 10 <u>2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2</u>		<u></u>	

18 JERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING 19 BW MODEL BA 291 190 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY 20 ELECTRONIC ENGINE INTEGRAL SHUTBOWN PROTECTION SYSTEM 21 JACOSS COMPRESSION BRAKE 22 IFRI QUITBOARD INDERS STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM 23 SHABINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD 24 SROWN AND ASH MOUNTED REGENERATION REQUEST SWITCH 25 SHABINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD 26 SHABINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD 27 SHABINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD 28 SHABINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD 29 SHABINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD 30 SHAPINE DENDINE MOUNTED PUEL PILTERFELE WATER SEPARATOR WITH 31 SALLON DISSEL EXPAUST FLUID TANK 32 SHOWN ARRANER (KYSSOR) BRAK AIR KONGT FEARING FAN DILUTCH 33 SHAPINE AND READ SHAPINE WITH THERMAL PROTECTION AND 34 INFORMATION HOROCATOR 35 SHAPINE DENDINE MOUNTED PUEL PILTERFELE WATER SEPARATOR WITH 36 SOLARE INCH ALUMRIUM RADIATOR 37 MENTER JESS AGE CAST SPEDER CAM FRONT BRAKES, COUBLE ANCHOR, 38 PART AND THE STAR OF A CORE AS STAR SHAPING AND AIR	17			-	1	-	
BW MODEL BAY21 19 O CHM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE 20 ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM 21 JASOBS COMPRESSION BRANC 22 TRA OUTBOARD LADDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH HE PHILLAR MOUNTED VERTICAL TALPIPE 32 RISINGER AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGISHERATION AND DASH MOUNTED PEGENERATION REQUEST SWITCH 38 RISINGER AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGISHERATION AND DASH MOUNTED PEGENERATION REQUEST SWITCH 39 SORG WARNER (KYSOR) REAR AIR ONDOFF ENSINE FAN ELUTCH 20 BOS QUARE INCH ALUMINUM RADATOR 21 BISSO SOLARE INCH ALUMINUM RADATOR 22 DELOG 12V 39MT+ PHOOCP STATTER WITH THERMAL PROTECTION AND ATTESPRATED MAGNETIC SWITCH 30 ALUSON AUTOMATIC SKORT SHARK KADJUSTERS 31 MERTICA 18,800 CP CAST SPIDER CAM PRONT BRAKES, DOUBLE ANCHOR, VARROLATED SHOES 32 MERTICA REVIDENTED FE 75W-30 FRONT AXLE LUBE 33 TRANSPER DEVINE STEERING WITH ROHS AUXILIARY GEAR 34 TRY THE 30 POWER STEERING WITH ROHS AUXILIARY GEAR 35 ROADRAAGER SYNTHETIO FE 75W-30 FRONT AXLE LUBE 36 TE 300H TAPER EAR FRONT SUSPENSION 37 FRONT SHOCK ABSORBERS 38 THA-E-100P 45.000H R-SERRIES TANDEM REAR AXLE 39 TRANSPER EAR FRONT SUSPENSION 40 ALUSON STEERING WITH ROHS AUXILIARY GEAR 41 MAL 17N MERTICA EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 42 DRIVER CONTROLLED TRACTION DIFFERENTIAL BOTH TANDEM REAR AXLE 43 (I) INTERAXLE LOCK VALVE (1)) DRIVER CONTROLLED TREFERENTIAL LOCK 44 OKAN AND CHARBERS ON FORWARD SIDE OF DRIVE AXLESS 45 BRAKE CAMS AND CHARBERS ON FORWARD SIDE OF DRIVE AXLESS 46 SPAKE CAMS AND CHARBERS ON FORWARD SIDE OF DRIVE AXLESS 47 UNITERAL ELOCK VALVE (1)) DRIVER CONTROLLED DIFFERENTIAL LOCK 48 FRONT STOOCK ABSORBERS 48 SPAKE CAMS AND CHARBERS ON FORWARD SIDE OF DRIVE AXLESS 49 SPAKE CAMS AND CHARBERS ON FORWARD SIDE OF DRIVE AXLESS 40 SPAKE CAMS AND CHARBERS ON FORWARD SIDE OF DRIVE AXLESS 40 SPAKE CAMS AND CHARBERS ON FORWARD SIDE OF DRIVE AXLESS 40 SPAKE CAMS AND CHARBERS ON FORWARD SIDE OF DRIVE AXLESS 50 FRANCOKSON FRANCE FURSTAN WIT	18	WEEN FUTURE WITH EXCENSION HUSE AT CLUTCH RELEASE BEARING	. 1	حر رز د	312401		- 1
20 ELECTRONIC CHOIRE INTEGRAL SHUTDOWN PROTECTION SYSTEM 21 DACOBS COMPRESSON BRAYS 22 TRE QUITBOARD LINDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM 4 SSERIELY WITH LH SHULLAR MOUNTED VERTICAL TALLPIRE 28 BIGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGISHERATION AND DASH MOUNTED PEGENERATION REQUEST SWITCH 29 GROUND WARREN (KYSOR) REAR AIR ONDOF ENDINE FAN DLUTCH 20 IS SALLON DESSELEXHAUST FLUID TANK 20 BORG WARRER (KYSOR) REAR AIR ONDOF ENDINE FAN DLUTCH 21 DOS DUPFLED ENGINE MOUNTED PLELF IT TERFUEL WATER SEPARATOR WITH WATERINFUEL INDICATOR. 28 1500 SQUARE INCH ALUMINUM RADIATOR 29 DELCO 17V 39R/TH HOO'OP STATTER WITH THERMAL PROTECTION AND WITEGRATED MAGNETIC SWITCH WATERINFUEL INDICATOR. 30 FALLON AUTOMATIC ARON TO STATEM WITH THERMAL PROTECTION AND WITEGRATED MAGNETIC SWITCH WHATER 1850 OF CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, WARRANT 1850 OF CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, WARRANT 1850 OF CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, WARRANT 1850 OF CAST SPIDER CAM FRONT SALE LUBSE 31 INFO-16-130A 18,000F FL I SINGLE FRONT AXILE LUBSE 32 MEANTOR AUTOMATIC FRONT SLACK ADJUSTERS 33 MEANTOR AUTOMATIC FRONT SLACK ADJUSTERS 34 ROADPANGER SYNTHETIC PE 75W-90 FRONT AXILE LUBSE 35 ROADPANGER SYNTHETIC PE 75W-90 FRONT AXILE LUBSE 36 ROADPANGER SYNTHETIC PE 75W-90 FRONT AXILE LUBSE 37 FRONT SPIOCK ABSONDERS 38 RT-14-100P 48,000F R SERGES TANDEM REAR RAXILE 39 ALUM FRONTION OF REFERENCE WATER FRONTION FRONTION AND FRONTION OF SERGES TONDEM REAR RAXILE 40 AND LITEMACK LOOK VALVE, (1) DRIVER FRONTION FLORE WITH FIUL ROUND VOKES STIME FOR THE PROPERTY OF THE P	19	BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SACETY	soca	ICHD	CALLY C	1755	i Ng
22 IAGCOSS COMPRESSION GRAVE 23 IRVITODIBBARD NIDRES SIZE MOINTED HORIZONTAL AFTERTREATMENT SYSTEM ASSERBLY WITH LIB PILLAR MOUNTED VERTICAL TAILPIPE 23 ISHGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGISTERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH 24 BRIGHT UPPER STACK(S) 25 ISGALON DIESEL EXHAUST FLUID TANK 26 BORS WARNER (RYSOR) REAR AIR DINOFF EMSINE FAN DLUTCH DDG SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-FUEL INDICATOR. 26 H1500 SOUARE INCH ALTIMINUM RADIATOR 27 DELCO 12V 35MT-HDIOCO STRANSHISSION ALLISON AUTOMATIC 4500 RDS TRANSHISSION ALLISON AUTOMATIC 4500 RDS TRANSHISSION ALLISON AUTOMATIC 4500 RDS TRANSHISSION 30 MERITOR 18,5%6 Q- CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 31 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 32 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 33 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 34 IRV THP 60 DOWER STEERING WITH RCHAS AUXILIARY GEAR 35 RAGARRAGER SYNTHETIO FE TWING PRONT AXLE LUBE 36 RAGARRAGER SYNTHETIO FE TWING FRONT SLACK ADJUSTERS 37 RAGARRAGER SYNTHETIO FE TWING PRONT AXLE LUBE 38 RAGARRAGER SYNTHETIO FE TWING PRONT AXLE LUBE 39 4.50 REAR AXLE RATIO 40 MSL 170N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL BOUND YOKES 41 MSL 170N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL BOUND YOKES 42 ORIVER CONTROLLED TRACTION DIFFERENTIAL BOTH TANDEM REAR AXLE S 43 (1) INTERAXLE LOCK VALVE (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD REAR AND REAR REAR AXLE VALVE 44 MERITOR 16,3X8 62 Q- CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, ARBRICATED BHOS 45 GRAVE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE (S) 46 TUTETRAC 6500% 25 TAGE REAR SPRING SUSPENSION 47 TUTFTRAC STANDARD RIDG PLEIGHT 48 SINCH AXLE SPACING 49 FOR STANDARD RIDGE CONTROLLED DIFFERENTIAL LOCK FORWARD REAR AND REAR REAR RAYLE VALVE 40 FRANCE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE (S) 41 TUTETRAC 6500% 25 TAGE REAR SPRING SUSPENSION 41 TUTFTRAC 6500% 25 TAGE REAR SPRING SUSPENSION 42 FRANCE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE (S) 43	20		V				
22 (RING OUTBOARD UNIDER STEP MOUNTED FORZONTAL AFTERTRATMENT SYSTEM ASSEMENT WITH LIP BUILLAR MOUNTED VERTICAL TAILPIPE 23 ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ARE GENERATION AND DASH MOUNTED RECEMERATION REQUEST SWITCH 24 ENGINT UPPER STACKS) 25 13 GALLON DIESEL EXHAUST FLUID TANK 26 BORG WARNER (RYSOR) REAR AIR ONNOFE ENGINE FAN ELUTCH 27 DOC SUPPLIED ENGINE MOUNTED FUEL FITER/FUEL WATER SEPARATOR WITH WATER IN-FUEL HOROATOR. 28 1500 SOLURE INCH ALUMINUM RADIATOR 29 DELEO 12V 39MT+ HOROCP STARTER WITH THERMAL PROTECTION AND NTEGRATED MAGNETIC SWITCH 30 ALLISON AUTOMATIC SOR FOST TRANSMISSION 31 MFS-16-133A 16,000F FLI SINGLE FRONT AXLE 32 MERITOR, 16,356 G- CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FARRICATED SHOES 33 MERTOR AUTOMATIC FRONT SLACK ADJUSTERS 34 TRY THP-80 POWER STEERING WITH ROHS AUXILIARY GEAR 35 RADARAGES SYNTHELING FE 75 WAS PRONT AXLE LUBE 36 RADARAGES SYNTHELING FE 75 WAS PRONT AXLE LUBE 37 FRONT SHOCK ABSORBERS 38 RAT-46-160P 45,000F R SERRES TANDEM REAR AXLE 40 MXL 175M MERTIOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 39 RADARAGES SYNTHELING FE 75 WAS PRONT AXLE LUBE 41 MXL 171M MERTIOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 42 DRIVER CONTROLLED TRACTION DIFFERENTIAL BOTH TANDEM REAR AXLES 43 ORIVER CONTROLLED TRACTION DIFFERENTIAL BOTH TANDEM REAR AXLES 44 MERTOR 65,000 R SERRES TANDEM REAR RAKE PRANSES, DOUBLE ANCHOR, FABRICATED SHOES 45 DRIVER CONTROLLED TRACTION DIFFERENTIAL BOTH TANDEM REAR AXLES 46 ORIVER CONTROLLED TRACTION DIFFERENTIAL BOTH TANDEM REAR AXLES 47 OFFICE AND ARD CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 48 OFFICE AND ARD CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 49 OFFICE AND ARD CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 40 FRANCK CAMPS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 41 ULFRAC GLOWS AS ROCKE EARS PSPRING SUSPENSION 42 DENDRICKSON FET 132 ORIVER CAN FAILE THE SERVICE OF DRIVE AXLE(S) 44 HENDRICKSON FET 132 ORIVER CAN FER AXLE WITH HULDSR. HULDSR. 45 DENDRICKSON FET 132 ORIVE		MCORCCOMPRESSION REASE			2 3-1		
RESEMBLY THE REPUTATION AND DASH MOUNTED PROCESS THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH 26 RIGHT UPPER STACK(S) 27 TO SALLON DIESEL EXPAUST FLUID TANK 28 BORS WARNER RYSORN REAR AIR ON/OFE ENGINE FAN DLUTCH WATERIN-FUEL INDIGATOR. 29 FLOO 12V 39MT+ HORNER MOUNTED FUEL FITER/FUEL WATER SEPARATOR WITH WATERIN-FUEL INDIGATOR. 20 INDIG SURPEID ENRING MOUNTED FUEL FITER/FUEL WATER SEPARATOR WITH WATERIN-FUEL INDIGATOR. 20 INDIG SURPEID ENRING MOUNTED FUEL FITER/FUEL WATER SEPARATOR WITH WATERIN-FUEL INDIGATOR. 20 PELCO 12V 39MT+ HORDOO'S STAFTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH 31 INFS-R-1333 18,0009 FLI SINGLE FRONT AXLE 32 MERTOR AUTOMATIC 4500 ROS TRANSMISSION 33 MERTOR AUTOMATIC 4500 ROS TRANSMISSION 34 INFS-R-1333 18,0009 FLI SINGLE FRONT AXLE 35 MERTOR SLOOKS GO CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FARRICATED SHOES 36 MERTOR AUTOMATIC FRONT SLACK ADJUSTERS 37 RANDAMORES SYNTHEID FC 759409 FRONT AXLE LUBE 38 ROAD ANABORES SYNTHEID FC 759409 FRONT AXLE LUBE 39 ROAD ANABORES SYNTHEID FC 759409 FRONT AXLE LUBE 40 MAIL 175N MERTIOR EXTERNIBED LUBE MAIN DRIVELINE WITH FULL ROUND 40 WAIL 175N MERTIOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND 40 WAIL 175N MERTIOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND 40 PROVED CONTROLLED TRACTION DIFFERENTIAL. BOTH TANDEM REAR AXLES 41 MAIL 175N MERTIOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND 41 PROVIDED CONTROLLED TRACTION DIFFERENTIAL. BOTH TANDEM REAR AXLES 42 ORIVER CONTROLLED TRACTION DIFFERENTIAL. BOTH TANDEM REAR AXLES 43 (I) INTERAXLE LOCK VALVE, (I) DRIVER CONTROLLED DIFFERENTIAL LOCK 44 MERTOR 16,5X8,652 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, 45 GRAVE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 44 MERTOR 16,5X8,652 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, 46 GRAVE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TO FURLEY AND TANDEM SERVES CONTROLLED DIFFERENTIAL LOCK 47 TO FURLEY AND TANDEM SERVES CONTROLLED DRIVE AXLE(S) 48 TO FURLEY AND TANDEM SERVES CONTROLLED DRIVER		PHOUTBOARD INDER STEP HOLDERS ASSESSED			Sandy Service and		
REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH 28 BROWN UPPER STACK(S) 29 13 GALLON DIESEL EXHAUST FLUID TANK 20 BORG WARNER (KYSOR) REAR AIR ONIOFF ENGINE FAN CLUTCH 27 DOS SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR. 28 1500 SQUARE INCH ALUMRIUM RADIATOR 29 DELCO 1/2 39MT+ PHOOPOP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH 30 ALUSON AUTOMATIC 4500 RDS TRANSMISSION 31 MS-FIR 1334 18,000E FIS 1 SINGLE FRONT SALE 32 MERITOR 18,5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 33 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 34 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 35 ROADRANGER SYNTHETIG FE 50X-90 FRONT AXLE LUBE 36 18,000F TAPERLER FRONT SUSPENSION 37 FRONT SHOCK ABSORBERS 38 RT 45 180P 45,000F RSERRIES TANDEM REAR AXLE 40 MAL 175N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 41 MXL 17N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 42 ORIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 ONLY FOR A STANDER AND REAR REAR RAXLE AXLE 44 MXL 17N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND 45 ORIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 45 ONLY FOR A STANDER AXLE VALVE 46 ORIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 47 ONLY FOR A STANDER REAR REAR RAXLE VALVE 48 MERITOR 16,5X8 87 OF CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 49 FORES AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 10 THETRAC 45,000F STAGE REAR SPRING SUSPENSION 41 TUFFRAC 64,000F STAGE REAR SPRING SUSPENSION 42 FOREART AND TRANSVERSE GONTROL ROOS 43 SINCH AXLE SPAGING 44 FENDRICKSON FARALIFT ULTRA HUDOZ COMPOSILITE 13,200F AIR LIFT 51 HENDRICKSON FARALIFT ULTRA HUDOZ COMPOSILITE 13,200F AIR LIFT 51 HENDRICKSON FARALIFT ULTRA HUDOZ COMPOSILITE 13,200F AIR LIFT 51 HENDRICKSON FARALIFT ULTRA HUDOZ COMPOSILITE 13,200F AIR LIFT 51 HENDRICKSON FARALIFT ULTRA HUDOZ COMPOSILITE 13,200F AIR LIFT 51 HENDRICKSON FARALIFT ULTRA HUDOZ		ASSEMBLY WITH THE PILLAR MOUNTED VERTICAL TAILPIRE	M i		The second secon	-	No Mar 1
48 BRIGHT UPPER STACK(S) 29 BORS WARNER (KYSOR) REAR AIR OMOFF ENGINE FAN CLUTCH 27 DOG SUPPLIED ENGINE MOUNTED PUEL FILTERFUEL WATER SEPARATOR WITH WATER NEFUL INDIGATOR. 28 1500 SCUARE INCH ALUMINUM RADIATOR 29 DELEO 122 WATER INCH ALUMINUM RADIATOR 29 DELEO 122 WATER INCH ALUMINUM RADIATOR 30 ALUSON AUTOMATIC 4500 RDS TRANSMISSION 31 MFS-16-133 R1,000 FLI SINGLE FRONT AXLE 32 MERITOR, 16,696 G 1-637 SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 33 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 34 TRY THE-80 POWER STEERING WITH RICHES ALUXLUARY GEAR 35 ROADRANGER SYNTHETIO FE STAY SPIDER CAM FRONT BRAKES, LUBBE 36 18,000 FLAPERLEAF FRONT SUSPENSION 37 FRONT SHOCK ABSORBERS 38 RT 46-180P 45,000 FR. SERIES TANDEM REAR AXLE 40 MXL 178N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 41 MXL 178N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 42 ORIVER CONTROLLED TRACTION DIFFERENTIAL BOTH TANDEM REAR AXLES 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND FRAN FREAR AXLE VALVE 44 MERITOR IS 63.68 20 C ASST SPIDER CAM REAR RAKES, DOUBLE ANGHOR, FABRICATED SPICES 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 45.000 FS. STAGE REAR SPIRIG SUSPENSION 47 INTERAC STANDARD RICH HEIGHT 48 SI INCH AXLE SPACING 49 FOREART AND TRANSVERSE CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND FRANKERS ON FORWARD SIDE OF DRIVE AXLE(S) 40 FOREART AND TRANSVERSE CONTROL RODS. 41 HENDRICKSON FS 13.200 F PUSSIER AXLE INTEGRAL WITH HUSS 2.00 AIR LIFT 51 HENDRICKSON FS ADALLET ULTRA HUC2 COMPOSILITE 13.200 AIR LIFT 51 HENDRICKSON FS 13.200 F PUSSIER AXLE INTEGRAL WITH HUSSR 2. HLUC2 52 JORDAN FS 13.200 F PUSSIER AXLE INTEGRAL WITH HUSSR 2. HLUC2 53 JORDAN FS 13.200 F PUSSIER AXLE INTEGRAL WITH HUSSR 2. HLUC2 54 AND FRANCISCON FF 13.200 F PUSSIER AXLE INTEGRAL WITH HUSSR 2. HLUC2	-23	REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH	1		i s		
BORG WARNER (KYSOR) REAR AIR ONIOFF ENGINE FAIN CLUTCH 27 DOC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATERIN-FUEL INDICATOR 28 1500 SOUARE INCH ALUMINUM RADIATOR 29 DELCO 12V 39MT+ HIDIOCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETICS SWITCH 30 ALLISON AUTOMATIC 4500 RDS TRANSMISSION 31 IMFS-16-133A 18,000F FLI SINGLE FRONT AXLE 32 MERITOR, 18,500 FLO SOAT SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 33 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 34 INTERNITOR BY STARTER OF THE STANDER FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 35 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 36 ROADRANGER SYNTHETIO FE 75W-90 FRONT AXLE LUBE 37 FRONT SHOEK ASSORBERS 38 RT 46-180P 48,000F RESERIES TANDEM REAR AXLE 39 A.30 FRAN ALIE RATIO 40 MXL 175M MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 41 MXL 17M MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND 39 YOKES 41 MIXET TIM MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND 42 GRUVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK 44 PROMYER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 44 NERTOR 16,538,62 OF CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45 GRAVE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 ULFTRAC 48,000F 2-STAGE REAR SPRING SUSPENSION 47 TUFFRAC STANDARD RIDE HEIGHT 48 SIS INCH AXLE SPACING 49 FOREIAFT AND TRANSVERSE CONTROL RODS 40 ENDRICKSON FF1 13,200F PUSHER AXLE INTEGRAL WITH HUUSER 2, HLUC2 50 HENDRICKSON FF1 13,200F PUSHER AXLE INTEGRAL WITH HUUSER 2, HLUC2 50 HENDRICKSON FF1 13,200F PUSHER AXLE INTEGRAL WITH HUUSER 2, HLUC2 50 HENDRICKSON FF1 13,200F PUSHER AXLE INTEGRAL WITH HUUSER 2, HLUC2	24	BRIGHT UPPER STACK(S)		<u> </u>		The	A
BORG WARNER (KYSOR) REAR AIR ON/OFF ENDINE FAM DLUTCH 27 DOS SUPPLED BROINE MOUNTED FUEL FILTERFUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR. 28 1500 SOUARE INCH ALUMINUM RADIATOR. 29 DELOO 12V SWITH HOLOOP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH INTEGRATED MAGNETIC SWITCH INTEGRATED MAGNETIC SWITCH WAS ALLESON AUTOMATIC 4500 RDS TRANSMISSION 30 ALLISON AUTOMATIC 4500 RDS TRANSMISSION 31 MFS-18-1330 18,000# FILT SINIGLE FRONT AXLE 29 MERTIOR, 16,5X6 OF CAST SPICER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 33 MERTIOR AUTOMATIC FRONT SLACK ADJUSTERS 34 ITW THP-80 FOWER STEERING WITH ROHAS AUXILIARY GEAR 35 ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LURE 36 IR, 000# TAPERLEAF FRONT SUSPENSION 37 FRONT SHOCK ABSORBERS 38 RT-48-180P 45,000# R-SERIES TANDEM REAR AXLE 49 IS OR BRAR AXLE RATIO 40 MXL 176N MERTIOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 41 MXL 17N MERTIOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND 39 PROVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 41 MXL 17N MERTIOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND 39 PROVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 42 DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 (1) INTERAXLE LOCK VALVE. (1) DRIVER CONTROLLED DIFFERENTIAL LOCK 50 FORWARD-REAR AND REAR REAR AXLE VALVE 44 MERTIOR 16,538.82 OF CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, 51 FRANKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 45,000# 2 STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDGE HEIGHT 48 SIS INCH AXLE SPACING 49 FOREIAFT AND TRANSVERSE CONTROL RODS 49 FOREIAFT AND TRANSVERSE CONTROL RODS 49 FOREIAFT AND TRANSVERSE CONTROL RODS 40 FINDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HUDGE 2, HLUC2 50 HENDRICKSON FF1 12,200# PUSHER AXLE INTEGRAL WITH HUDGE 2, HLUC2 51 HENDRICKSON FF1 12,200# PUSHER AXLE INTEGRAL WITH HUDGE 2, HLUC2 52 JERUS AND AND AND AND AND AND AND	25			-			
DOC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATERIN-FUEL INDICATOR 1500 SOUARE INCH ALUMINUM RADIATOR DELCO 12V 38MT+ HDIOCO STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNET CS WITCH 30 ALLISON AUTOMATIC 4500 RDS TRANSMISSION 31 MES-16-133A 18,000F FLI SINGLE FRONT AXLE MERITOR, 18,696 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FARRICATED SHOES 33 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 34 TRW THP-80 POWER STEERING WITH ROHS AUXILIARY GEAR 35 RADADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUSE 36 RADADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUSE 37 FRONT SHOCK ABSORBERS 38 RADADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUSE 39 A.50 REAR AXLE RATIO 40 MXL 178N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 41 MXL 178N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 42 GRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 IN THE MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND 44 WERITOR 18,538,82 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FORWARD-REAR AND REAR REAR AXLE VALVE 44 WERITOR 18,538,82 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FORWARD-REAR AND REAR REAR AXLE VALVE 45 GRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 45,000# 2-STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDE HEIGHT 48 SIS INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE CONTROL RODS. 49 FORE/AFT AND TRANSVERSE CONTROL RODS. 50 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HUSER 2, HUC2 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HUSER 2, HUC2 52 SUSPENSIONS 52 JENSHMANUE AND AVIS SERVER AXLE INTEGRAL WITH HUSER 2, HUC2 53 SERVER PUSHERS USPENSION WITH HENDRICKSON FF1 3XLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HUSER 2, HUC2 53 SERVER PUSHERS USPENSION WITH HENDRICKSON FF1 3XLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HUSER 2, HUC2	26	BORG WARNER (KYSOR) REAR AIR ON/OFF ENGINE FAN CLUTCH					and the state of t
28 1500 SOUARE INCH ALUMINUM RADIATOR 29 DELCO 12V 39MT + IDDICCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MANDER CIS SWITCH 30 ALLISON AUTOMATIC 4500 RDS TRANSMISSION 31 MF-3-1533 15,000# FL1 SINGLE FRONT AXLE 32 MERITOR 16,506 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 33 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 34 TRW THP-80 POWER STEERING WITH ROHAS AUXILIARY GEAR 35 ROADRANGER SYNTHETIC FE 759/-90 FRONT AXLE LUBE 36 18,000# TAPERLEAF FRONT SUSPENSION 37 FRONT SHOCK ABSORBERS 48 RT-46-180P 45,000# R-SERIES TANDEM REAR AXLE 49 400 REAR AXLE RATIO 40 MXL 178N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 41 MXL 178N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES 42 DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD REAR AND REAR REAR AXLE VALVE 44 MERITOR 16,538,62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANGHOR, FABRICATED SHOES 45 SRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 10 TIVETRAC 45,000# 2-STAGE REAR SPRING SUSPENSION 10 TIVETRAC 5TANDARD RIDE HEIGHT 55 MICH AXLE SPACING 56 NICH AXLE SPACING 57 HENDRICKSON FR1 13,200# PUSHER AXLE INTEGRAL WITH HUSGR-2, HLUC2 58 HENDRICKSON FR1 13,200# PUSHER AXLE INTEGRAL WITH HUSGR-2, HLUC2 58 SUSPENSIONS 59 SUSPENSIONS	27	DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH			to an employee and the second		
DELCO 12V 39MT + IDDOCP STARYER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH 30 ALLISON AUTOMATIC 4500 RDS TRANSMISSION 31 MFS-19-133A 18,000# FLY SINGLE FRONT AXLE 42 MERITOR 18,5% CP CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 33 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 34. TRW THP-80 POWER STEERING WITH RCH45 AUXILIARY GEAR 35 ROADPANIGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE 36 18,000# TAPERLEAF FRONT SUSPENSION 37 FRONT SHOCK ABSORBERS 18 38 RT-48-180P 45,000# R-SERIES TANDEM REAR AXLE 4.30 REAR AXLE RATIO 40 MXL 178 MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 18 T MAL 178 MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES 41 MXL 178 MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES 42 DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR REAR AXLE VALVE 44 MERITOR 18,5X8 62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 45,000# 2-STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDE HEIGHT 48 68 INCH AXLE SPACING 49 FOREART AND TRANSVERSE CONTROL RODS 49 FOREART AND TRANSVERSE CONTROL RODS 50 HENDRICKSON PRANSVERSE CONTROL RODS 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HUSSR-2, HLUC2 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HUSSR-2, HLUC2 52 SUSPENSIONS	28	· mailinearman and an an an an an an an an an an an an an					
INTEGRATED MAGNETIC SWITCH			1				- 134 95 100
MERITOR 16,500 C CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 33 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 34 TRW THP-80 POWER STEERING WITH RCH4S AUXILIARY GEAR 55 ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE 36 18,000# TAPERLEAF FRONT SUSPENSION 27 FRONT SHOCK ABSORBERS 39 1-30 REAR AXLE RATIO 40 MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 41 MXL 176N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES 42 DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR REAR RAXLE VALVE 44 MERITOR 16,500 8C Q CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 45,000# 2-STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDE HEIGHT 48 56 INCH AXLE SPACING 49 FOREIAFT AND TRANSVERSE GOTTROL RODS. 50 HENDRICKSON PARALET ULTRA HLUCZ COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HEUDRICKSON FF1 AXLE 51 HENDRICKSON PARALET ULTRA HLUCZ COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HEUDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS	20	INTEGRATED MAGNETIC SWITCH	/			4	
MERITOR, 16,5% 0+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 38 MERITOR AUTOMATIC FRONT SLACK ADJUSTERS 39 TRW THP-80 POWER STEERING WITH RCH4S AUXILIARY GEAR 85 ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE 18,000 TAPERICAF FRONT SUSPENSION 19,7 FRONT SHOCK ABSORBERS 19,38 RT-46-180P 45,000 R SERIES TANDEM REAR AXLE 19,9 4.30 REAR AXLE RATIO 40 MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 18 THE MENTON EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES 19 AND REAR AXLE RATIO 41 MXL 176N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES 42 DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR REAR AXLE VALVE 44 MERITOR 18,5X8,62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 INTERRAC 45,000 2+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 47 TUFTRAC 45,000 2+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 48 SINCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE GONTROL RODS 49 FORE/AFT AND TRANSVERSE GONTROL RODS 50 HENDRICKSON PARALLET ULTRA HLUCZ COMPOSILITE 13,200# AIR LIFT 51 STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUSIR 2, HLUC2 SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUSIR 2, HLUC2 SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUSIR 2, HLUC2 SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUSIR 2, HLUC2 SUSPENSION							
#ABRICATED SHOES MERITOR AUTOMATIC FRONT SLACK ADJUSTERS TRW THP-80 POWER STEERING WITH RCH45 AUXILIARY GEAR \$5 ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE \$6 18,000# TAPERLEAF FRONT SUSPENSION \$7 FRONT SHOCK ABSORBERS \$8 RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE \$9 94 430 REAR AXLE RATIO 40 MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES \$1			1		thys colony, almost part in a minimum.		
34. TRW THP-80 POWER STEERING WITH RCH45 AUXILLARY GEAR 85. ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE 36. 18,000# TAPERLEAF FRONT SUSPENSION 27. FRONT SHOCK ABSORBERS 38. RT-46-180P 45,000# R-SERIES TANDEM REAR AXLE 39. 4,30 REAR AXLE RATIO 40. MXL 178N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 18T MENTON AUTO INTEXACE 41. MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND 42. ORIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43. (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK 44. MERITOR 16,5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, 45. FABRICATED SHOES 45. BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46. TUFTRAC SA,000# 2-STAGE REAR SPRING SUSPENSION 47. TUFTRAC STANDARD RIDE HEIGHT 48. 55 INCH AXLE SPACING 49. FORE/AFT AND TRANSVERSE CONTROL RODS. 40. HENDRICKSON PARALIET ULTRA HLUCZ COMEOSILITE 13,200# AIR LIFT 51. STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51. HENDRICKSON FF1 13.200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 52. GURSPINIONS		MERITOR 15,5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	/				1. 2
35 ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE 36 18,000# TAPERLEAF FRONT SUSPENSION 37 FRONT SHOCK ABSORBERS 38 RT 46-1800 # 8,000# R-SERIES TANDEM REAR AXLE 39 4,30 REAR AXLE RATIO 40 MXL 178N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 18 T	33	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		 			
35 ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE 36 18,000# TAPERLEAF FRONT SUSPENSION 37 FRONT SHOCK ABSORBERS 38 RT 46-160P 45,000# R-SERIES TANDEM REAR AXLE 39 4,30 REAR AXLE RATIO 40 MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 18 T	34	TRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR	V	ļ <u></u>		i	
18 18,000# TAPERLEAF FRONT SUSPENSION 27 FRONT SHOCK ABSORBERS 38 RT 46-160P 45,000# R-SERIES TANDEM REAR AXLE 39 4,30 REAR AXLE RATIO 40 MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 18 T M SUTPON ANTO I NAMED YOKES 41 MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND 42 VOKES 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK 44 MERITOR 16,5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDE HEIGHT 48 SE INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE CONTROL RODS 50 HENDRICKSON PARALIET ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT 51 STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 52 SUSPENSIONS	35	ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE					
37 FRONT SHOCK ABSORBERS 48 RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE 39 4.30 REAR AXLE RATIO 40 MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 41 MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES 42 DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD REAR AND REAR REAR AXLE VALVE 44 MERITOR 16,5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 45,000# 2-STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDE HEIGHT 48 56 INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE CONTROL RODS 50 HENDRICKSON PARALIET ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL, WITH HLUS/R-2, HLUC2 SUSPENSIONS	36	18,000# TAPERLEAF FRONT SUSPENSION	- V	<u> </u>	· · · · · · · · · · · · · · · · · · ·		
43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC STANDARD RICE HEIGHT 47 TUFTRAC STANDARD RICE HEIGHT 48 56 INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE GONTROL RODS 50 HENDRICKSON PARALIFT ULTRA HLUCZ COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL, WITH HLUS/R-2, HLUCZ SUSPENSIONS	.37						-
39 34.30 REAR AXLE RATIO 40 MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES 18 T M FUTON AUTO I NAMED A 41 MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND 42 DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE 44 MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDE HEIGHT 48 65 INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE CONTROL RODS. 50 HENDRICKSON PARALIET ULTRA HLUCZ COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS	₹ 38	RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE					
MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES ### MXL 176N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND ### MXL 176N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND ### MXL 176N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND ### MXL 176N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND ### ROUND DRIVER CONTROLLED TRACTION DIFFERENTIAL LOCK ### FORWARD-REAR AND REAR REAR AXLE VALVE ### MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, ### FABRICATED SHOES ### FORE/ARS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) ### ROUND HAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) ### FORE/AFT AND TRANSVERSE GONTROL RODS. ### FORE/AFT AND TRANSVERSE GONTROL RODS. ### PORE/AFT AND TRANSVERSE GONTROL RODS. ### HENDRICKSON PARALIET ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT ### STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE ### HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 ### SUSPENSIONS	39						*****
MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES 42 DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE 44 MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDE HEIGHT 48 56 INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE CONTROL RODS. 49 FORE/AFT AND TRANSVERSE CONTROL RODS. 50 HENDRICKSON PARALIET ULTRA HLUCZ COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS	40	MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL POLIND VOYES	V				-
DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES 43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE 44 MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDE HEIGHT 48 56 INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE CONTROL RODS. 50 HENDRICKSON PARALIET ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FET AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS	<i>N</i> 4	18T MENTON AUTOINHAME	/				
43 (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE 44 MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDE HEIGHT 48 56 INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE CONTROL RODS. 50 HENDRICKSON PARALIET ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS 52 (M.DASH VALVE AND (4) OF HOT FOR AND (5) OF HENDRICKSON FF1 AXLE		TOURS TO THE REPORT OF THE PARTY OF THE PART					
(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE 44 MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDE HEIGHT 48 56 INCH AXLE SPACING. 49 FORE/AFT AND TRANSVERSE CONTROL RODS. 50 HENDRICKSON PARALIFT ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS	42	UNIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES					
FORWARD-REAR AND REAR-REAR AXLE VALVE 44. MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45. BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46. TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION 47. TUFTRAC STANDARD RIDE HEIGHT 48. 56 INCH AXLE SPACING. 49. FORE/AFT AND TRANSVERSE CONTROL RODS. 50. HENDRICKSON PARALIFT ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE. 51. HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL, WITH HLUS/R-2, HLUC2 SUSPENSIONS.			V				
44 MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES 45 BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 46 TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION 47 TUFTRAC STANDARD RIDE HEIGHT 48 56 INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE CONTROL RODS 50 HENDRICKSON PARALIFT ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS	43	(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE	1		1		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) 10 TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION 17 TUFTRAC STANDARD RIDE HEIGHT 18 56 INCH AXLE SPACING 19 FORE/AFT AND TRANSVERSE CONTROL RODS 50 HENDRICKSON PARALIFT ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS 52 (A) DASH VALVE AND (A) OF LOS FOR SUSPENSION	44 ,.	MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR			The state of the s		74
TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION TUFTRAC STANDARD RIDE HEIGHT 48 56 INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE CONTROL RODS 50 HENDRICKSON PARALIFT ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS 52 (A) DASH VALVE AND (A) OF LOCE FOR ALLE	45	Allina (1997)	-), E.
47 TUFTRAC STANDARD RIDE HEIGHT 48 56 INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE CONTROL RODS. 50 HENDRICKSON PARALIFT ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS 52 (A) DASH VALVE AND (A) OF LOCE FOR ALLE		TUETRAC 46.000# 2-STAGE REAR SERING SUSPENSION	V,				The second second
48 56 INCH AXLE SPACING 49 FORE/AFT AND TRANSVERSE CONTROL RODS. 50 HENDRICKSON PARALIFT ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS 52 (A) DASH VALVE AND (A) OF FOR SUSPENSION			V				
49 FORE/AFT AND TRANSVERSE CONTROL RODS 50 HENDRICKSON PARALIFT ULTRA HLUCZ COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUCZ SUSPENSIONS 52 (A) DASH VALVE AND (A) OF LOT FOR SUSPENSION		SS INCH AVI E CHACING	V				
50 HENDRICKSON PARALIFT ULTRA HLUC2 COMPOSILITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS 52 (A) DASH VALVE AND (A) OF LOCE FOR SUPPLIES.		Employment of the second of th	1				
STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE 51 HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS							
52 M DARL VALVE AND WAR FOR AN		STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE	/				
52 (1) DASH VALVE AND (1) GAUGE FOR SINGLE LIFT AXLE	51	HENUKICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLUS/R-2, HLUC2 SUSPENSIONS					
	52	(f) DASH VALVE AND (1) GAUGE FOR SINGLE LIFT AXLE					

.

, į

:			ž.				-5
11	53	REVERSE LIFT AXLE WIRING WITH LAST STATE RETENTION WITH IGNITION OFF					
	54	AIR PIPING FOR (1) LIFT/NON-LIFT AXLE WITH REGULATOR CHASSIS MOUNTED			4		
	55	MERITOR 15X4 Q+ CAM PUSHER/TAG BRAKES, DOUBLE ANCHOR, FABRICATED		-	erroritorer A tributer i manage et auto di disconi espana a se		
		SHOES	1				- W. W.
	56	MERITOR AUTOMATIC PUSHER/TAG SLACK ADJUSTERS	/			17-	
	.57	HENDRICKSON HLUC2 13,200# AIR LIFT STEERABLE PUSHER AXLE SUSPENSION			<u>.</u>		te '
Î	58	WABCO 45/4M ABS WITHOUT TRACTION CONTROL	V		3		1.40
	.59	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED THROUGH IGNITION	/				
	60	SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME	/		- 414		
Ž	61	5650MM (222 INCH) WHEELBASE					
	62	11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI	/		Citing section 2 - 1	j.	
2.7	63	1/4 INCH (6MM) C-CHANNEL INNER FRAME REINFORGEMENT	1		Antonio Mariano de Sporido promiso propriato de Caracida de Caraci		-
Ĭ.	64	HEAVY DUTY SUSPENSION CROSSMEMBER	1				
	65	16.5 INCH CHROME STEEL STRAIGHT BUMPER			The state that he gives we have the property of the same of the sa		
	66	100 GALLON/378 LITER ALUMINUM FUEL TANK - LH					
	67	GOODYEAR G296 MSA 385/65R22.5 18 PLY RAD IAL FRONT TIRES MCHELP	7	12.7			
1	68	GOODYEAR G288 11R22,5 16 PLY RADIAL REAR TIRES			Y		
	69	GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES	1				
	70	CONMET PRE-SET BEARING ALUMINUM REAR HUBS					1. 635
	71	ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS	/			•	A STATE OF THE PARTY OF THE PAR
	72	ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS	/	7 - 1			
	73	ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS				E.S.,	
	74	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB 11011 BBC	51821				
	75	IAIR CAB MOUNTS	7				
	76	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE	1				and the state of t
	77	CHROMED HOOD MOUNTED AIR INTAKE GRILLE					
	78	DUAL 26 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS ROOF MOUNTED	/				
	79	DUAL HORN SHIELDS			***************************************		man and head agreement
Ĺ.,		HALOGEN COMPOSITE HEADLAMPS WITH BRIGHT BEZELS					***
	81	DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE	N	· · · · · · · · · · · · · · · · · · ·			
	. 82	DOOR MOUNTED MIRRORS					
	83.	LH AND RH 8" BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS	/				
	84	TINTED DOOR GLASS LH AND RH WITH TINTED OPERATING WING WINDOWS				<u> </u>	
		RH AND LH ELECTRIC POWERED WINDOWS					
. -		INTERIOR CONVENIENCE PACKAGE WITH CB PROVISION	//		<u> </u>		
ساونسا	the street of the street of	2-1/2 LB. FIRE EXTINGUISHER	'				
		HEATER, DEFROSTER AND AIR CONDITIONER					المناء والمراجع
نب	, u u	INCULENT ACTION LETY VIAN VIV COUNTY FOUND	√	<u> </u>			<u> </u>

89	CAB INSULATION					<u></u>
90		V				
91	LH AND RH ELECTRIC DOOR LOCKS					
92	(1) 12 VOLT POWER SUPPLY IN DASH	1				
93	TRIANGULAR REFLECTORS WITHOUT FLARES			-		
94	BOSTROM TALLADEGA 910 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH AIR LUMBAR					
95	HIGH BACK NON SUSPENSION PASSENGER SEAT					
96	LH AND RH INTEGRAL DOOR PANEL ARMRESTS	1				
97	CLOTH DRIVER SEAT COVER	V,				
98	CLOTH PASSENGER SEAT COVER	V				
		V,				
99	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN	2				
100	97 DB BACKUP ALARM	V				
101	ELECTRONIC CRUISE CONTROL WITH SWITCHES ON AUXILIARY GAUGE PANEL (B	/		The state of the s		
102	ODOMETER/TRIP/HOUR/DIAGNOSTIC/VOLTAGE DISPLAY: 1X7 CHARACTER, 26 WARNING LAMPS, DATA LINKED, ICU3					
103	DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1939, LOCATED BELOW DASH	/				- "
104	2 INCH ELECTRIC FUEL GAUGE			-		
105	FUEL FILTER RESTRICTION INDICATOR		+			
106	DUAL REAR AXLE TEMPERATURE GAUGES FOR TANDEM AXLES		 			
107	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE					
108	ENGINE OIL TEMPERATURE GAUGE			ļ		· · · · · · · · · · · · · · · · · · ·
109	2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		ļ			
110	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		-			
111	ELECTRIC ENGINE OIL PRESSURE GAUGE	1				energe announce of the second
112	AWFMWB RADIO WITH FRONT AUXILIARY INPUT 🗸			***************************************	1.6	****
113	The state of the s				-	<u> </u>
114	DASH MOUNTED RADIO ELECTRONIC 3000 RPM TACHOMETER TOP MOCUNTED	/	***************************************	and a state of the	-	·
115	TRAILER HAND CONTROL BRAKE VALVE			ann main manamanga da ara ka diffinisa	1	
116	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHERWIPER AND			<u> </u>		<u> </u>
f17	HAZARD IN HANDLE					Year a San
	PAINT: ONE SOLID COLOR	1				
118	CAB COLOR (EQUAL TO L5495EB ULTRA RED PEARL METALLIC ELITE BC)					***************************************
119	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT					
120	Weight Front 9324 lbs: Weight Rear 9694 lbs. Total Weight 19,018 lbs.					
	Unit cost and buy back proposal	/				
1	Bidder shall list the purchase price per unit here and on top sheet. \$ 145,603.	(42 <u>)</u>		•		-
2	Bidder shall list the guaranteed three (3) year/150,000 mile dealer buy back price here per ur	nit and on t	op sheel. S	91,500.	(en	7
	The state of the s					
<u> </u>				2.		

Prepared for: Eugene Neff Craighead County Highway Department 2800 Moore Rd Jonesboro, AR 72401 Phone: 870-933-4510

Prepared by: Pat Mchugh CROWS TRUCK SERVICE 5278 HWY, 78 MEMPHIS, TN 38118 Phone: 901-366-6611

SPECIFICATION PROPOSAL

Weight Weight Description Front Rear WESTERN STAR 4700 PRL-18T (EFF:04/14/18) Data Version SPECPRO21 DATA RELEASE VER 002 Vehicle Configuration 4700 SET-FORWARD FRONT AXLE CHASSIS 9,100 6,720 2019 MODEL YEAR SPECIFIED SET FORWARD AXLE - TRUCK TRAILER TOWING PROVISION AT END OF 10 10 FRAME FOR TRUCK LH PRIMARY STEERING LOCATION General Service

TRUCK/TRAILER CONFIGURATION

DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)

CONSTRUCTION SERVICE

GOVERNMENT BUSINESS SEGMENT

DIRT/SAND/ROCK COMMODITY

TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS

MAXIMUM 8% EXPECTED GRADE

SMOOTH CONCRETE OR ASPHALT PAVEMENT -MOST SEVERE IN-TRANSIT (BETWEEN SITES) **ROAD SURFACE**

WESTERN STAR VOCATIONAL WARRANTY

EXPECTED FRONT AXLE(S) LOAD: 18000.0 ibs

EXPECTED REAR DRIVE AXLE(S) LOAD:

46000,0 lbs

EXPECTED PUSHER AXLE(S) LOAD: 13200.0 lbs



Prepared for:
Eugene Neff
Craighead County Highway Department
2800 Moore Rd
Jonesboro, AR 72401

Prepared by:
Pat Mchugh
CROWS TRUCK SERVICE
5278 HWY, 78
MEMPHIS, TN 381,18
Phone: 901-366-6611

Description

Weight Front Weight Rear

EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 77200.0 lbs

EXPECTED GROSS COMBINATION WEIGHT: 80000,0 lbs

Truck Service

Phone: 870-933-4510

END DUMP BODY

Engine

DETROIT DD13 12.8L 450 HP @ 1625 RPM, 1900 GOV RPM, 1650 LB/FT @ 975 RPM

Electronic Parameters

65 MPH ROAD SPEED LIMIT

CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT

5 MINUTES IDLE SHUTDOWN WITH CLUTCH AND SERVICE BRAKE OVERRIDE

PTO MODE ENGINE RPM LIMIT - 1400 RPM

PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED OR PARK BRAKE NOT APPLIED

PTO RPM WITH CRUISE RESUME SWITCH - 900 RPM

PTO MODE CANCEL VEHICLE SPEED - 6 MPH

PTO GOVERNOR RAMP RATE - 25 RPM PER

SECOND

ONE REMOTE PTO SPEED

PTO SPEED 1 SETTING - 900 RPM

SOFT CRUISE CONTROL ENABLED

PTO MINIMUM RPM - 600

Engine Equipment

2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION

2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)

STANDARD OIL PAN

ENGINE MOUNTED OIL CHECK AND FILL

ONE PIECE VALVE COVER

SIDE OF HOOD AIR INTAKE WITH DONALDSON HIGH CAPACITY AIR CLEANER WITH SAFETY ELEMENT, FIREWALL MOUNTED

DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE

Application Version 9.3,212 Data Version PRL-18T.002 Copy of Cralghead County



04/28/2018 11:56 AM

Page 2 of 17

Prepared for:
Eugene Neff
Craighead County Highway Department
2800 Moore Rd
Jonesboro, AR 72401
Phone: 870-933-4510

Prepared by:
Pat Mchugh
CROWS TRUCK SERVICE
5278 HWY, 78
MEMPHIS, TN 38118
Phone: 901-366-6611

Description	Weight Front	Weight Rear	
(3) ALLIANCE MODEL 1231XOE, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES	-10		
BATTERY BOX FRAME MOUNTED	35		
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB			
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN			
NON-POLISHED BATTERY BOX COVER	i		
POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER	2		
BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE			
AIR COMPRESSOR DISCHARGE LINE			
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM			
JACOBS COMPRESSION BRAKE			
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE			
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH			,
11 FOOT 06 INCH (138 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT			
STANDARD CURVE BRIGHT UPPER STACK(S)	•		
RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP			
13 GALLON DIESEL EXHAUST FLUID TANK	35	10	
100 PERCENT DIESEL EXHAUST FLUID FILL			
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING			
LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION			
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD			
BORG WARNER (KYSOR) REAR AIR ON/OFF ENGINE FAN CLUTCH		•	
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED			
DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR			·



Prepared for: Eugene Neff Craighead County Highway Department 2800 Moore Rd Jonesboro, AR 72401 Phone: 870-933-4510

Prepared by:
Pat Mchugh
CROWS TRUCK SERVICE
5278 HWY, 78
MEMPHIS, TN 38118
Phone: 901-366-6611

Description

Weight Front Weight Rear

FULL FLOW OIL FILTER

1500 SQUARE INCH ALUMINUM RADIATOR
MOUNTING FOR FIREWALL MOUNTED SURGE

MOUNTING FOR FIREWALL MOUNTED SURGE TANK

ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT

GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT

CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES

HDEP FIXED RATIO COOLANT PUMP AND RADIATOR DRAIN VALVE

LOWER RADIATOR GUARD

PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER

PHILLIPS-TEMRO 300 WATT/115 VOLT OIL PRÉHEATER

CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR

ALUMINUM FLYWHEEL HOUSING

MITSUBISHI 12V MOD 3.175-DP60 STARTER WITH INTEGRATED MAGNETIC SWITCH

Transmission

ALLISON 4500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION

170

50

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 -AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV

ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES

PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

S1 PREFORMANCE PRIMARY SHIFT SCHEDULE, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

S1 PERFORMANCE SECONDARY SHIFT SCHEDULE, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

1800 RPM PRIMARY MODE SHIFT SPEED

Application Version 9.3.212 Data Version PRL-18T,002 Copy of Craighead County



04/28/2018 11:56 AM

Prepared for: Eugene Neff Craighead County Highway Department 2800 Moore Rd Jonesboro, AR 72401

Phone: 870-933-4510

Prepared by: Pat Mchugh CROWS TRUCK SERVICE 5278 HWY, 78 MEMPHIS, TN 38118 Phone: 901-366-6611

Description

Weight Front Weight Rear

1600 RPM SECONDARY MODE SHIFT SPEED

LOAD BASED SHIFT SCHEDULE AND VEHICLE ACCELERATION CONTROL RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED **VOCATIONAL USAGE**

ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR, BLUNT CUT, MOUNTED BETWEEN DRIVER AND PASSENGER SEATS

CUSTOMER INSTALLED CHELSEA 277 SERIES

PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION

MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND

PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED

TRANSMISSION PROGNOSTICS - ENABLED 2013

WATER TO OIL TRANSMISSION COOLER, FRAME MOUNTED

TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK

SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)

15

Front Axle and Equipment

MFS-18-133A 18,000# FL1 71.0 INCH KPI/3.74

INCH DROP SINGLE FRONT AXLE

MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES

NON-ASBESTOS FRONT BRAKE LINING

CONMET CAST IRON FRONT BRAKE DRUMS

FRONT OIL SEALS

VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL

STANDARD SPINDLE NUTS FOR ALL AXLES

MERITOR AUTOMATIC FRONT SLACK **ADJUSTERS**

STANDARD KING PIN BUSHINGS

TRW THP-60 POWER STEERING WITH RCH45

AUXILIARY GEAR

POWER STEERING PUMP

4 QUART POWER STEERING RESERVOIR

OIL/AIR POWER STEERING COOLER

60

90

Application Version 9,3,212 Data Version PRL-18T.002 Copy of Craighead County



04/28/2018 11:56 AM

Page 5 of 17

Prepared for: Eugene Neff Craighead County Highway Department 2800 Moore Rd Jonesboro, AR 72401 Phone: 870-933-4510

Prepared by:
Pat Mchugh
CROWS TRUCK SERVICE
5278 HWY, 78
MEMPHIS, TN 38118
Phone: 901-366-6611

Description	Weight Front	Weight Rear	
ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE	<u> </u>		
Front Suspension			
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION	-90		
FRONT SHOCK ABSORBERS			
Rear Axle and Equipment			
RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE		450	
4.30 REAR AXLE RATIO			
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING			
MXL 18T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	40	40	
MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES			
DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES		30	
(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD- REAR AND REAR-REAR AXLE VALVE			
INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH			
INDICATOR LIGHT FOR EACH DRIVER CONTROLLED TRACTION DEVICE SWITCH			
MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES			
NON-ASBESTOS REAR BRAKE LINING			
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)			
CONMET CAST IRON REAR BRAKE DRUMS			
REAR OIL SEALS			
WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS		*	
HALDEX AUTOMATIC REAR SLACK ADJUSTERS			
SYNTHETIC 75W-90 REAR AXLE LUBE			

TUFTRAC 46,000# REAR SPRING SUSPENSION

TUFTRAC STANDARD RIDE HEIGHT

AXLE CLAMPING GROUP

Application Version 9.3.212 Data Version PRL-18T,002 Copy of Craighead County



04/28/2018 11:56 AM

490

Page 6 of 17

The Jonesboro Sun

AILY AND SUNDAY

Proof of Publication

STATE OF ARKANSAS COUNTY OF CRAIGHEAD		· · · · · · · · · · · · · · · · · · ·
		,
		÷
circulation printed in the Wes advertising manager at the da a bonafide circulationin such	solemnly swear that I IONESBORO SUN daily newspaper of general stern District of Craighead County and I was such classifiate of publication hereinafter stated, and that said newspaceounty at said dates, and had been regularly published in next before the date of the first publication of the advert terment was published in said	aper had said county
newspaper_1	_times once a week for_1	The state of the s
weeks consecutively, the firs	t insertion therein having been made on the	
19	day of April, 2018	<u> </u>
	day of	_
	day of	
Ÿ .	day of	
	day of	
	day of	
7th insertion	~ 1//	-
<u>Lisa A.</u>	Lynn	r
Sworn to and subscribed befo	re me this 19 day of April 2018 April 2018	-
My commission 4 Lo-2	a	OFFICIAL SEAL TON
Fee for print, \$		JANET MELTON JANET MELTON 12389619
Cost of Proof \$ 76.70	•	NOTARY PUBLIC ARKANSAS NOTARY PUBLIC ARKANSAS NOTARY PUBLIC ARKANSAS NOTARY PUBLIC ARKANSAS NOTARY PUBLIC ARKANSAS
Rec'd Payment \$		MY COMMISSION FACTOR
Total \$ 76.70	The state of the s	

CRAIGHEAD COUNTY JUDGES OFFICE BILLING DEPT 511 UNION STE 119 JONESBORO, AR 72401 (870)933-4500

Class Liner Ad #90722856 Summary:

Description: NOTICE TO BIDDERS Craighead C

Size: 1.00 x 4.10

Net Cost

\$76.70

Prepaid Amount

\$0.00

Amount Due

\$76.70

If paid by credit card, your statement will show the charge as "Newspaper Services - Paxton Media"

Order Detail:

Publication	Start	 Insertions
20JN Jonesboro Sun		1

NOTICE TO BIDDERS

Craighead County is now accepting bids until 2:00 PM, May 2, 2018, at the Craighead County Judge's office for the following:

Purchase two (2) Dump trucks with three year/ 150,000 mile dealer buyback program.

Bid specifications may be picked up at the County Judge's office, Craighead County Courthouse Annex, 511 Union St, Suite 119, Jonesboro, Arkansas, Monday through Friday, from 8:00 A.M. until 5:00 P.M.

Bids will be opened at 2:00 PM, May 2, 2018, in the County Judge's office.

The County reserves the right to reject any and all bids or any part of any specific bid.

Bid specifications are available on the County Web Site at www.craigheadcounty

<u>org</u> Al Haines Purchasing Agent Craighead County NOTICE TO BIDDERS
Craighead County is
now accepting bids until 2:00 PM, May 2, 2018,
at sthe Craighead
Gounty Judge's office
for the following:
Purchase two (2) Dump
trucks with three year/
i50,000 mile dealer buypack program
Bid specifications may
be picked up at the
County Judge's office,
Graighead County
Courthouse Annex, 5:11
Union, st., Suite :119
Jonesboro, Arkansas,
Monday through Friday,
from 8:00 A.M. until 5:00
P.M.
Bids will be opened at
2:00 PM, May 2, 2018, in
the County Judge's office,
The County Judge's office,
The County reserves
the right to reject any
and all bids or any part
of any specific bid.
Bid specifications are
available on the County
W e b S it e a t
www.sfaigheadcounty
Org
Al Haines
Purchasing Agent
Craighead County