

CRAIGHEAD COUNTY
INVITATION TO BID-Not an Order
 Craighead County Judge's Office
 511 Union St.; Suite 119
 Jonesboro, Arkansas 72401

PURCHASING OFFICE

BID NO. 2025-9

DATE: February 12, 2025

Sealed bids, subject to the conditions on the reverse hereof, and as may be attached hereto, will be received at this office until 2:00 PM February 26, 2025 and then publicly opened, for furnishing the supplies, materials, and/or services as described below.

Bids will be opened February 26, 2025.
 2:00 P.M. Local Time

F.O.B Jonesboro, Arkansas

BY: Al Haines
 PURCHASING DIRECTOR

Maximum Delivery or completion time after issuance of Purchase

Order or work ordered by County 180 days.

Item #	DESCRIPTION	QUANT	UNIT	UNIT PRICE	AMOUNT
1	Furnish two (2) each Dump Trucks with Automatic transmissions and with installed dump beds to Craighead County Road Department, 2800 Moore Road, Jonesboro, AR. 72401 according to attached specifications. Trucks are to have dump beds and hydraulics installed and fully operational when delivered.	2			
2	This bid package contains 6 pages. All 6 pages should be returned to complete bid.				
3	Bid must be signed by authorized company representative.				
4	Bidder should: A. Clearly define and list warranty information on each item in years. B. Include all labor, delivery charges, training, programming, and any other charges FOB Jonesboro, Arkansas 72401, in bid price. C. Include product literature and specifications with bid. D. All relevant information will be considered when determining best bid for Craighead County. E. Specify cash discounts, if available. F. Note bid number on outside of bid envelope. G. Specify approximate ship time in days, if awarded bid. F. List make, model, and manufacturer of equipment being offered. G. Quote same or equal equipment in all aspects. H. Specify nearest service and parts supply location to Jonesboro, AR.				
5	Does bidder meet all dump truck and bed specifications? Yes _____ No _____ If no, clearly list and define differences on a separate sheet.				
6	Attached equipment list with names and part numbers is for reference.				
7	Bidder should put total bid price on this sheet. Total bid price is \$ _____				
8	Bidder shall list purchase price per unit here. \$ _____				

EXECUTION OF BID

Date _____

We, the undersigned, have read all the requirements set forth in this bid proposal including specifications, instructions, conditions, and pertinent information regarding the articles being bid on, and we agree to furnish articles at the prices stated.

Arkansas Use Tax Register No. _____

Bidder _____ Address _____

(Person Authorized to Sign Bids) Title _____

UNSIGNED BIDS WILL BE REJECTED

BIDS ARE SUBJECT TO REJECTION UNLESS SUBMITTED ON THIS FORM

NOTICE TO BIDDERS, SEE REVERSE SIDE OR ATTACHMENTS FOR INSTRUCTIONS AND CONDITIONS.

**CRAIGHEAD COUNTY
JONESBORO, ARKANSAS
CONDITIONS OF BIDDING**

Compliance with the following conditions is necessary for consideration of this bid.

- 1 Signature-This bid must be signed with the firm name and by an authorized officer, employee or agent.
- 2 Sales Tax-Should be shown in the bid price and added by the vendor to the invoice billing to the County.
Contractors are to include all costs into the bid price, including applicable taxes.
- 3 Freight and other delivery charges-to destination at designated County facility in the County must be included in bid.
Charges may not be added after the bid is opened.
- 4 Discounts-Show rate, total amount, and latest day any discounts will be allowed after receipt of article and invoice,
otherwise County will deduct allowed discount when payment is made.
- 5 Firm Price-All prices quoted will remain firm for at least 30 days from date of bid, unless otherwise specified
by the County or bidder
- 6 Tax Exempt-Craighead County is exempt from State sales tax on self propelled equipment and motor vehicles.
Example: Motor graders, excavators, dozers, dump trucks, pickup trucks, etc.
- 7 Identical Bids-In the event of two or more identical low bids, the contract may be awarded arbitrarily or for
any reason to any of such bidders, or split in any proportion between the said two or more bidders at discretion of the County.
- 8 Clean up-Complete cleanup and proper disposal of any and all job related items is considered to be a part of any
contract let by Craighead County.
- 9 Ambiguity in bid-Any ambiguity in any bid as the result of omission, error, lack of clarity or non-compliance
specifications, instructions, and all conditions of bidding shall be construed in the light most favorable to the County
- 10 Construction
A. When requested, the Contractor is to supply the County with evidence of having and maintaining proper and
specifically Workman's Compensation Insurance in accordance with the laws of the State of Arkansas,
Public Liability, and Property Damage. All premiums and cost shall be paid by Contractor. In no way will the
County be responsible in case of accident.
B. A Performance Bond equaling the total amount of any bid exceeding \$50,000 must be provided for
erection of any public building, public structure, or public improvement(Pursuant to Arkansas Code 18-44-503.)
- 11 The County reserves the right to reject any and all bids, accept in whole or in part, to waive informalities in bids
received, to accept bids on materials or equipment with variations from specifications in those cases where efficiency
of operation will not be impaired, and unless otherwise specified by bidder, to accept any item in the bid. If unit prices
and extensions thereof do not coincide, the County may accept the bid for the lesser amount whether reflected
by extension or by the correct multiple of the unit price.

INSTRUCTIONS TO BIDDERS

(Please read carefully)

- 1 Submit bid on bid form attached or reverse side of this sheet.
- 2 Address all bids to: Purchasing Director, Craighead County Judge's Office, 511 Union St.; Suite 119,
Jonesboro, Arkansas 72401 and make certain to indicate identifying bid number on the outside of bid envelope.
- 3 DO NOT include Federal Excise Tax in bid. County will furnish exemption certificate.
- 4 Sate Manufacturer, Brand Name, Model, etc. for each item bid on.
- 5 Samples of items, when required must be furnished free, and, if not called for within 30 days from date of
bid opening, will be disposed of by the County
- 6 Bids received after stated time will not be considered.
- 7 Be sure and read all conditions and verify amounts before submitting bids. No changes or additions will be
allowed after submission.
- 8 Guarantees and warranties should be attached as a part of the bid, as they may be a consideration in awarding contract.
- 9 Delivery or contract completion time is to be shown, as this date may, where time is of the
essence, determine the contract award.
- 10 Additional information may be obtained from the Purchasing Department.

THE COUNTY RESERVES THE RIGHT TO ACCEPT PART OR ALL OF ANY SPECIFIC BID OR BIDS

AND TO ACCEPT BID WITH OR WITHOUT TRADE-IN, AND REJECT ANY AND ALL BIDS.

General								
A	Trucks (automatic transmissions) and dump beds shall be the latest year model in current production with proven performance by manufacturer and shall meet all federal emissions and all other EPA regulations.(Specify year model)							
B	Note: Part of specifications may be Freightliner specific. Please bid equal equipment.							
C	Note: Part of specifications may be Godwin EL series specific. Please bid equal equipment.							
VEHICLE AND DUMP BED SPECIFICATIONS								
F	Dump Bed Specifications (Beds being offered shall be equal to the following specifications)					Meet Specifications		
						Yes	No	
1	R/S Godwin Truck Body Company Model EL 16052311 (Ox Body Stampede)							
2	Elliptical floor, length 192, Pivot 180 degrees, Inside width 86, Side height 52.							
3	Custom single acting hoist, Electric Tarp system-6200.							
4	6" diameter cylinder rod(3) stage cylinder with 2000 PSI							
5	Hoist lifting capacity 56,540 lbs. (28 ton)							
6	140" cylinder stroke							
7	50 degree dump angle							
8	High lift gate (6') opening discharge							
9	16 Cubic yard capacity							
10	Fender bottom rail 10 gauge, Wood Board gusset height 8", Bulkhead 74.							
11	All Hydraulics, All safety features, flaps, lights,							
12	Air shift PTO							
13	Asphalt apron, Deck 1/4" AR450, Sides 3/16" AR450, Rear post material 1/4" high tensile							
14	Air operated tailgate, High lift, Height 56, Material, 3/16" hardox AR450, air operated controls.							
Vehicle Configuration								
1	114SD CONVENTIONAL CHASSIS							
2	SPECIFY MODEL YEAR							
3	SET FORWARD AXLE - TRUCK							
4	TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK							
5	FREIGHTLINER LEVEL II WARRANTY							
6	EXPECTED FRONT AXLE(S) LOAD : 18000.0 lbs.							
7	EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs.							
8	EXPECTED PUSHER AXLE(S) LOAD : 12350.0 lbs.							
9	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 76350.0 lbs.							
10	EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs.							
11	DD13 12.8L 450 HP @ 1800 RPM, 2080 GOV RPM, 1650 LB/FT @ 1100 RPM							
12	2010 EPA/CARB EMISSION CERTIFICATION							
13	DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE							
14	(3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES							
15	POSITIVE AND NEGATIVE POSTS FOR JUMPSTART MOUNTED NEAR/ON BATTERY TRAY/BOX							
16	ZF-SACHS 15-1/2 INCH TWIN XTEND ULTRA SOFT DAMPER CERAMIC CLUTCH							
17	TORQUE LIMITING CLUTCH BRAKE							
18	ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING							

19	BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE					
20	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM					
21	JACOBS COMPRESSION BRAKE					
22	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH LH B-PILLAR MOUNTED VERTICAL TAILPIPE					
23	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH					
24	BRIGHT UPPER STACK(S)					
25	13 GALLON DIESEL EXHAUST FLUID TANK					
26	BORG WARNER (KYSOR) REAR AIR ON/OFF ENGINE FAN CLUTCH					
27	DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR					
28	1500 SQUARE INCH ALUMINUM RADIATOR					
29	DELCO 12V 39MT+ HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH					
30	ALLISON AUTOMATIC 4500 RDS TRANSMISSION OR EQUIVALENT					
31	MFS-18-133A 18,000# FL1 SINGLE FRONT AXLE					
32	MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES					
33	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS					
34	TRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR					
35	ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE					
36	18,000# TAPERLEAF FRONT SUSPENSION					
37	FRONT SHOCK ABSORBERS					
38	RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE					
39	4.30 REAR AXLE RATIO					
40	MXL 176N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES					
41	MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES					
42	DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES					
43	(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE					
44	MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES					
45	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)					
46	TUFTRAC 46,000# 2-STAGE REAR SPRING SUSPENSION					
47	TUFTRAC STANDARD RIDE HEIGHT					
48	56 INCH AXLE SPACING					
49	FORE/AFT AND TRANSVERSE CONTROL RODS					
50	HENDRICKSON PARALIFT ULTRA HLUC2 COMPOSITITE 13,200# AIR LIFT STEERABLE PUSHER SUSPENSION WITH HENDRICKSON FF1 AXLE					
51	HENDRICKSON FF1 13,200# PUSHER AXLE INTEGRAL WITH HLU/R-2, HLUC2 SUSPENSIONS					
52	(1) DASH VALVE AND (1) GAUGE FOR SINGLE LIFT AXLE					

53	REVERSE LIFT AXLE WIRING WITH LAST STATE RETENTION WITH IGNITION OFF					
54	AIR PIPING FOR (1) LIFT/NON-LIFT AXLE WITH REGULATOR CHASSIS MOUNTED					
55	MERITOR 15X4 Q+ CAM PUSHER/TAG BRAKES, DOUBLE ANCHOR, FABRICATED SHOES					
56	MERITOR AUTOMATIC PUSHER/TAG SLACK ADJUSTERS					
57	HENDRICKSON HLUC2 13,200# AIR LIFT STEERABLE PUSHER AXLE SUSPENSION					
58	WABCO 4S/4M ABS WITHOUT TRACTION CONTROL					
59	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED THROUGH IGNITION					
60	SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME					
61	5650MM (222 INCH) WHEELBASE					
62	11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI					
63	1/4 INCH (6MM) C-CHANNEL INNER FRAME REINFORCEMENT					
64	HEAVY DUTY SUSPENSION CROSSMEMBER					
65	16.5 INCH CHROME STEEL STRAIGHT BUMPER					
66	100 GALLON/378 LITER ALUMINUM FUEL TANK - LH					
67	GOODYEAR G296 MSA 385/65R22.5 18 PLY RADIAL FRONT TIRES					
68	GOODYEAR G288 11R22.5 16 PLY RADIAL REAR TIRES					
69	GOODYEAR G338 1AD 295/75R22.5 14 PLY RADIAL PUSHER/TAG TIRES					
70	CONMET PRE-SET BEARING ALUMINUM REAR HUBS					
71	ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS					
72	ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS					
73	ACCURIDE 29644A 22.5X8.25 10-HUB PILOT ALUMINUM DISC PUSHER/TAG WHEELS					
74	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB					
75	AIR CAB MOUNTS					
76	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE					
77	CHROMED HOOD MOUNTED AIR INTAKE GRILLE					
78	DUAL 26 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS ROOF MOUNTED					
79	DUAL HORN SHIELDS					
80	HALOGEN COMPOSITE HEADLAMPS WITH BRIGHT BEZELS					
81	DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE					
82	DOOR MOUNTED MIRRORS					
83	LH AND RH 8" BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS					
84	TINTED DOOR GLASS LH AND RH WITH TINTED OPERATING WING WINDOWS					
85	RH AND LH ELECTRIC POWERED WINDOWS					
86	INTERIOR CONVENIENCE PACKAGE WITH CB PROVISION					
87	2-1/2 LB. FIRE EXTINGUISHER					
88	HEATER, DEFROSTER AND AIR CONDITIONER					

89	CAB INSULATION					
90	SOLID-STATE CIRCUIT PROTECTION AND FUSES					
91	LH AND RH ELECTRIC DOOR LOCKS					
92	(1) 12 VOLT POWER SUPPLY IN DASH					
93	TRIANGULAR REFLECTORS WITHOUT FLARES					
94	BOSTROM TALLADEGA 910 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH AIR LUMBAR					
95	HIGH BACK NON SUSPENSION PASSENGER SEAT					
96	LH AND RH INTEGRAL DOOR PANEL ARMRESTS					
97	CLOTH DRIVER SEAT COVER					
98	CLOTH PASSENGER SEAT COVER					
99	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN					
100	97 DB BACKUP ALARM					
101	ELECTRONIC CRUISE CONTROL WITH SWITCHES ON AUXILIARY GAUGE PANEL (B DASH PANEL)					
102	ODOMETER/TRIP/HOUR/DIAGNOSTIC/VOLTAGE DISPLAY: 1X7 CHARACTER, 26 WARNING LAMPS, DATA LINKED, ICU3					
103	DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1939, LOCATED BELOW DASH					
104	2 INCH ELECTRIC FUEL GAUGE					
105	FUEL FILTER RESTRICTION INDICATOR					
106	DUAL REAR AXLE TEMPERATURE GAUGES FOR TANDEM AXLES					
107	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE					
108	ENGINE OIL TEMPERATURE GAUGE					
109	2 INCH TRANSMISSION OIL TEMPERATURE GAUGE					
110	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY					
111	ELECTRIC ENGINE OIL PRESSURE GAUGE					
112	AM/FM/WB RADIO WITH FRONT AUXILIARY INPUT					
113	DASH MOUNTED RADIO					
114	ELECTRONIC 3000 RPM TACHOMETER					
115	TRAILER HAND CONTROL BRAKE VALVE					
116	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE					
117	PAINT: ONE SOLID COLOR					
118	CAB COLOR (EQUAL TO L5495EB ULTRA RED PEARL METALLIC ELITE BC)					
119	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT					
120	Weight Front 9324 lbs. Weight Rear 9694 lbs. Total Weight 19,018 lbs.					